A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Curtain tension

What is the function?

- Stabilizes curtain and allows door to run smoothly
- Reduces wrinkles on doorblade
- Increased wind load capability
- Supports the crash function, aligns the bottom beam after crash

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace according to door type related specification sheet

Can I also replace it earlier?

- Yes, if the dimension between the spring windings are not the same
- If the ropes fray
- Abrasion of pulleys
- Knots in rubber cable

How do they wear?

During the lifetime of the curtain tension there will be wear and tear due to:

- The force of the springs and the rubber cables is lowered over time
- Corrosion of the spring

Ropes

- Fray due to movement over the pulleys. Forces on ropes due to high number of crashes

Pulleys

- Friction of rope over pulley. Drag force of the rope
- Ageing of bearing due to corrosion / abrasion

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

- There could be damage to other parts of the door; when the rope/spring breaks, the curtain will not run smoothly
- Higher costs for repair
- Closing under high wind load is reduced or not possible which can lead to a loss of current wind class
- No full crash function on certain products / incr. swing amplitude of bottom beam after crash (RR600/450/355)
- Increased noise during operation
- An overbalanced door can lead to crash into upper end position in case of use of emergency lever

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PL.MAP/DEU-EN-1.0/1504

Maintenance & Modernization