WORK ORDER

Client :		PO Number:	AMU-1211	W. O. No-	SO/22-23/035
AMULYA TRADERS		PO Dated :	19-08-2022	W. O. Date	20-08-2022
Address:		PO Received Date:	19-08-2022	Sales Co ordinator	Shailesh
Maple Leaf , Flat No 1 & 2,Sr 18/B ,Behind Mega Center Hadapsar, Pune -411013		Ref. Quotation:	SQA.22.23.0076R2	Front Sales Person	Shailesh

Dispatch Address:

John Deere India Pvt Ltd
Gat No. 164,165/1 & 2, 166-167 & 271-291,
Sanaswadi, Pune - 412208

A Technical Terms:

Sr. No	Description of Goods	Technical Details	UOM	Qty.	Supply Rate	Installation Rate	Total Amount	Dwg. Approval Status
1	ALU - High Speed Rolling Shutter (100% European Components) with Radar and Loop Detector on both sides. Size : Width 3000 mm X Height 4000 mm	Sheet 2	Nos	2			-	Pending
						Total	-	

Non standard items/extra requirement, if any:

B Commerical Terms:

1	Payment Terms:	50 % advance and 50% after completion.		
2A	Delivery Date as per PO:	10-12 weeks from Purchase Order	2B. Required Delivery Date:	
3A	Transportation Scope:	Included	3B. Transportation Charges:	
4	P&F Charges:			
5A	Loading Scope:	NIHVA Scope	5B. Loading Charges:	
6A	Unloading Scope:	CLIENT Scope	6B. Unloading Charges:	
7A	Lifting Equipments Scope:	CLIENT Scope	7B. Available Lifting Equipments:	
8	Warranty:	12 months from the date of supply.		
9A	Height arrangement Scope:	CLIENT Scope	9B. Available Equipments for working at Site:	
10	Electricity Supply:	CLIENT Scope		
11	GST:	18%		
12A	Installation Scope:	NIHVA Scope	12B. Installation required date:	
13	Mode of import:	NA		
14	HSS:	NA		
15	Documentation Required:	Standard Handover Documents ,Material test Certificates		
16A	Total site visits required:		16B. Site visit charges:	

Certified that the above work order finalised in presence of:

GM	SALES		Operation	PROJECT	DESIGN	Date & Time
A.K.	V.T.		S.B.	S.M.	M.S	22-08-2022

NIHVA MAKE - High Speed Door - (ALU Speed Door)

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- Patented rubber drive method

Sr. No	Description	Specifications
1	Use	Internal / External Door
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of
3	Opening speed	upto 2 m/s
4	Closing speed	0.7 m/s
5	Security Features	EN 13241-1 Standard
6	Resistance to wind	class 4
7	Curtain	Aluminium 19.0 mm
8	Door Leaf Material /	Polyurethane filled RAL 9006 aluminium lamella
9	Hood Cover	Included
10	Motor Cover	Included
11	Guide Material /	Aluminium Anodized , Painting in any RAL9006 lamalla colour
12	Operator & Control	German Make Motor
13	Connecting Voltage	220V , 1Ph , N
14	Open-Stop-Close	Standard
15	Protection Category	IP 54
16	Power Consumption	0.75 kw Motor
17	Emergency Off Button	Standard
18	Closing Zone	Optical Safety edge, bottom edge sensor
19	External Route	Photocell
20	Emergency Opening	Crank Handle
21	Door Area Monitoring	Radar and Loop detector on both side
22	Window	one row of window