**SKB STORAGE INDUSTRIES SDN. BHD.** (557922-U)
(A Subsidiary of SKB Shutters Corporation Berhad)
Lot 22 Jalan Teknologi, Taman Sains Selangor, Kota Damansara, 47810 Petaling Jaya, Selangor, Malaysi
Tel : (60) 3-6157 2277 (12 lines) Fax : (60) 3-6157 221
website : www.skb-shutters.com
Registered Trademark No. 85/B03843
ISO 9001-2008 CERTIFIED

# Quotation

**Quotation Ref: SKB-1805-378**

**Attn:** Mr.Purva Merwade
**To : Nihva Technology**
**Add :** India.
**email :** nihvacare@nihva.com
**Project : Supply only**

**Date :** 31-May-18
**Quote Validity:** 30 days
**Delivery :** 21 Days after drawing approved and payment.
**Payment Term :** 30% Down payment upon order confirmation.
70% Full payment prior to collection of goods.
**(All deposit made are non-refundable)**
**Price : Supply Ex-Factory in US Dollar**
(Collected by Container Bases (FCL))

**Supply For : SKB 2 hours Fire Rated Steel Insulated Shutte**
**Shutter Slats :** SKB-F7D Double Walled Roll Form Steel with Rockwool Infilled, P/Coat to SKB std RAL colour
**Slat Thickness:** ditto
**Shutter Design :** SKB F7D
**Shutter Guide :** G70
**Bottom Bar :** Steel Insulated Bottom bar
**Weather Seal :** Excluded
**Push Button Switch:** SKB standard
**Operated By :** Motorise 230Volt 50Hz 1P with manual override chain
**Fire Mode :** Fire Shutter will auto close via upon receiving 24VDC Fire Signal

**Standard Specifications:**
Box Covers of Galvanised Finish
Box Frame Standard, Single powder coated.
Standard Installation - Behind R.C. Beam.

For Motor Operated Unit:
Motor comes with one unit push button switch & manual overide.Internal wiring from motor to push button 12 feet away from motor position only.

| No. | Width ( mm ) | Height ( mm ) | Quantity (Units) | Operated By | Unit Price (USD) | Total Price (USD) |
|---|---|---|---|---|---|---|
| 1 | 9600 | 4000 | 1 | SKB 2000 Motor + ERA | 9,477 | 9,477 |
| 2 | 4000 | 4000 | 1 | SKB 1000 Motor + ERA | 4,148 | 4,148 |
| 3 | 3000 | 3000 | 1 | SKB 700 Motor + ERA | 2,594 | 2,594 |
| 4 | 2800 | 2400 | 1 | SKB 500 Motor + ERA | 2,003 | 2,003 |
| 5 | Steel Crate (LCL) | | 4 | | 150 | 600 |
| | | Total Units | 1 | **Total Ex-Factory Price (USD)** | **$** | **18,822** |

***Terms and Conditions :***
(1) ERS = ERS400 Electric Releaser 24VDC; TFU = TFU2 Thermal Fusible Link. Excluded/Optional Upon Request.
(2) Remote Control and bottom safety air sensor are Excluded / Optional Upon Request.
(3) Steel Crate USD150/unit below 6 meter; USD250 above 6 meters for LCL Collection.
(4) Without Windlock, maximum windload is 20 ¬ 30km/hours ; pressure is 6¬9kgs/m2.
(5) SKB Standard Colour, Outdoor: RAL9010 (White) and RAL7025 (Grey) Only.
Shutter shall powder coated minimum 50 micron, and, minimum 20 micron to 50 micron for shutter box.
(6) Shop Drawing supply within 7 days after received Firm Purchase Order.
(7) Buyer is requested to sign and approve the drawing submitted in order to commence fabrications.
(8) All roller shutter offers shall be supplied with Galvanized Steel Guide Rails as standard unless mentioned otherwise in this quot
(9) All motorized roller shutters is designed with Open & Close travel speed of approximately 50mm to 70mm per second as standa
(10) All power point with Terminal or Isolater Switch to be provided by buyer to each motor position, 300mm from motor.
(11) The roller shutters offered with Standard Operation Design. Any extra safety features such as Automatic Reset Device, TFL. Delay Timer Closing, Infra-Red Safety Sensor, Shutter Safety Brake Arrester, Powerless Assisted Lift Up System, PVC Fins Si at Guide Rail, Anti Wind Locking System, DC Power Back Up Motor, Wireless Remote Control System are charged separately request.
(12) All Shutter box Covers shall be of Galvanized surface treated as standard unless indicated separately in writing, signed and ap in the quotation.
(13) All Roller Shutter's Box Cover includes Back & Bottom Galvanised Finishing 0.8mm Thick Steel Covers as standard.
(14) All Roller Shutter are designed for installation Behind Wall or Face Fixed Type as standard. For Between-wall design opening Hanging Steel Angle Installation under floor slab, additional charges is applicable.
(15) Items requested and quoted for powder coating finishing are applicable to slat, bottom bar & shutter box only.
(16) Fabrications is solely based on Approved Shop Drawings Only. No site measurement will be taken. All amendments and modif on items which had commenced fabrication shall be chargeable and written notice is required for the alteration and modificatic
(17) All SKB Roller Shutters includes a warranty of 12 months for manufacturing defects from date of Exwork. Defect arrising from negligence or vandalism is not covered under warranty claims and are chargeable to recover its condition.
(18) Product Warranty is Void if any modification is carried out by buyer and it does not include any Lightning Strike or act of God d to the electrical system of the controls.
(19) Once production commenced, any changes by buyer shall treat as variation order and must inform SKB by written instruction f buyer with company letter head or personal order with IC No. and Name with signature.
(20) This quotation is subject to the terms & conditions as specified above and in 0
(21) Delivery Date shall be given only after buyer signed and approved the submitted drawing for Production.

SKB Storage Industries Sdn Bhd
**Marilyn Lai**
email:marilyn@skb.com.my
Overseas Sales Department

Buyer's Signature & Date