High Performance Door Rapid Roll® 392 (High Speed Door)



Door type	RR392	PL. indicate your requirement
Description	Flexible High Performance Door, opening in vertical direction, for interior and exterior use	
Side frames	Bended galvanized steel profiles. All steel parts galvanized, springs for curtain tension and counterbalance in the side frame	
Door curtain	Transparent PVC with vertically applied side reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar RAL 3002).	
Wind protection	Through wind taps on the door curtain	
Wind resistance	Class 2 (EN 12424)	
Bottom profile	Anodized aluminum	
Drive unit	Gear motor	
Protection	IP 55	
Control system	ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC	
Supply voltage	ACS 50: 3L(N)PE/230/380/400/415V; 50 Hz Transformer necessary for 440/480/500V; 50 Hz	
Safety devices	Electrical safety contact edge, stationary safety photocell, and drop down protection by integrated balancing system.	
Manual activation	By releasing the brake at ground level. Opening/closing speed: up to max. 0.8 / 0.8 m/s	
Size max	(DW x DH) 6000 x 6000 mm	
Make	ALBANY Rapid Roll® 392	
Options		

Cover	➢ Top roll cover made of galvanized steel ➢ Motor cover made of plastic, colour grey (similar RAL 7040)	
Door curtain (alternatively)	➢ PVC with coloured reinforcement stripes ➢ Beige (similar RAL 1014), ➢ Yellow (similar RAL 1021), ➢ Orange (similar RAL 2011), ➢ Green (similar RAL 6018), ➢ White (similar RAL 9016) or ➢ Grey (similar RAL 7035). ➢ PVC with silicone-free reinforcements stripes ➢ RollTex® Plus (fabric stiff across the grain) – colour ➢ Blue (similar RAL 5002), ➢ Orange (similar RAL 2009) or ➢ Grey (similar RAL 7001) ➢ Window DWxDH 500x700 mm (only for RollTex® Plus curtain) ➢ Window DWxDH 700x500 mm (only for RollTex® Plus curtain)	
Control system (alternatively)	Frequency converter control system MCCVectorControl, based on vector control system including boost function for start-up, ➢ (Open/close) up to max. 2.2/0.9 m/s, ➢ Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz, ➢ Transformer necessary for 220/230/500V; 50/60 Hz	
Miscellaneous	➢ Knock out function with sensor ➢ Chain drive ➢ Extended flexible seal ➢ Actuators ➢ Additional safety devices	
Delivery	Installation incl. wiring	

91 8551008333 ☎ +91 20 66304033

Email: marketing@nihva.com