ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems Germany GmbH - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Auftrags-Nr./Order No 30959175 Datum/Date 2024-07-05 Referenz/Reference Mr. Kurhade Verkäufer/Salesman

Kunden-Nr./Customer No.	Innendienst/Internal department	Versandart/Way of delivery
1059669	Olga Ziebart +49.2941.766. x 746	
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA-708	FCA / Pilzen incl.standard versand / PickUP SEA

Lieferadresse/Delivery address	Nr. Lieferadresse/Delivery address No.	Zahlungsbedingungen/Terms of payment
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India		Due Net 30

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price
10	AD_RR300_PLUS	ASSA ABLOY RR300 Plus	2024-08-05	1.000	ST	6,623.00	6,623.00

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.000 mm
Door control system	MCC (7110)
AAES Inside type	No IoT Gateway
MCC(7110) type	MCC in cabinet 500x500mm
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum

ASSA ABLOY Entrance Systems Germany GmbH
Am Mondschein 25
D-59557 Lippstadt

Phone:+49 (0) 2941/766-0
Service: +49 (0) 2941/766-555
service.de.entrance@assaabloy.com
www.assaabloyentrance.de

Commerzbank AG
SWIFT: COBADEFFXXX
IBAN Nr.: DE 09 20040000 0402 4014 00
Reg court Hannover: HRB 217498

VAT No.: CZ687164472
Management:
Marina Lindholm
Aron Literski

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
Motor cover	Motor cover made of plastic, grey colour similar to RAL 7040
Top roll cover	Top roll cover made of aluminium
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Actuator 1	Double loop detector without wire and plastic sealing mass
Function actuator 1	Open by impulse / Close after time
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

20 AD_RR300_PLUS ASSA ABLOY RR300 Plus 2024-08-05 1.000 ST 6,623.00 6,623.00

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.000 mm
Door control system	MCC (7110)
AAES Inside type	No IoT Gateway
MCC(7110) type	MCC in cabinet 500x500mm
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
Motor cover	Motor cover made of plastic, grey colour similar to RAL 7040
Top roll cover	Top roll cover made of aluminium
MCC-display position	Wall mounted

ASSA ABLOY Entrance Systems
Germany GmbH
Am Mondschein 25
D-59557 Lippstadt

Phone:+49 (0) 2941/766-0
Service: +49 (0) 2941/766-555
service.de.entrance@assaabloy.com
www.assaabloyentrance.de

Commerzbank AG
SWIFT: COBADEFFXXX
IBAN Nr.: DE 09 20040000 0402 4014 00
Reg court Hannover: HRB 217498

VAT No.: CZ687164472
Management:
Marina Lindholm
Aron Literski

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Actuator 1	Double loop detector without wire and plastic sealing mass
Function actuator 1	Open by impulse / Close after time
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

30 AD_RR300_PLUS ASSA ABLOY RR300 Plus 2024-08-05 1.000 ST 7,062.00 7,062.00

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.800 mm
Daylight height	3.500 mm
Door control system	MCC (7110)
AAES Inside type	No IoT Gateway
MCC(7110) type	MCC in cabinet 500x500mm
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
Motor cover	Motor cover made of plastic, grey colour similar to RAL 7040
Top roll cover	Top roll cover made of aluminium
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	1.000 mm

ASSA ABLOY Entrance Systems
Germany GmbH
Am Mondschein 25
D-59557 Lippstadt

Phone:+49 (0) 2941/766-0
Service: +49 (0) 2941/766-555
service.de.entrance@assaabloy.com
www.assaabloyentrance.de

Commerzbank AG
SWIFT: COBADEFFXXX
IBAN Nr.: DE 09 20040000 0402 4014 00
Reg court Hannover: HRB 217498

VAT No.: CZ687164472
Management:
Marina Lindholm
Aron Literski

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Mains connection cable length	4.500 mm
Combibox cable length	4.500 mm
Actuator 1	Double loop detector without wire and plastic sealing mass
Function actuator 1	Open by impulse / Close after time
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	4300X480X400
Dimension packing 2 LxWxH	800X600X580

40	AD_RR300_PLUS	ASSA ABLOY RR300 Plus	2024-08-05	1.000	ST	6,560.00	6,560.00

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2.500 mm
Daylight height	3.500 mm
Door control system	MCC (7110)
AAES Inside type	No IoT Gateway
MCC(7110) type	MCC in cabinet 500x500mm
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
Motor cover	Motor cover made of plastic, grey colour similar to RAL 7040
Top roll cover	Top roll cover made of aluminium
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	1.000 mm
Mains connection cable length	4.500 mm
Combibox cable length	4.500 mm
Actuator 1	Double loop detector without wire and plastic sealing mass
Function actuator 1	Open by impulse / Close after time
Documentation language	English

ASSA ABLOY Entrance Systems
Germany GmbH
Am Mondschein 25
D-59557 Lippstadt

Phone:+49 (0) 2941/766-0
Service: +49 (0) 2941/766-555
service.de.entrance@assaabloy.com
www.assaabloyentrance.de

Commerzbank AG
SWIFT: COBADEFFXXX
IBAN Nr.: DE 09 20040000 0402 4014 00
Reg court Hannover: HRB 217498

VAT No.: CZ687164472
Management:
Marina Lindholm
Aron Literski

ASSA ABLOY

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

Warenwert/Value of goods		26,868.00
Summe/Total	EUR	26,868.00

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
ASSA ABLOY Entrance Systems Germany GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems
Germany GmbH
Am Mondschein 25
D-59557 Lippstadt

Phone:+49 (0) 2941/766-0
Service: +49 (0) 2941/766-555
service.de.entrance@assaabloy.com
www.assaabloyentrance.de

Commerzbank AG
SWIFT: COBADEFFXXX
IBAN Nr.: DE 09 20040000 0402 4014 00
Reg court Hannover: HRB 217498

VAT No.: CZ687164472
Management:
Marina Lindholm
Aron Literski