ASSA ABLOY Machine Protection Door - RP300 - Without MCC Vector Control

Sr .No.	Specification	ASSA ABLOY Machine Protection Door - RP300 - Without MCC Vector Control
1	**Door version:**	Vertical Rapid Roller Door for machine protection.
2	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.
3	**Door blade:**	PVC material transparent with reinforcement stripes silicone-free in red (RAL 3002).
4	**Bottom beam**	Aluminium anodized.
5	**Drive unit:**	Drive unit IP 55, either RH or LH as an option, with control cable (standard length = height of door)
6	**Opening / closing speed:**	Approx. max. 2,0 / 1,2 m/s
7	**Control system:**	MCC Frequency converterVector Control for opening/closing speed up to 2,4 / 1,4 m/s for door with safety contact edge, protection IP 55. Without display, interface card delivered separately, including power- and interface cable, with main switch in separate box. **(Not Included as per client request)**
8	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz
9	**Safety features:**	Safety edge with cable chain integrated in side frames, door line photocell (Transmitter / Receiver) inside side frames, emergency crank and mechanical drop-down protection.
10	**Safety limit switch:**	1 Schmersal safety limit switch PL e EN ISO 13849-1, SIL 3 EN 62061 on drive side integrated in the side frame to save space.