ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No** 30767181 **Datum/Date** 2019-11-14 **Referenz/Reference** Mr. Marne **Verkäufer/Salesman**

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Olga Ziebart +49.2941.766. x 746	Sea freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA 466	FCA / Hemau, Germany / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Versanddatum** **Ship date**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
10	**AD_DIVIROLL**	**ASSA ABLOY RP300 Wide**	**2019-12-17**	**1.000**	**ST**	**6,348.00**	**6,348.00**

Serien-Nr. 2640000325

Daylight width	5.000 mm
Daylight height	3.000 mm
Side frame extension X-Level	150 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Extended sealing lip	Sealing lip elongated by 150 mm
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648
Reference no. special door 02	318901
Warranty	1 Year
Dimension packing 1 LxWxH	5500X480X400
Dimension packing 2 LxWxH	800X600X580

special references
****
REF: 319648 according to VW standard
REF: 318901 contact edge instead of pre-running photocell
.

20 AD_DIVIROLL ASSA ABLOY RP300 Wide 2019-12-17 1.000 ST 5,777.00 5,777.00

Serien-Nr. 2640000326

Daylight width	3.500 mm
Daylight height	3.620 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

	monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

special references
****
REF: 319648 according to VW standard
.

30 AD_RP300_C ASSA ABLOY RP300 2019-12-17 1.000 ST 4,300.00 4,300.00

Serien-Nr. 91000067751

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	3.300 mm
Customer specification	317933 RP300 VW
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	220934
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X370

special references
****
REF: 317933 according to VW standard
REF: 220934 shaft cover from bearing side for RP300
.

40 AD_DIVIROLL ASSA ABLOY RP300 Wide 2019-12-17 1.000 ST 6,348.00 6,348.00

Serien-Nr. 2640000327

Daylight width	5.000 mm
Daylight height	3.000 mm
Side frame extension X-Level	150 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Extended sealing lip	Sealing lip elongated by 150 mm
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648
Reference no. special door 02	318901
Warranty	1 Year
Dimension packing 1 LxWxH	5500X480X400
Dimension packing 2 LxWxH	800X600X580

special references
****
REF: 319648 according to VW standard
REF: 318901 contact edge instead of pre-running photocell
.

50 AD_DIVIROLL ASSA ABLOY RP300 Wide 2019-12-17 1.000 ST 5,777.00 5,777.00

Serien-Nr. 2640000328

Daylight width	3.500 mm
Daylight height	3.620 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. / item	Produkt / Product	Beschreibung / Description	Versanddatum / Ship date	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

special references
****
REF: 319648 according to VW standard
.

60 AD_RP300_C ASSA ABLOY RP300 2019-12-17 1.000 ST 4,300.00 4,300.00

Serien-Nr. 91000067752

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	3.300 mm
Customer specification	317933 RP300 VW

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	220934
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X370

special references
****
REF: 317933 according to VW standard
REF: 220934 shaft cover from bearing side for RP300
.

70 AD_DIVIROLL ASSA ABLOY RP300 Wide 2019-12-16 1.000 ST 6,348.00 6,348.00
Serien-Nr. 2640000329

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Daylight width	5.000 mm
Daylight height	3.000 mm
Side frame extension X-Level	150 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Extended sealing lip	Sealing lip elongated by 150 mm
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648
Reference no. special door 02	318901
Warranty	1 Year
Dimension packing 1 LxWxH	5500X480X400
Dimension packing 2 LxWxH	800X600X580

special references

****

REF: 319648 according to VW standard

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

REF: 318901 contact edge instead of pre-running photocell
.

80	**AD_RP300_C**	**ASSA ABLOY RP300**		**2019-12-17**	**1.000**	**ST**	**4,300.00**	**4,300.00**

Serien-Nr. 91000067753

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	3.300 mm
Customer specification	317933 RP300 VW
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	220934
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X370

special references
****

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

REF: 317933 according to VW standard
REF: 220934 shaft cover from bearing side for RP300
.

90 AD_DIVIROLL ASSA ABLOY RP300 Wide 2019-12-17 1.000 ST 6,348.00 6,348.00

Serien-Nr. 2640000330

Daylight width	5.000 mm
Daylight height	3.000 mm
Side frame extension X-Level	150 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	1,7 m/s
Max. Closing Speed	1,0 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Extended sealing lip	Sealing lip elongated by 150 mm
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Special door	Yes
CE - Sign	Yes
Reference no. special door 01	319648

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Reference no. special door 02 318901
Warranty 1 Year
Dimension packing 1 LxWxH 5500X480X400
Dimension packing 2 LxWxH 800X600X580
special references
****
REF: 319648 according to VW standard
REF: 318901 contact edge instead of pre-running photocell
.

100 AD_RP300_C ASSA ABLOY RP300 2019-12-17 1.000 ST 4,300.00 4,300.00

Serien-Nr. 91000067754

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	3.300 mm
Customer specification	317933 RP300 VW
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	Without photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm with yellow frame
Window Quantity	1
Height:bott.edge to bott.prof.	1.250 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	4.500 mm
Mains connection cable length	4.500 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Prepared for Schmersal switch 1 side
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Wiring plan English
MCC display language English
Special door Yes
CE - Sign Yes
Reference no. special door 01 220934
Warranty 1 Year
Dimension packing 1 LxWxH 4500X480X400
Dimension packing 2 LxWxH 800X600X370
special references
****
REF: 317933 according to VW standard
REF: 220934 shaft cover from bearing side for RP300
.

110	**D8820R0040**	**MCC display with bracket Zn**	**2019-12-16**	**10.000**	**ST**	**373.18**	**3,731.79**
	MCC display with side frame bracket Zn						

Warenwert/Value of goods **57,877.79**

Summe/Total **EUR** **57,877.79**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye