HICON DAN-doors
DOORS TO THE WORLD

SLIDING DOORS CHILL/FREEZE

TECHNICAL DESCRIPTION:

Door Type	-	Horizontal Sliding Door (Chiller and freezer application)
Door Blade	-	0.6 mm galvanized steel – PVC-coated - Food safe available in the RAL colours:
Thickness:	-	60 mm, 80mm, 100 mm,120mm and 150 mm
Insulation:	-	High insulating, polythan - free foam
Frame		2 mm anodized aluminium (when freeze application, max -25˚, however, never to be used for blast freeze doors)
Insulation:	-	The frame is always insulated.
Sliding Rails:	-	Anodized aluminium.
Rollers:	-	The rollers are made of POM (nylon). The roller brackets, the stud bolt, the washer and the nuts are made of SS.

108, 109 Toy City Udyog Kendra Ecotech III Greater Noida 201306

doors@hicon.co.in

HICON DAN-doors
DOORS TO THE WORLD

SLIDING DOORS CHILL/FREEZE

Recess: - The sliding rail is supplied with recess blocks to ensure hermetic closing towards frame and floor.

Gaskets: - Rubber quality approved for use in the food industry. The gaskets are fitted into anodized aluminium profiles.

Handles: -

Face side:	If manual - Solid stainless steel DAN-doors handle fitted on edge of door blade. If automatic – Bow handle
Rear side:	Flush fitted stainless steel handle in a nylon holder manual as well as automatic.

Bottom Guide: - The bottom guide rail and the bottom guides are manufactured in salt water resistant anodized aluminium. The bottom guides are supplied with solid nylon bushes.

Min/ Max size

1 leaf: W x H: 1000 x 2000 / W: 3200 x 3600
2 leaf: W x H: 1600 x 2000 / W: 6000 x 3600

FREEZER DOORS :

Heating Arrangement: - Supplied with heating cables in both frame/threshold and door blade. The threshold which is manufactured of anodized aluminium is to be placed into the floor.

Alternatively, the door can be supplied without a threshold, if supplied with extra heating at bottom of the door blade.

The heating cables on the door blade are fitted

108, 109 Toy City Udyog Kendra Ecotech III Greater Noida 201306

doors@hicon.co.in

into aluminium profiles with the gaskets.

The heating cables are terminated in a connection box for connection to a 230 V / 50 Hz supply (Connection to other voltage is possible.) Power consumption per meter for this heating cable is approx. 30 W.

Remark - Heating in the floor around the door is always recommended.

ADDITIONAL EQUIPMENT:

Locks: - Cylinder lock with emergency opening device in black PEHD 1000 nylon and stainless steel. Heating in locks for freezer doors.
(To be locked from face side or rear side.)

Padlock fitting with or without emergency opening device in black PEHD1000 nylon and stainless steel.(To be locked from face or rear side)

Window: - Standard sizes:

- 150 x 300 mm
- 400 x 600 mm
- 500 x 600 mm

Frame: - Available in anodized aluminium

or

Stainless steel - AISI 304.

Window: - Min. 2-layer thermo glass

Sliding Rail: - Stainless steel - AISI 304.

Automation: - Can be supplied with tooth belt automation.

(Further information to be found in the paragraph about automation for sliding doors)

HICON DAN-doors
DOORS TO THE WORLD

SLIDING DOORS CHILL/FREEZE

Sliding Rail Protection: - Identical to door blade

Emergency Hatch/Door:
- Hatch standard size : 600 x 1000 mm
- Door standard size : 800 x 1800 mm

Kick Plates: - Door width x height 300 mm (standard)

or

Door width x height 800 mm (max)

Blast Freeze: - Freezer room doors can be manufactured as blast freezer doors.

108, 109 Toy City Udyog Kendra Ecotech III Greater Noida 201306

doors@hicon.co.in