Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR300

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR300

Product group	Description	250.000 cycles or 3 years	300.000 cycles	300.000 cycles or 5 years	500.000 cycles	500.000 cycles or 5 years	1.000.000 cycles	1 year	5 years	10 years	wear / tear related
Actuators	Photocell receiver re / tr									●	
	Reflection photocell, 15m cable									●	
	Reflection photocell, 8m cable									●	
Safety	Wireless safety system receiver					●					
Curtain	Curtain										●
	Set of wind tabs				●						
Top roll	Flange bearing				●						
	Top roll				●						
Bottom profile	Battery for wireless safety system							●			
	Contact strip								●		
	FlexEdge			●							
	Rubber profile with contact strip								●		
	Spiral cable		●								
	Wireless safety system transmitter					●					
Crash	Rope, 3,2 mm, L=9500 mm								●		
	Sliding part complete for crash-version		●								
	Switch for crash									●	
Sliding/Guiding	Sliding part				●						
Drive unit	Drive unit - contactor control				●						
	Drive unit - frequency converter						●				
	limit switch block, 6 contacts incl. Cams									●	
Brake	Brake - contactor control				●						
	Brake - frequency converter						●				
Encoder	Encoder									●	
	Limit switch, digital	●									

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

Technical data subject to change without notice
© ASSA ABLOY Entrance Systems AB PL.MAN/RR300/DEU.EN-1.1/1504 / 64 100 477

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization