PSTM ENGINEERING

Office &Works- Sai Industrial Estate, Plot No 2, Survey No – 59/1, Chowisawadi, Charoli, Pune – 412105, PH – 9503943176, Email - sales@pstmengineering.com

---

Quotation

REF/PSTM/202122/RP21 **Date: December 14, 2021.**

Product: Automatic six Head Liquid filling line with Airjet Cleaning system, inner plug and four Head Screw capping machine , Filling Range: 100 Ml to 1000 ml. Type of Bottles: Round Pet Bottles

Reference: - Your discussions with undersigned.

Kind attention: - Mr. Kumbhar Sir

Technical Specification for GMP Model VF-1000 Automatic Six Head Liquid Filling with Airjet Cleaning, Inner Plug Pressing and Four head screw capping Machine.

1.0	**Machine**	GMP Model Auto Six Head Juice Filling Line with four head screw capping machine.
2.0	**Range**	From 100 ml. to 1000 ml. Depending upon specific gravity, Viscosity and flow properties of the Product.
3.0	**Out-put in BPM (Bottles per minute)**	42 to 48 BPM (1200 ml.) depending upon Product Characteristics, its fill weight, specific gravity of the product, its flow properties.
4.0	**Suitability**	Any type of Bottle, Glass bottles, Metal tin, HDPE Bottles, Pet Bottles
5.0	**Power**	Three Phase 440 V AC
6.0	**Pneumatics**	SMC/Festo.
7.0	**Power**	440 V AC, 3 Phase, 50 Hz, 5.0 Hp.
8.0	**PLC**	Delta with colour HMI Touch screen
9.0	**Electricals**	Siemens Make.
10.0	**Contact Part**	Stainless Steel SS 316.
11.0	**Mounting**	On Ant vibration mounting.
12.0	**Net Weight**	1800 kg (approx).
13.0	**Max. dia. Of Bottle**	120 mm.
14.0	**Max. Height of Bottle**	75 mm to 250 mm.
15.0	**Overall Dimension**	12.0 Mtr. Long X 3000 mm Deep X2500 mm height.
16.0	**Dosing Unit**	Volumetric linear piston filler (Pneumatic).
17.0	**Accuracy**	For fill 100 ml to 1000 ml will be 1.0 to 2.0%. Actual accuracy depends upon type of product and consistency in its flow characteristics.

PRICE OF THE ABOVE MACHINE IS AS UNDER:

	"IPACK" Make Automatic Six head Liquid Filling Line (Pneumatic) Consisting of the Following:		
1.0	**<u>Rotary Turn Table</u>: - 1 No.** ➢ 36" outer Diameter with side guides. ➢ Top plate aluminium casting with SS 304 machined top surface. ➢ Structure made of 40 mm Square tube with all side covering. ➢ Fix drive 0.5 Hp. With suitable gear box. ➢ Mat Finish (GMP Model) ➢ Output 70 to 80 Bottles per Minute.	**Rs.1,25,000.00**	
2.0	**<u>Airjet Cleaning system: -</u>** ➢ Airjet cleaning system mounted on Infeed conveyor ➢ First high pressure is inserted into the bottle and air in the bottle is sucked with high vacuum. ➢ air jet cleaning from top of bottle system. ➢ Line speed 60-70 Bottles per minute ➢ High pressure air injucted into the bottle and the sucked. ➢ Line direction Left to right. ➢ Single station Automation.	**Rs.1,50,000.00**	
3.0	**<u>Infeed Conveyor 3.0 Mtr. Long with two stoppers</u>: - 1 Set.** ➢ SS slat chain conveyor 120 mm width x 3.0 Mtr. Long ➢ Height of the conveyor 850 mm. to 900 mm. ➢ SS 304 Sq. tube 40 mm for legs support. ➢ 0.33 Hp. Drive Buonfiglio Make. ➢ 0.5 Hp VFD for speed variation Delta Make. ➢ Total conveyor made of SS 304. (GMP Model) ➢ Output 70 to 80 bottles/minute. ➢ Line direction left to right.		
4.0	**<u>Automatic Six Head Linear Liquid filling machine (Pneumatic)</u>: - 1 No.** ➢ Six head Viscous Liquid filling machine (Pneumatic). ➢ Pneumatic cylinder SMC/Festo Make. ➢ Non-Flameproof Model. ➢ Structure in SS 304 & contact parts will be in SS 316. ➢ Filling Range 100 ml. To 1000 ml. without any change parts. ➢ 60 to 66 Bottles/minute (500 ml.) ➢ Positive shut off nozzle for drip free filling. ➢ SS 316 Hopper with Inlet & Outlet 200 Ltrs. Capacity. ➢ Silicon Braided Hoses for suction & discharge for filling. ➢ Sanitary fittings with TC clamps. ➢ NRV type valves for suction and discharge. ➢ Easy hassle-free dose adjustment. ➢ Common Height adjustment with diving nozzle assembly. ➢ Total line is synchronized with PLC controlled system. ➢ No Bottle No filling system. ➢ Facility of production count.	**Rs.16,50,000.00**	
	Automatic rotary Indexing type Single Inner Plug Pressing machine consisting of		

5.0	**the following sub-assemblies: 1 Nos.** ➢ Indexing type rotary indexing type Single head inner plug pressing ➢ Infeed and outfeed conveyor system ➢ Infeed and outfeed turrets ➢ Automatic Vibrator cap feeder for inner caps feeding ➢ Commen Drive system ➢ Speed 60 to 70 BPM ➢ No bottle no capping system ➢ GMP Model & Non Flame Proof mode.	**Rs.5,50,000.00**	
6.0	**Automatic rotary Four Head Screw Capping machine consisting of the following sub-assemblies: 1 Nos.** ➢ Continuous rotary type four head screw capping machine ➢ Infeed and outfeed conveyor system ➢ Infeed and outfeed turrets ➢ Automatic Vibratory cap feeder for cap feeding ➢ Special capping die to suit the caps ➢ Common Drive system ➢ No bottle no capping system ➢ GMP Model & Flame Proof mode.	**Rs.6,50,000.00**	
7.0	**COOLING TUNNEL(BOTTLE WASHING WITH COOLING SYSTEM)** ➢ In this system first bottle is wash through the water spray by special designed nozzles ➢ MOC – SS304 ➢ Two stages are provided for primary wash and secondary washing ➢ One conveyor is provided, ➢ One chamber with header and nozzles ➢ Collection tank with drain is provided ➢ Length of the conveyor is 3100mm and width – 400mm ➢ Centrifugal pump- Crompton make, 0.5 HP each ➢ Capacity – 60 to 70 bottles per minute ➢ Length of the conveyor - 3000mm ➢ Width – 400mm ➢ Size – 3500mm Lx500mm W x 1700mm H	**Rs.4,50,000.00**	
8.0	**BOTTLE DRYING SYSTEM** ➢ MOC –SS304 ➢ This is used for external water is to be removed from bottles ➢ One chamber is provided ➢ Length of the conveyor with chamber is 2500mm ➢ Drying air knife is provided for removing of external air ➢ Capacity – 10 to 12 bottles per minute ➢ Length of the conveyor with chamber - 2500mm ➢ Size – 3000mm L x450mm W x1600mm H ➢ Power – 05 HP	**Rs.2,50,000.00**	
	SS Shrink tunnel Electrical: - 1 No. ➢ SS Slat chain Conveyor 2.5 Mtr. Long. ➢ Height of the conveyor 850 mm +/- 50 mm ➢ Shrink tunnel 1200 mm Long. ➢ Temperature controller for heat adjustment.		

9.0	➢ Sleeve placement will be manual ➢ Output 60 Bottles per minute	**Rs.2,50,000.00**	
	Automatic Wrap Around Sticker labelling Machine for round Bottles only.  **Overview of the Equipments** Machine is used to apply self-adhesive sticker labels on Round/Flat Containers. This Machine gives Full Wrap around Or Partial Wrap around on opposite side to the container as per requirement **Operation of the equipment** Containers will be loaded on to the Conveyor manually or with the help of Turn Table. One by one each container will be passed through the separator and shall go toward the label dispensing unit. While passing through the dispensing unit, labels will be applied automatically on to the containers and later on containers shall pass through the wrapping unit, where wrapping of labels on the containers shall take place. **Salient Features of the Equipment's** • Structure of S.S 304. • Conveying system to convey the product. • Imported A.C frequency variable drive for variable speed with constant torque. • Specially designed drive mechanism. • Dispensing Unit to dispense labels. • stepper Motor drive for labelling • Wrap around mechanism to wrap the label on product. • Micro controller controlled (Fiber Optic based) Product Sensor to sense the product. • Micro controller controlled (Fiber Optic based) Label Gap sensor to sense the gap between two labels. • Reel mechanism (Size: - 250 mm) to hang the roll. • Label release mechanism. • Break assembly to avoid variation during releasing of roll. • Microprocessor base Electronic control system for total operation of the machine with programmable feather touch key board & L.C.D display (P.L.C.) with programming facility. Speed of the Machine: 60 to 70 Bottles per Minute	**Rs.5,90,000.00**	
	Total Amount Rupees Forty Six Lakhs & Sixty Five Thousand Only.	**Rs.46,65,000.00**	

TERMS & CONDITIONS:-

1.0	**Prices**	Prices quoted above are Ex-works Pune. Packing & Forwarding @3.0% Extra.. Freight, Insurance, taxes & duties, octroi as applicable at the time of supply, will be extra to your account.
2.0	**Payment**	60% advance along with the order and balance against Proforma Invoice, but before dispatch.
3.0	**Trials and Inspection**	Will be carried out by the buyer at our works at Pune before despatch. The buyer will provide sufficient quantity of product and packing material I.e., Pouches & Product for trial purpose.
4.0	**Delivery**	12-16 weeks After commercially cleared order.
5.0	**Transit Insurance**	Extra At actuals.
6.0	**Freight charges**	Extra at actuals to your account. Machine shall be despatched on Freight **" TO PAY "** basis.
7.0	**Initial Commissioning**	**Travelling charges, Lodging and Boarding charges and 4000/- per day including travelling days.**.Supervision of Installation & commissioning will be done by our Service Technicians for the entire machine. This include Training of your Personnel and trial production run.All material handling equipment and unskilled labour will be arranged by the customer.
8.0	**Warranty**	One year against any manufacturing defects or faulty workmanship from the date of supply of machine. However all Electrical parts, Rubber / Plastic Parts and consumables are excluded from the warranty. For bought out items, the scope & period of warranty will be to the extent that it is offered to us by our suppliers.
9.0	**Validity**	This offer is valid for 30 days from date of offer and thereafter it is subject to our reconfirmation.
10.0	**Cancellation**	In the event that an order with advance payment is cancelled by you, we reserve the right to forfeit the advance and to recover from you all the consequential losses , including the value of all work completed and in process.
11.0	The company reserves the right to introduce changes in design and Dimension.	
12.0	Disputes, if any, are subjected to Pune juridiction only.	