Albany make Machine Protection Door RP300			
Sr. No	**Description**	**Albany make Machine Protection Door RP300**	
1	**Door version:**	Vertical Rapid Roller Door for machine protection.	
2	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.	
3	**Door blade:**	Rolltex Plus Curtain **(Orange)**	
4	**Bottom beam**	Aluminium anodized.	
5	**Drive unit:**	Drive unit IP 55, LH as an option, with control cable (standard length = height of door)	
6	**Opening / closing speed:**	Approx. max. 2,4 / 1,7 m/s	
7	**Control system:**	MCC Frequency converterVector Control for opening/closing speed up to 2,4 / 1,4 m/s for door with safety contact edge, protection IP 55. Without display, interface card delivered separately, including power- and interface cable, with main switch in separate box.	
8	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz	
9	**Safety features:**	Safety edge with cable chain integrated in side frames, door line photocell (Transmitter / Receiver) inside side frames, emergency crank and mechanical drop-down protection.	
10	**Safety limit switch:**	1 Schmersal safety limit switch PL e EN ISO 13849-1, SIL 3 EN 62061 on drive side integrated in the side frame to save space.	
12	**Display**	Display "Up-Stop-Down"	
13	**Motor Position**	Left Hand Side	
14	**Interface Card**	MCC without display unit, with combibox in plastic (175x250x150 mm) with PLC interface card and main switch included in combibox, including power- and interface cable.	PLC interface card needed
15	**Accessories**	Top Cover & Motor Cover	