Scissor Lift (Mobile-Motor)



Type	Scissor Lift	PL. indicate your requirement
Make	NIHVA	
Capacity in KG	500 Kgs To 10000 Kgs	
Platform Width in MM	Customized	
Platform Length in MM	Customized	
Lip Width in MM / Lip Length in MM	Customized	
Shut Height in MM	Customized	
Lip Operation Mode	Hydraulically Operated	
Operation Control	Through Panel	
Power Pack	Hydraulic	
Drive Type	Direct by electric Motor	
Motor Ratings HP / Make	1HP/Crompton	
Pump Design Flow (LPM)	2.5	
Pump Type	Gear	
Safety Valve Set Pressure (Kg/Sq. Cm)	120	
Volume of Oil Receiver (Liter)	7	
Power Supply	3 Phase	
Color	Golden Yellow	
No. of Scissor	1	
Fixing	On Floor / Within Pit	
Railing Type	Required / Not Required (2 side)	
Pendent	Optional	
Lifting Speed (Mtr. /Min.)	3	
Lowering Speed (Mtr. /Min.)	1.5 / 2	
Resting Pads	Optional	
No. of Fixed wheels	2	
No. of Castor Wheels	2	
Wheel Type	Nylon / Steel / Rubber / PU	
Wheel Dia in MM	125	
Lifting Speed (Mtr. /Sec.)	3	
Lowering Speed (Mtr. /Sec.)	1.5 / 2	

91 8551008333 ☎ +91 20 66304033

Email: marketing@nihva.com