Technical Specification of Retractable Roof		
Sr no	**Material**	**Specification**
1	Aluminium Raw Material	Special design of extruded aluminium profile with grade 6063-T5.
2	Joining Plate	Top quality 304 stainless steel connection joiner with ASTM A240 standard. (Thickness over 3.5mm,holding the aluminum structure)
3	Fastners and Hardware	304 stainless steel screws and bolts having a high tensile strength of 800 Mpa.
4	EPDM Seal	Shore Hardness A60,Tensile strength 115kg/sqcm
5	Loading carring capacity	80 kg/sqm on support structure
6	Wind Pressure calculation	120 Km/Hr
7	Guide	Aluminium 6063-T5 with Powder coated
8	Surface Treatment	Seven Tank Powder coating process
9	Motor rating	IP56
10	Motor Make	Nice
11	Remote Make and Range	Nice with 25meter range
12	Push Button Make	Schneider
13	Electric Cable Make	Polycab
14	Direction of Motor	Single Phase Bi-directional Motor
15	Mechanical Limit swith	Included
16	Wheel	High corrosion resistance Nylon Material with IS standard 7369 (1983).
17	Support Structure Material	SS304 with ASTM A240 and ASTM A312.



Office Add:- 187/ G-Block, 1st Floor, Thermax Chowk, MIDC, Above Renault Showroom, Chinchwad, Pune - 411019
Reg. Add:- 8/1 Coromant Heg. Soc. Sec. No. 27, Nigdi, Pradhikaran, Pune - 411044.
+91 2066 3040 33 +91 85 51091 333 sales@nihva.com www.nihva.com | CIN No U72900PN2012PTC143948

Report	
Sr no	**Name of Report**
1	Aluminium Test certificate
2	Structural STAAD analysis report
3	EPDM rubber test report
4	Motor Test report
5	Powder coating TC
6	Assembly inspection report
7	QC Inspection Report
8	Installation Manual
9	Critical Spare part list
10	Warrenty certificate



Office Add:- 187/ G-Block, 1st Floor, Thermax Chowk, MIDC, Above Renault Showroom, Chinchwad, Pune - 411019
Reg. Add:- 8/1 Coromant Heg. Soc. Sec. No. 27, Nigdi, Pradhikaran, Pune - 411044.
+91 2066 3040 33 +91 85 51091 333 sales@nihva.com www.nihva.com | CIN No U72900PN2012PTC143948