





Elevation



Top View

Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
UC-Under Cut
FFL-Finished Floor Level

ASSESORIES DETALES

(a) HINGES: 3 No.SS Ball bearing butt hinges 100x75x3mm.(iclean)


(b) LOCK: Mortise dead lock,Cylinder(Both side key) with Escutcheon (iclean)

(c) DOOR CLOSER (iclean)

(d) HANDLE : D Handle(254mm) (iclean)

Shutter thickness : 47 mm
Frame Sheet thick : 1.2mm
Shutter sheet thick : 0.8mm
Fixing : On Soliid Brick plasterd wall with Anchors
Electrostatic powder coated

NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.



Detail view of Section A

STEEL DOOR SIZES			
WOW	WOH	QUANTITY	LOCATION
900	2100	8	GROUND FLOOR
800	2100	1	
900	2100	5	FIRST FLOOR

COLOR -

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

SINGLE LEAF STEEL DOOR

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	NAME	DATE	SIGN.
DRAWN	OMKAR	11/03/16	
CHECK	ANIL	11/03/16	
REV.	00		
APPRD.			
MFG			

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT - HYOSUNG T&D
PROJECT -
SITE -
DWG. NO. - NIHVA/15-16/229
SCALE: 01 | WT: | SHEET: 01 OF 01
If any queries contact : projects@nihva.com