RapidRoll® 300 Plus F+R

High speed roll door for emergency routes

ALBANY
ASSA ABLOY

Technical data sheet

ASSA ABLOY, the global leader
in door opening solutions



NIHVA

ASSA ABLOY Entrance Systems is a leading supplier of entrance automation solutions for efficient flow of goods and people. With our worldwide presence we offer products and services dedicated to satisfying end-user needs for safe, secure, convenient and sustainable operations. ASSA ABLOY Entrance Systems is a division within ASSA ABLOY.

ALBANY
ASSA ABLOY

NIHVA
NIHVA Technologies Pvt. Ltd.

www.assaabloyentrance.com

High speed roll door RapidRoll® 300 Plus F+R for emergency routes

The high speed roll door RapidRoll® 300Plus (refer to separate technical datasheet) has special additional features that enable it to be marked with the F+R name to indicate it may be used for escape routes. The door has various monitoring devices that guarantee that the door opens securely on an ongoing basis. The direction of the emergency route can only be defined in one direction for the door and this is set by the side on which the radar sensor is installed.

RADAR MOTION SENSOR

It is equipped with a direction detecting radar motion sensor that is authorised for the use in escape routes. This enables the door to open automatically in an emergency and ensures that the door opens automatically as soon as people move towards it in the escape direction. The radar movement sensor always has priority over all other pulse generators. The radar sensor covers the full width of the door and guarantees secure recognition of people up to a distance of 1.5 m in front of the door.

AUTOMATIC SELF-OPENING

If the power fails or an error occurs the workflow brake is released automatically. This results in the door opening automatically to a minimum of 2 metres as a result of the counterbalance, guaranteeing free movement in the escape route in an emergency.

SELF-TEST

The MCC^{VectorControl} system has a special software that carries out a self-test on the door and other security devices every 24 hours using special software in order to guarantee the perfect operation of the emergency function. The timing of the self-test can be set individually by the operator of the door.


ZERTIFIKAT ◆ CERTIFICATE ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Bescheinigung über eine Konformitätsprüfung

TÜV SÜD Industrie Service

Bescheinigungs-Nr.:	1000813
Antragsteller / Bescheinigungsinhaber:	ALBANY DOOR SYSTEMS GmbH Am Mondschein 25 D-59557 Lippstadt
Auftragsdatum:	16.02.2007
Hersteller:	ALBANY DOOR SYSTEMS GmbH Am Mondschein 25 D-59557 Lippstadt
Produkt, Typ:	Schnellauftor in Flucht- und Rettungswegen RapidRoll 300 PLUS F+R
Prüflaboratorium:	TÜV SÜD Industrie Service GmbH Prüflaboratorium für Produkte der Fördertechnik Prüfbereich Maschinen der Fördertechnik Gottlieb-Daimler-Straße 7 70794 Filderstadt
Datum und Nummer des Prüfberichtes:	15.06.2008 1000813
Prüfgrundlagen:	98/37/EG (Maschinenrichtlinie) DIN EN 13241-1:2004 Tore - Produktnorm Richtlinie über automatische Schiebetüren in Rettungswegen (AutSchR) = soweit auf Tore übertragbar =
Gültigkeit:	Diese Bescheinigung gilt bis zur Außerkraftsetzung der Richtlinie 98/37/EG (bis 28.12.2009)
Ergebnis:	Das Produkt erfüllt für den im Anhang zu dieser Bescheinigung angegebenen "Anwendungsbereich" – bei Einhaltung der dort genannten "Anwendungsbedingungen" – die Anforderungen der Prüfgrundlagen
Ausstellungsdatum:	18.06.2008

Prüflaboratorium für Produkte der Fördertechnik
Prüfbereich Maschinen der Fördertechnik

Werner Rau | Wolfgang Kübler

TÜV SÜD Industrie Service GmbH · Westendstrasse 199 · 80686 München · Germany

TÜV®

TÜV-APPROVAL*)

The RapidRoll® 300 Plus F+R complies with the key requirements of the "Guideline for automatic sliding doors in escape routes" (AUtSCHR).

*) Each individual installation requires the approval of the relevant building inspection authority.

Options RapidRoll® 300 Plus F+R on the standard RapidRoll® 300 Plus

Escape route door	suitable
Wind resistance	Class 1 - EN 12424 to H = 3500 mm Class 0 - EN 12424 from H > 3500 mm
Size in mm H min./max.	2300 / 4000 mm
Control system	only MCC^{VectorControl} with special software
	Security devices stored in additional casing
Switch box	
Casing and main switch	optional
Switch to deactivate the escape route function	optional
Top roll cover	optional[1)]

[1)] In the F+R design a roll cover for fixing the radar sensor is included as standard. For doors with a height of ≤ 2500 mm a top roll cover is required to comply with the requirements of the 13241-1 standard. For heights over 3700 mm an additional holder is required that enables the maximum installation height for the radar sensor of 4000 mm.


RapidRoll® 300 Plus F+R equipped with direction-detecting radar motion sensor.


Switch to deactivate the escape route function.


MCC^{VectorControl} system with extended casing to accept the necessary security devices.


Optional:
Control box with operator display and main switch.

Copyright by Albany ASSA ABLOY Technical data subject to change without notice

64 100033/12/11 EN