S P E C I F I C A T I O N S

Sr. No.	DOCK LEVELLER
1.00	Please see Table 2.
1.01	Load Capacity : 6 ton (12,000 lbs) static and/or 15,000 kg dynamic load (30,000 pounds dynamic).
1.02	10 years warranty: 2.25m wide and 2.50m long.
1.03	Height differential between lowest and highest position of leveler: min. 250 mm up and min. 250 mm down
1.04	Lip type : hinged lips
1.05	Lip length : minimal 450 mm (18") in combination with 100 mm (4") thick rubber bumper.
1.06	Leveler Seals : A seal required between leveller and concrete warehouse floor. Use brush or rubber seal.
1.07	Dock bumper : Install 2 of 50 cm (20") high by 100 mm (4") thick vertical dock bumpers.
1.08	Safety : Anti-fall mechanism (a mechanical lock system to maintain leveler in upward position during maintenance).
1.09	Interlock with dock door : Electrical interlock with dock door motor preventing power to leveler if dock door is not in full open position. Provision only required.

S P E C I F I C A T I O N S	
Sr. No.	**DOCK SHELTER**
1.00	Please see Table 2.
1.01	Dock shelter in wall shall have with flexible curtains.
1.02	Provides additional seal between trailer top and shelter to prevent rainwater running off the trailer top into DC.
1.03	An additional top seal before the dock seal: E.g. RainGuard RG-3000 from Rite-Hite.
1.04	Height of truck cargo hold floor from road level: 0.9 m minimum to 1.5 m maximum.
1.05	Expected minimum size of truck cargo hold: 2.30 m width x 1.5 m height
1.06	Expected maximum size of truck cargo hold: 3m width x 3.6m height
1.07	Dock shelter shall cater to all sizes of truck cargo hold and truck body height within the range mentioned above.