Tech. Specs. Sheet	Telescopic Sliding Gate	NIHVA



NIHVA make – Motorized Telescopic Sliding Gate

Door type	**Motorized Sliding Gate**
Clear Opening gate dimension	8 Mtr (W) x 2 Mtr(H)
Opening Direction	**Horizontal - from left to right or reverse**
Mounting Location area	Inside area
Design Pattern	Standard Tubular Design Pattern
Outer Frame Tube Sizes	80 x 80 x 3.2 mm
Internal Vertical Tube Sizes	40 x 40 x 2 mm
Gap Between Tubes	100 mm C/C
Bottom Rail on ground	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
Bottom Rollers	Heavy Duty Bottom Wheel With both side Bearings (chrome plated)
Full Height Column sizes	100 x 100 x 3.2 mm
Guide Rollers supporter during Gate movement	**Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate**
Painting	2 Coats of EPOXY primer and 2 coats of Synthetic enamel paint
El motor	100% imported European make Motor
Emergency Operation	Manual after turn the switch
Telescopic Mechanism	Inbuilt with Gate
Operating Switch	Push Button from inside

91 8551008333 ☎ +91 20 66304033

Email: marketing@nihva.com

Safety	Photocells, Flashing Light
Metal Rack	zinc plated metal rack
Installation Checks	need to be check = space requirements + substructure + Mounting access + Access in the event of power cut
Civil work	Client scope – client need to grout the I beam in concrete to create track for sliding gate