NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

Project Name: Endress + Hauser Flowtec (India) Pvt. Ltd.

Technical Specifications

Sr. No	Product Name	Model No	Make	Pages
A.	High Speed Door	HS9020G	ASSA ABLOY	1
B.	Sectional Door	OH1042P	ASSA ABLOY	2
C.	Retractable Dock Shelter	DS6060A	ASSA ABLOY	3
D.	Swing Dock Leveler	DL6010S	ASSA ABLOY	3
E.	Scissor Lift		NIHVA	4
F.	Double Skinned Motorised Rolling Shutter		Teckentrup	4

A) High Speed Door **Internal Application**




HS9020G



SIDE GUIDES



Safety Facilities



Sr. No	Description	Specifications
1	Size	(W) 4000 mm X (H) 4000 mm
2	Quantity	7 Numbers
3	Structure	Galvanized steel
4	Colours	8 standard colors - white, yellow, green, orange, red, gray, black, blue
5	Safety	• Photocells in side columns • Flexible soft bottom edge including wireless edge activator • Break-away and self-repair function
6	Operation	Operator + control unit
7	Operating speed	Opening: up to 1,2 m/s (optional 2,0 m/s) ; Closing: 0,5 m/s
8	Wind load resistance	Class 1 (300 Pa (N/m²)) maximum wind load while closing 50 N/m²
9	Air permeability	Class 1 (24 m³/m²/h at 50 Pa)
10	Water penetration	Class 2 (50 Pa (N/m²))
11	Thermal transmittance	6,02 W/(m²K)
12	Lifetime expectations	1.000.000 cycles
13	Temperature working range	5 °C to +40 °C
14	Vision window	Horizontal one row of height 400 mm at eye level

Additional Accessories Required

Sr. No	Description	Specifications
1	Buzzer	When Door will open or close there will be beep sound
2	Flashing Lights	Lights are used to display the current door behavior. Flashing light will flash during door movement.
3	Radar Sensor 	An infrared sensor above the door detects an object (person, vehicle) within a specified distance from the door and opens the door automatically. This is an ideal solution for frequent vehicle or personal traffic.
4	External push button box 	Used for opening & closing of door. Installed on the inside or outside wall beside the door
5	Pull-rope switch 	Pulling the rope opens the door. Installed on the inside construction above the door A pull-rope switch above the door opening can be operated from e.g. a forklift truck.

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019


An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM


B) Sectional Door




OH1042P



LOW LIFT
(head room < 500mm)



Vertical Lift
(head room > 2 x height)



Sr. No	Description	Specification
1	Size	(W) 4000 mm X (H) 5000 mm
2	Quantity	8 Nos
3	Vision Windows	2 Nos at central panel
4	Opening Direction & Mounting	Vertical (For Quantity 7 Nos)
5	Opening Direction & Mounting	Low lift (For Quantity 1 No)
6	Opening/Closing Speed	CDM9 0,28 m/s
7	Door Material	GI Steel
8	Panel Thickness	42 mm Square Grid, steel sheet
9	Filling	CFC-free polyurethane
10	Panel colour	RAL 9002 Grey White Powder coated
11	Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
12	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
13	Water Penetration	EN 12425 class 3
14	Air Permealibity	EN12426 class 3
15	Wind Load	EN21424 class 3
16	Thermal Transittance	EN 12428 1.10W /m2K
17	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
18	Door saftey	Doors equiped with spring break device
19	Incase of Power failuer	Doors to be equiped with quick release fuction
20	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
21	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
22	Emergency Operation	by Disengagement rope manual
23	Operating Switch	Up/Down Keypad + stopbutton
24	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
25	Environmental Green Product Declaration Certification	As per ISO 14025 and EN 15804

Additional Accessories Required

Sr. No	Description	Specifications
1	Flashing Lights	Lights are used to display the current door behavior. Flashing light will flash during door movement.
2	Interlocking 	Developed for climate control & safety; If door A is open, door B cannot be opened. If door B is open, door A cannot be opened.

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

C) Retractable Dock Shelter



Retractable Dock Shelter




Docking System (Sectional Door, Dock Leveler, Dock Shelter)

Sr. No	Description	Specification
1	Size	(W) 3450 mm x (H) 3600 mm
2	Quantity	4 Nos
3	Curtain colour	Black
4	Parking Guides	White, Yellow
5	Wall Fixings	Concrete, Sandwich light Concrete, Load house cavity, insulated panel
6	Top & Side Curtaiins	Double Layer High Quality Polyester
7	Thickness	3.0 mm
8	Weight	Approx 3400 g/m2
9	Continous Roof Cover	One layer high quality Polyester
10	Thickness	0.5 mm

D) Swing Dock Leveler







Safeguard emergency stop with two cylinders.

Sr. No	Description	Specification
1	Size	(W) 2000 mm x (H) 2500 mm
2	Quantity	4 Nos
3	Capacity	15 T
4	Control Unit Protection Class	IP54
5	European Standards	EN 1398
6	Coating	RAL 5010, Hot dip galvanized
7	Control unit	Supervision 105, 105A, i105, i305 Service & fault Indicator
8	Vertical working range Rise above dock Fall below dock	250 - 620 mm 270 - 350 mm
9	Platform tear-plate thickness with platform reinforcements according to the load capacity	6/8, 8/10 mm
10	Lip material & length	Steel, 400 / 500 mm
11	Nominal voltage	400V 3-phase

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

E) Scissor Lift





Sr. NO	Description	Specification
1	Capacity	15 Ton
2	Platform Size	(W) 2000 mm X (L) 2500 mm
3	Shut Ht	1000 mm
4	Max Ht	2200 mm
5	Lift Ht	1200 mm
6	Safety Railing	Length side only
7	Manual Lip	3 Piece(240 + 1500 + 240) - 1 Side Only
8	Maintenance Stopper	2 NOS
9	Fabrication	3500 KGS
10	Push Button Pendent	Flexible pendent with 5 mtr Cable - 1 No
11	Control Panel	Outside pit - 1 No
12	Rubber Safety Edge or Safety Bellow	
13	Safety Bellow	All side
14	Power Pack Inside Pit with Buzzer	15 HP, 3 Phase - Eaton make
15	Hydraulic Cylinder	Two numbers with Bore 150 X stroke 500 mm - Eaton make
16	Hot Dip Galvanised	IS 2629 / EN ISO 1461 / As per ASTM
17	Hose	Parker Hoses
18	Hardware	
19	Cable	Polycab cables
20	Hydraulic Oil	Grade 68 - 125 Ltr
21	Paint	Glossy - 20Ltr

F) Double Skinned Motorised Rolling Shutter





Sr. No	Description	Specification
1	Size	(W) 4000 mm x (H) 4000 mm
2	Quantity	4 Nos
3	Roller shutter curtain profile type	ThermoTeck steel filled with PU-foam
4	Roller shutter surface outside	Galvanized with protective fill
5	Emergency drive operation	Emergency hand crank
6	Control unit	CS 310 (dead man) with built-in triple button, CEE-plug with wire
7	Bottom profile	ET-1 for Teckentrup ThermoTeck
8	Drive type / -edition	Direct mount drive TAR 1.14 KU 400V/3Ph AWG ; 12 U/min; IP54; 60% ED
9	Drive mounted	Inside left, standing