NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Fresenius Kabi India Private Limited
Plot No-1,Phase-III,Honda Industrial Estate,
Honda Sattari, Goa - 403530, India

Date : **21.10.2019**
Quote NO : **SQT.19.20.2145R**
Kind Attn : **Mr. Swapnil Desai**
Email Id : Swapnil.Desai@fresenius-kabi.com
Contact No: **8326733600**

Subject : Revised Quotation for High Speed Door HS9020GAT, HS 9020G Clean Room Door & Sliding Glass Door

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions. This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2,3,4,5
C.	General Conditions	6
D.	Terms & Condtions	6

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Length (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
	Option 1 : HS9020GAT							
1	Albany Make Rapid Roll Up Door (Bottle Packing, Presterile Area)	1810	2050	1	4,82,000	4,82,000	20,000	20,000
2	Albany Make Rapid Roll Up Door (Bottle Packing, Presterile Area)	2600	2040	1	5,29,000	5,29,000	20,000	20,000
3	Albany Make Rapid Roll Up Door (Packing to Warehouse)	1920	2040	2	4,83,000	9,66,000	20,000	40,000
	Option 2 : HS9020G							
1	Albany Make Rapid Roll Up Door (Bottle Packing, Presterile Area)	1810	2050	1	4,37,000	4,37,000	20,000	20,000
2	Albany Make Rapid Roll Up Door (Bottle Packing, Presterile Area)	2600	2040	1	4,80,000	4,80,000	20,000	20,000
3	Albany Make Rapid Roll Up Door (Packing to Warehouse)	1920	2040	2	4,38,000	8,76,000	20,000	40,000
	Glass Door							
4	Besam Sliding Glass Door	1100	2000	1	2,48,000	2,48,000	20,000	20,000
5	Automatic Swing Door	1100	2000	1	2,60,000	2,60,000	15,000	15,000
	Scissor Lift							
6	Pit Mounted Scissor Lift	1100	3050	1	3,90,000	3,90,000	20,000	20,000
	Telescopic Conveyor							
7	Telescopic roller conveyor	7500	530	1	5,41,000	5,41,000	50,000	50,000
				Total		**52,09,000**		**2,65,000**
8	P&F Charges			3%		**1,56,270**		
	Total Without Taxes					**53,65,270**		**2,65,000**
	GST Extra @ 18%			18%		9,65,749		47,700
	Total With Taxes					**63,31,019**		**3,12,700**
9	Transportation Charges					**In Client Scope**		
10	Unloading Charges @ Site					**In Client Scope**		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification


NIHVA ASSA ABLOY - Albany Make HS9020GAT



Sr. No	Description	Specifications
1	Door Type	The HS9020GAT is a compact, airtight door with integrated motor for inside environments, type clean room
2	Door Construction	Door Constrcution in Stainless Steel 304
2	Sealing	Unique side column technology provides excellent seal on all 4 sides thereby reducing heat loss.
3	Opening & Closing Speed	Opening: up to 2 m/s, Closing: 0.5 m/s
4	Safety features:	• Photocells in side columns, • Flexible door curtain without ridged parts • Flexible soft bottom edge including wireless edge activator • Break-away and self-repair function.
5	Vision Window	Single row with 400 mm Height
6	Wind load resistance	Class 1 (300 Pa (N/m²)) maximum wind load while closing 50 Pa (N/m²)
7	Water penetration	Class 2 (50 Pa (N/m²)
8	Air permeability	• Class 3 - Over Pressure • Class 1 - Under Pressure
9	Thermal transmittance	6,02 W/(m²K)
10	Lifetime expectations	1,000,000 cycles
11	Radar Sensor	On Both Sides

NIHVA ASSA ABLOY - Albany Make HS9020G






Side Guide



Safety Facilities



Sr. No	Description	Specification
1	Area of Use	Interior applications.
2	Drive System	Gravity Driven System
3	Opening Speed	up to 2.0 m/s depending on size of door.
4	Closing Speed	up to 0.5 m/s depending on size of door.
5	Photocells	Inside Columns
6	Safety	• Flexible soft bottom edge including wireless edge activator. • Break-away and self-repair function.
6	Wind Load Resistance	(EN 12424) Class 1 (300 Pa (N/m^2)). Maximum wind load while closing 50 Pa (N/m^2)
7	Water Penetration	(EN 12425) Class 2 (50 Pa (N/m^2)) 20 minutes water spray
8	Air Permeability	(EN 12426) Class 1 (24 $m^3/m^2/h$ at 50 Pa)
9	Thermal Resistance	(EN 12428) 6,02 $W/(m^2K)$
10	Temperature Working Range	5 °C to +40 °C
11	Door Curtain	900 g/m^2 colored PVC, Flexible door curtain without ridged parts
12	Various Window	400 mm height single row
13	Operator	220V - 240V 1-phase 0,75 kW 16A
14	Operator Protection	IP65. Soft start/stop significantly prolongs motor lifespan.
15	Control Unit Protection	IP54
16	Lifetime Expectations	1,000,000 cycles
15	Side Column	Unique side column technology provides excellent seal on all 4 sides thereby reducing heat loss
16	Lifetime Expectations	1,000,000 cycles
15	Control Unit Protection	IP54
16	Motor	The motor with frequency converter guarantees smooth and reliable operation.
15	Control Unit Protection	Control unit with display, impulse Up and Down buttons, an emergency stop mushroom button and a mechanical main switch.
16	Lifetime Expectations	1,000,000 cycles

Automatic Sliding Glass Door





Sr. No.	Description	Specification
1	Power Supply	100-240 VAC ±10% 50/60 Hz
2	Power consumption	max. 250 W
3	Open and closing speed variable	up to 1.7 m/s (2 leaves)
4	Hold-open time	0 – 60 s
5	Ambient temperature	- 20°C to + 50°C
6	Relative humidity (non-condensing)	max. 85%
7	Operator type	Bi part operator
8	Glass	10mm thick toughened glass

Pit Mounted Scissor Lift





Sr. No.	Description	Specification
1	Capacity	2.5 ton
2	Platform size	3050L x 1100W
3	Shut ht	500 mm
4	Max ht	1500 mm
5	Lift ht	1000 mm
6	Power pack	5HP,3Phase
7	Safety railing	both length side only 900 mm height
8	Color shade	as per req.
9	Safety Features	• Pilot operated Check valve for anti-fall. • Over load relay • M.C.B • Limit Switch for Max Ht. • Buzzer

Telescopic roller conveyor

Sr. No.	Description	Specification
1	Total Length	7500 mm
2	Collapsed length	4900
3	Width	530 mm
4	Height	1000 mm
5	Cotrol	
6	Material Conveying	Automatic Forward & reverse
7	Telescopic movement	Manual

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk,
MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description	Remark
1	Secured and fully covered Store area to keep the material	In Client Scope
2	Scaffolding/Hydra/Crane/Forklift etc - Required for Installation at Site	In Client Scope
3	Electrical Supply on the site single phase/three phase points at different places.	In Client Scope
4	Any civil / masonry/structural work required	In Client Scope
5	All structure support required	In Client Scope
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	In Client Scope
7	Conduits, Cables required	In Client Scope

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 12-13 Weeks for High Speed Door from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

For any further Clarification /Information in this Concern, Please feel free to Contact **Mr. Swapnil Kulat on 7219207333**

With Best Regards
Vivek
8530370333
For NIHVA Technologies Pvt Ltd