Product:

High Performance Door RapidProtect™ 2000 made of aluminum

Description:

High performance door, opening in vertical direction, for use in material handling.

Side frames made of edged galvanized steel, all steel components galvanized, balancing system integrated in the side frames

Door curtain: Door curtain of ecru anodized aluminum lamellas, hingeless connected by means of flexible heavy belts, wear-less to wind up without to contact each other, each single lamella can be replaced easily, pre-fitted on the top roll.

Opening / closing speed: max. 2.3/1.3 m/s

Wind resistance: class 3, EN 12424

Drive unit: gear motor, pluggable electrical connections

Protection: IP 55

Control unit: MCCVectorControl, with vector control technology and boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service

Control voltage: 24 V DC.

Supply voltage: 3L/(N)PE 380/400/415/440V; 50/60 Hz, 10

Transformator necessary for 230/480/500V; 50/60 Hz.

Safety devices:

Pre-running photocell with integrated cable chain in the side frames,

drop down protection by integrated balancing system

safety limit switch: magnetic switch with reader performance level e according to EN ISO 13849-1 and SIL3, according to EN 62061, switch integrated in side frame.

Manual activation:

by releasing the brake at ground level. Partly opening by means of the pre-stressed tension springs.

Size max.: (DWxDH) 3000 x 3000 mm

Make: ALBANY RapidProtect™ 2000

Optional

Cover

Top roll cover, anodized aluminum

Motor cover, PVC

Cover for the backside of the top roll for self-supporting installation

Surface / material:

- Side frames with covers made of anodized aluminum
- Side frames with colour coating
- Aluminum lamella with coloured coating

Miscellaneous:

- Door line photocell in the side frames
- Aluminum lamella with windows
- Extended flexible seal
- Supports for self-supporting installation
- Actuator
- Additional safeties

Delivery

Installation incl. wiring