NHIVA Sliding Gate



NIHVA USP:-

- Motorized or manual drive system propels the gate along.
- Constructed from sturdy materials like steel or aluminium.
- Obstacle detection sensors prevent accidents by halting gate movement.
- Includes latch or electronic system for secure closure.
- Operated via control panel or remote transmitter for convenience.
- Length of gate can be fabricated from 1000mm - 15000mm.
- Can be fabricated for gates up to 18000 kg weights capacity.
- Bottom rail made up of polished bright bar supported with heavy duty beam.







Shivaah Technologies Pvt ltd

+91 2066 3040 33
+91 85 51091 333
sales@nihva.com
www.nihva.com
www.shivaah.com

NHIVA Sliding Gate

Technical Specification	Description	
Product	Motorized Sliding Gate	
Dimensions		
Width Min. /Max.	• Single Leaf : 1000/15000mm • Double Leaf :1000/30000mm	
Height Min. /Max.	• 1000/3000mm • Larger Dimension on request	
Opening	• Horizontal	
Mounting Location	• Inside/ Outside	
Material	• Stainless Steel, Hot dip Galvanized	
Sheets	• M.S/GI/Perforated /Aluminum sheets/Wood.	
Ornamental Designs	• On Request or as per client design.	
Options Available (as per requirement)	• Spikes /Wicket gate/Side Gates in the similar pattern as the main gate any type of Customized Design can be made on request.	
Automation		
Drive Unit	• Motorized / Manual	
Emergency Operation	• Manual release knob.	
Accessories (Optional)	**Operational** • Additional Push Button • Key switch • Remote Control with receiver • Magnetic Loop Detector	**Safety** • Safety Photocell • Vertical Safety • Edge Sensor • Flashing Light



Technologies Pvt. ltd