MPO
Horizontal Open well Submersible pumpset– 3 Phase



Technical Data:
Flow: upto 2250 LPM
Head: upto 78 m
Power: upto 30 HP
Voltage: available in 3 phase

Material of construction:
Casing : Cast Iron
Impeller : Cast Iron
Motor Body : SS/CI

Application:
Water transfer in:
- Bungalows
- Farm houses
- Apartments
- Agriculture

Standard Features:

- No need of foundation and foot wall as installed under water
- SS shaft for long and trouble free life
- Energy efficient motor design
- Motor designed to operate in wide voltage range
- Motor filled with anti corrosive liquid to increase life of internal parts
- Strong carbon v/s stainless steel thrust bearing for longer life

Selection Table

Openwell 3 Phase

Pump Model	kW	HP	Outlet Size (mm)	Discharge (LPM) / Total Head (m)																						
				8	11	12	15	16	18	19	21	22	24	25	26	28	30	32	33	35	39	41	48	50	56
MPO020	1.50	2.00	40					250	235	220	195	180	150	130	115	50									
MPO020L	1.50	2.00	50	640	550	500	410	350																	
MPO031	2.20	3.00	40										250	240	235	220	205	190	180	150					
MPO032	2.20	3.00	40							350	330	320	290	275	250	180									
MPO033	2.20	3.00	50		680	660	585	550	485	435	300														
MPO034	2.20	3.00	65	930	810	775	600	400																	

Pump Model	kW	HP	Outlet Size (mm)	Discharge (LPM) / Total Head (m)																						
				8	11	12	15	16	18	19	21	22	24	25	26	28	30	32	33	35	39	41	48	50	56
MPO055	3.70	5.00	40											500	490	470	445	425	410	380	300	270			
MPO056	3.70	5.00	50							690	650	635	600	575	550	500	450	325							
MPO057	3.70	5.00	65			1150	1020	960	860	805	690	600	430												
MPO078	5.50	7.50	40																			330	240	210	60
MPO079	5.50	7.50	50												720	685	655	620	590	530	340	250			
MPO0710	5.50	7.50	65							1040	1000	980	920	900	870	785	730	640	590	420					
MPO0711	5.50	7.50	80					1450	1320	1270	1100	1030	850	780	620										

Conversion Table: 1 m = 3.281 ft and 1 m³/hr = 16.67 LPM = 3.67 GPM

Pump Model	HP	Outlet Size (mm)	Discharge (LPM) / Total Head (m)																							
			19	21	24	27	30	32	33	34	35	38	42	48	50	53	56	59	60	62	65	68	71	74	78
MPO1012	10.0	40											470	420	405	370	325	250	230	100					
MPO1013	10.0	50						820	810	790	770	730	650	420	300										
MPO1014	10.0	65			1250	1150	1050	970	925	900	810	400													
MPO1015	10.0	80		1540	1390	1210	990	750	600																
MPO1016	10.0	80	1400	1200	500																				
MPO1217	12.5	50				1000	920	900	880	870	850	800	740	600	550	400									
MPO1218	12.5	65				1200	1140	1090	1050	1040	1000	910	650												
MPO1219	12.5	80		1770	1640	1470	1300	1060	920	780															

Pump Model	HP	Outlet Size (mm)	Discharge (LPM) / Total Head (m)																							
			19	21	24	27	30	32	33	34	35	38	42	48	50	53	56	59	60	62	65	68	71	74	78
MPO1520	15.0	50											900	780	735	660	550	440	400						
MPO1521	15.0	50													880	840	785	710	670	625	480	300			
MPO1522	15.0	65									1250	1160	1050	800	600										
MPO1523	15.0	80		1980	1860	1760	1640	1520	1475	1380	1290	800													
MPO2024	20.0	50															850	810	800	740	690	630	550	460	300
MPO2025	20.0	65												1280	1230	1150	1045	900	800	650					
MPO2026	20.0	80						1650	1620	1580	1540	1420	1200	600											
MPO2527	25.0	80										1860	1760	1550	1450	1300	1100								
MPO3028	30.0	80											2250	2080	2000	1830	1710	1550	1500	1350					

Note: The above performance is based on mean supply voltage of 415 V at 50 Hz and subject to change due to continuous R&D.

Conversion Table: 1 m = 3.281 ft and 1 m³/hr = 16.67 LPM = 3.67 GPM

NIHVA
NIHVA Technologies Pvt. Ltd.