

Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
UC-Under Cut
FFL-Finished Floor Level

ASSESORIES DETALES

(a) HINGES: SS Ball bearing butt hinges 100x75x3mm

(b) LOCK : Mortise Dead lock,Cylinder(Both side key) with Escutcheon


(c) DOOR CLOSER

(d) HANDLE : D Handle(254 mm)

(e) CONCEALED FLUSH BOLT

Shutter thickness : 47 mm
Frame Sheet thick : 1.2mm
Shutter sheet thick :0.8mm
Fixing : On Soliid Brick plasterd wall with Anchors
Electrostatic powder coated


NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.



Elevation



Top View



Detail view of Section A

SS door size		
WOW	WOH	QUANTITY
1980	2180	1

ORIENTATION- CLIENT SHOULD MENTION DOOR ORIENTATION FROM HANDLING SHEET.

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

SS DOOR

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	NAME	DATE	SIGN.
DRAWN	OMKAR	09/05/16	
CHECK	ANIL	09/05/16	
REV.	01		
APPRD.			
MFG			

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT - MARS INTERNATIONAL
PROJECT -
SITE -
DWG. NO. - NIHVA/16-17/0014
SCALE:01 | WT: | SHEET: 01 OF 01
If any queries contact : projects@nihva.com