Double wall Motorized Rolling Shutter

Door type	Double wall / Slat Rolling Shutter	
Clear Opening dimension (W) X (H)	Rs-1: 4000mm (W) X 5000mm (H) Rs-2: 5000mm (W) X 6000mm (H) Rs-3: 4000mm (W) X 5000mm (H) Rs-4: 3500mm (W) X 5000mm (H) Rs-5: 2500mm (W) X 2700mm (H)	
Opening Direction	Vertical - from bottom to Top	
Mounting Location area	Only Inside area	
Mounting Surface	Side Brackets: Optional = On Concrete / Steel & Side Guides : Optional = On Concrete/Steel / Masonry	
Opening/Closing Speed	0.1 m/sec	
Wind Resistance	120 Km/hr	
Door material		
Slats material	insulated pre coated Galvanized steel (Polyurethane foam)	
Slat size	95mm x 19mm with PU filled inside	
Curtain Profile	Corrugation	
Bottom Profile	125mm x 15mm with extra angle support. (Optional - Rubber Bottom Seal)	
Side Guide Profile	M.S." U" Shaped profile 125 x 40mm x 3 mm thick (as per the opening width dimension)	
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h	
Side Brackets	MS Plate 3 mm to 10 mm thick , as per the opening dimension	
Hood Cover	Made of GI Sheet Thickness 0.8 mm with 25x25x3mm angle stiffener	
Surface finish		
Painting	Powder coated – Off white color	
Vision Windows	With Vision Window / without Vision Window	
Automation		
Control Type	Optional = Dead man / Pulse Control	
Drive Unit & Mounting Type	Option 1) Electric Motor (Imported German Make) (Single Phase/Three Phase) - Direct Mounting on Shaft	
Emergency Operation	Manual Rope Drive	
Operating Mode	Push Button from inside & Outside also	
Accessories	Flashing Light / Safety Photocell	
Installation Constraint any	Need to be check = Space requirements + sub structure scope of work + Mounting access + Access in the event of power cut + clear opening dimensions	