NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Indamer
Mumbai Operation Gate No. 8, Militry Camp,
Kalina, Santacruz (E), Mumbai - 400 029

Project, Location :

Date : 20.1.2021
Quote NO : SQT.20.21.2943R1
Kind Attn : Rohan Dhumal
Email Id : rohand@aarindamertechnics.com
Contact No: 9579622491

Subject : Revised Quotation for Bollards

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions.
This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2
C.	General Conditions	3
D.	Terms & Condtions	3

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Diameter (mm)	Shaft Height (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	J275 2K20 HA STAINLESS STEEL Automatic Retractable Traffic Hydraulic Bollard (K4 Certified Bollards) Cylinder height from ground 800mm. Cylinder diameter 275 mm. Cylinder material AISI 316L Stainless Steel. Cylinder treatment Satin finishing.	275	800	16	581,000	9,296,000	25,000	400,000
	Total			**16**		**9,296,000**		**400,000**
2	P&F Charges			3%		278,880		
	Total Without Taxes					9,574,880		400,000
	GST Extra @ 18%			18%		1,723,478.40		72,000
	Total With Taxes					**11,298,358**		**472,000**
3	Transportation Charges					Extra at atcual		
4	Unloading Charges @ Site					In Client Scope		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

NOTE :	**Every Bollards needs Civil Pits.** **Civil Pits work in Clients Scope.**



FAAC J275 2K20 HA BOLLARD

Hydraulic Automatic HIGH SECURITY BOLLARD FAAC J275 2K20 HA is crash tested in accordance to:
PAS 68: Impact test specifications for vehicle security barrier systems
IWA 14-1: Vehicle Security Barriers - Part 1: Performance requirement, vehicle impact test method and performance rating

Sr No	Description	Specification
1	Model	J275 2K20 HA STAINLESS STEEL
2	Drive	Hydraulic unit
3	Cylinder height from ground	800mm / 31.5 inches
4	Cylinder diameter	275mm / 10.8 inches
5	Cylinder material	AISI 316L stainless steel
6	Cylinder treatment	Satin finishing
7	Cylinder's head	Aluminium
8	Head treatment	Anti-corrosion Rilsan® resin
9	Ground cover material	Aluminium
10	Ground cover treatment	Anti-corrosion Rilsan® resin
11	Rising time	~8 s
12	Lowering time	~4,5 s
13	Emergency automatic lowering	YES (OPTIONAL)
14	Emergency lowering time	~2
15	Obstacle detection while rising	YES (OPTIONAL)
16	Emergency manual lowering	Accessible with supplied key
17	Gentle Stop function	YES
18	Power supply	207 V~ ... 243 V~ - 50/60 Hz
19	Max consumption	575 W
20	Protection index	IP67
21	Load class(EN 124)	C250
22	Break-in resistance (2 units configuration)	673.000 J
23	Operating temperature	-15°C / +55°C
24	Operating temperature with heater (accessory)	-25°C / +55°C
25	Control Unit	Push Button with safety Loop Detector
26	Bollard weigth	170 kg // 375 pounds
27	Bollard packagind dimensions LxWxH	1.200 mm x 800 mm x 450 mm // 47 inches x 31 inches x 18 inches

PIT

28	Dimensions LxWxH	550 mm x 619 mm x 1245 mm // 22 inches x 24 inches x 49 inches
29	Material	Steel EN 10346-DX53+Z140-A: thickness 2mm / 0,08 inches
30	Counterframe	Ductile casted iron, treated with cataphoresis
31	Pit weight	80 kg // 176 pounds
32	Pit packaging LxWxH	800 mm x 600 mm x 700 mm // 31 inches x 24 inches x 28 inches

FOUNDATION

33	Dimensions LxWxH (2 units configuration)	2.400 mm x 3.100 mm x 1.540 mm // 95 inches x 122 inches x 61 inches
34	Concrete Specifications	Class C25/30 Concrete with 10-30 aggregate according to UNI EN 12620 standard. Bollard shall be installed after at least 7 days of concrete setting; using a proper additive, it's possible to reduce to 3 days
35	Surrounding ground compacting index	≥ 90% of the Proctor optimum curve, according to UNI EN 13286-2:2005 standard

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description
1	Secured and fully covered Store area to keep the material
2	Scaffolding/Hydra/Crane/Forklift Etc - Required for Installation at Site
3	Electrical Supply on the site single phase/three phase points at different places.
4	Any civil / masonry/structural work required
5	All structure support required
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.
7	Conduits, Cables required

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 10 - 12 weeks from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

Please feel free to Contact **Mr. Vijay Tarak on 8551093333** For any further Clarification /Information in this Concern.

With Best Regards
Shailesh Bhoir
8551091333
For NIHVA Technologies Pvt Ltd