

Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
UC-Under Cut
FFL-Finished Floor Level

ASSESORIES DETALES

(a) HINGES: SS Ball bearing butt hinges 100x75x3mm.(iclean)

(b) LOCK: Mortise dead lock,Cylinder(Both side key) with Escutcheon (iclean)


(c) DOOR CLOSER (iclean)

(d) GLASS : Single glazed 5mm Thick Vision Glass of size 200x800mm


(e) HANDLE : D Handle(254mm) (iclean)

Shutter thickness : 47 mm
Frame Sheet thick : 1.2mm
Shutter sheet thick : 0.8mm
Fixing : On Solid Brick plastered wall with Anchors
Electrostatic powder coated


NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.



Elevation



Top View



Detail view of Section A

COLOR -

STEEL DOOR SIZES			
WOW	WOH	QUANTITY	LOCATION
1000	2100	20	GROUND FLOOR
800	1600	3	
900	2100	1	
1000	2100	6	FIRST FLOOR
600	2100	5	
1200	2100	1	
800	1600	2	

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

SINGLE LEAF STEEL DOOR

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	NAME	DATE	SIGN.
DRAWN	OMKAR	11/03/16	
CHECK	ANIL	11/03/16	
REV.	00		
APPRD.			
MFG			

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT - HYOSUNG T&D
PROJECT -
SITE -
DWG. NO. - NIHVA/15-16/211
SCALE: 01 | WT: | SHEET: 01 OF 01
If any queries contact : projects@nihva.com