Sr no	Specification	Unit	NIHVA Dock leveller	ASSA ABLOY - Crawford Dock Leveller
1	Basic Capacity	kg	**15000 Dynamics**	**15000 Dynamics**
2	Dock Leveler Size Length	mm	2500	2500
3	Dock Leveler Size Width	mm	2000	2000
4	Dock Leveler Size Height	mm	550	600
5	Working Range Above/Below	mm	(+)300/ (-)250	(+)520/ (-)350
6	Slope	degree	10%	12.50%
7	Tilt Compensation	mm	100	100
8	Lip size	mm	2000(w)X400(L)	2000(w)X400(L)
9	Power Pack	Hp	1 HP	1 HP
10	Control Panel operating Push button details	Nos	4 push button . (Platform Up & Down, Lip Up & Down)	Two push Button
11	Colour	RAL sed	As per client requirement	RAL5010
12	Top Surface thickness in	mm	8	8
13	Lip Surface thickness in	mm	16	8
14	Power pack pump make ,type & model	NA	Hydrotech	Assa Abloy
15	Control panel switch gear makes	Na	NA	NA
16	Working pressure	Bar	100	100
17	Control panel IP protection	NA	IP55	IP54
18	Input supply Requirement	3 Phase voltage & Current requirement	3 Phase - 400 volt	3 Phase - 400 volt
19	PIT W L H	MM	2080X2500X555	2040 X2520X605
20	TRAILER HT CONSIDERED	M	1300	1300
21	Hose Burst Value / NRV	NA	Included	Included
22	Bumper s 2 nos	Nos	Included	Included
23	Maintenance work safety stopper	NA	Included	Included
24	Price	INR	220000	
25	Installation	INR	Included	Included
26	Freight	INR	Included	Included