A guide to preventative maintenance for Albany High Performance Doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions



Crash System

What is the function?

- Prevents damage to the bottom beam, which can lead to damage on the side frame
- Reduces the cost of accidents
- Allows the door to remain in function
- Carries the wind load even after a crash

What is the manufacturer's specification?

To make sure the manufacturer's specifications are observed, replace according to door type related specification sheet

Can I also replace it earlier?

- Yes, if there are visible damages to the sliding part
- If there is wear on sliding parts or ropes
- If the bottom beam is bent due to crashes

How do they wear?

During the lifetime of the crash system there will be wear and tear due to:

- A damaged sliding part or PVC-washer, if crashed several times
- Wear on sliding piece due to steel rope (RR600SRD) and on rope itself due to abrasion (RR355)
- Scratches and bumps on bottom beam due to the contact with fork-lifts or other vehicles

What is the risk of not replacing?

When not following the manufacturer's specifications the customer is taking the responsibility for unintended breakdown, e.g.:

- The wind resistance will be reduced, which can lead to unintended stops. When the bottom beam breaks out of line it triggers the crash sensor, which causes the door to stop
- The rope can break which can lead to a broken spring (see curtain tension)
- Crash detection may not work due to broken PVC washer, i.e. the door will continue running after crash

Top reasons for preventive maintenance

- Keeps the warranty valid
- Prevents unexpected and expensive break-downs
- Prolongs lifetime
- Cost saving
- Minimises risk of personal injury
- Minimises energy loss
- Fulfills legal requirements
- Improves working environment

©ASSA ABLOY Entrance Systems AB/PLMAP/DEU-EN-1.0/1504

ASSA ABLOY ENTRANCE SYSTEMS Maintenance & Modernization