Supply & Installtion of Telescopic belt conveyor		**Supplier Name**	**NIHVA Technologies**
Technical Specifcations - Telescopic Belt conveyor		**Contact No**	**Vijay 8551093333**
DOC REF	**STD-LE-BQ-R0-RFP-TELESCOPIC BELT CONVEYOR**	**Address**	**Pune maharashtra**
DRG NO	**LT000025**	**Manufacturer name**	**NIHVA Technologies**

TECH SPECS-SYSTEM COMPNENTS- SUGGESTED BY CLIENT

Sl no.	Type	Technical Specifications	Customer specification			Supplier Remarks
			UOM	Ref	Specs.	
CA-TS-1	General	Description	yes/no		Telescopic belt Conveyor for movement of irregular Bags of size 1000 x 500 x 500 mm into and out of the trucks .Max - 32 feet truck	OK
CA-TS-2		Technical Detail Drawing Provided	yes/no		NA	After PO reciept
CA-TS-3		Deviation Sheet Duly Populated - Declare Yes or No	yes/no		yes	Supplier to indicate Deviations with Full Clarity in the Deviation Template provided.
CA-TS-4		Safety Precautions Acceptable	yes/no		yes	EHS document to be referred.(Will refer seperatly)
CA-TS-5		Compliance to Safety Standards, Laws & Regulations Incl. the EHS Guidelines of Customer	yes/no		yes	EHS document to be referred.(Will refer seperatly)
CA-TS-6	Shipment Size & Typ	Shipment Min Size	mm		300mm x 100mm x 200mm Poly Bags & Carton Boxes	Ok
CA-TS-7		Shipment Max Size	mm		1016 mm x 508 mm x 508 mm Poly Bags & Carton Boxes	Ok
CA-TS-8		Shipment Min Weight	kg		1 kg (Poly Bags & Carton Boxes)	Ok
CA-TS-9		Shipment Max Weight	kg		25 (Poly Bags & Carton Boxes)	Ok
CA-TS-10		Shipment Type	Typ		Irregular shaped Nylon Bags / Regular Shaped Carton Boxes	Ok
CA-TS-11	Telescopic Belt Conveyor	Manufacturer Name	Name		Supplier to Specify	NIHVA Technologies
CA-TS-12		Nominal width	mm		1000	800 mm belt width we connsidered
CA-TS-13		Overall Height (Max) Exc Guide	mm		450 - 500 Max	850 mm total height from ground to belt top .
CA-TS-14		Collabsed Length	mm		5000	Ok
CA-TS-15		Extended Lebgth	mm		15000 (5000 + 10000mm extension)	Ok
CA-TS-16		Drive Power Rating- Belt Drive	kW		2.2- 3	Depend on design
CA-TS-17		Drive Power Rating - Conveyor Extension	kW		0.55-0.75	Depend on design
CA-TS-18		Drive Power Rating - Elevation	kW		NA	NA
CA-TS-19		Rated Voltage (Nom)	V		415	Ok
CA-TS-20		Drive Control	Typ		VFD	Ok
CA-TS-21		Type of Drive System	Typ		Geared Motor (Non Worm Type)	worm type
CA-TS-22		Geared Motor Make	Name		SEW Euro drive Geared Motor - Hollow Shaft with Torque Arm Only	Ok
CA-TS-23		Stand Design	Typ		Fixed	Stand is grouted to earth
CA-TS-24		Belt Type	Typ		PVC / PVK - Rought top	PVC black belt is ok for this ,
CA-TS-25		Belt Spec	Typ		Habasit or Forbo	Forbo make we use
CA-TS-26		Belt Joints	Typ		Mechanical	Ok
CA-TS-27		Bed Type	Typ		Slider Bed with Prepainted/Coated Galvalume	We use skid plate below the belt with powder coated
CA-TS-28		Actuation / Switch	Typ		Required at Panel and and at the front of the conveyor	Joystick type at the front (Ok)
CA-TS-29		Roller Support			NA	Na
CA-TS-30		Conveyor Speed (Nom)	m/s		0.4	Ok
CA-TS-31		Conveyor Speed (Max)	m/s		0.5	Ok
CA-TS-32		Conveyor Speed (Min)	m/s		0.3	Ok
CA-TS-33		Load capacity per unit length of Conveyor	kg/m		50	Ok
CA-TS-34		Belt Thickness (Nom)	mm		3	2.3 mm to 3 mm