High Performance Door
Rapid Roll® 300 Plus
(High Speed Door)



Door type	RR300 Plus	PL. indicate your requiremen
Description	Flexible High Performance Door, opening in vertical direction for interior use in wind-protected areas	
Side frames	Made of aluminum	
Door curtain	Made of transparent PVC with fabric reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar to RAL 3002).	
Top roll	Made of anodized aluminum	
Wind protection	wind tabs on the door curtain	
Wind resistance	Class 1 (EN 12424).	
Bottom profile	anodized aluminum	
Drive unit	Hollow shaft gear motor	
Protection	IP 55	
Control system	ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC	
Supply voltage	ACS 50: 3L(N)PE/230/380/400/415V, 50Hz Transformer necessary for 440/480/500V 50Hz	
Safety devices	electrical safety contact edge, evaluation via integrated cable chain, door line photocell in the side frames, drop down protection by integrated balancing system	
Manual activation	By releasing the brake at ground level. Depending on width/height ratio the door opens up to max. 2.0 m	
Opening / closing Speed	Up to max. 1.2 / 1.2 m/s.	
Size max	(DWxDH) 5000 x 5000 mm.	

Make	ALBANY RapidRoll® 300 Plus Alu	
Options:		
Surface / material: **Covers**	Top roll cover required for doors DH < 2500 mm Motor cover required for doors DH < 2500 mm	
Door curtain (alternatively):	PVC with coloured reinforcement stripes: ➢ Beige (similar RAL 1014), ➢ Yellow (similar RAL 1021), ➢ Orange (similar RAL 2011), ➢ Green (similar RAL 6018), ➢ White (similar RAL 9016) or ➢ Grey (similar RAL 7035). ➢ PVC with silicone-free reinforcement stripes - colour ➢ Blue (similar RAL 5010), ➢ Alu-grey (similar RAL 7037), ➢ Red (similar RAL 3002), ➢ Yellow (similar RAL 1021), ➢ Orange (similar RAL 2011), ➢ White (similar RAL 9010), ➢ Black (similar RAL 9005). ➢ Curtain made of RollTex® Plus - colour ➢ blue (similar RAL 5002), ➢ orange (similar RAL 2009) or ➢ grey (similar RAL 7001) ➢ Curtain made of RollTex® Original - colour ➢ Blue (similar RAL 5002), ➢ Orange (similar RAL 5002) or ➢ Grey (similar RAL 7001) ➢ Curtain made of NomaTex® - colour ➢ Grey (similar RAL 7038, varnishable on request) ➢ Window (DWxDH) 500x700mm (only for	

	RollTex® or NomaTex®) ➢ Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®) ➢ Vision panels for curtain NomaTex® ➢ Curtain made of NomaTex® flame retardant without vision panels or window- colour grey (similar RAL 7045) ➢ Curtain made of fabric type travitop - colour ➢ Blue (similar RAL 5010), ➢ red (similar RAL 3002) or ➢ grey (similar RAL 7035) ➢ vision panels for curtain type travitop	
Control system (alternatively)	Frequency converter control system MCC^{VectorControl}, based on vector control including boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service, ➢ (open/close) up to max. 2,2/0,9 m/s, ➢ Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz , ➢ Transformer necessary for 220/230/500V	
Miscellaneous	➢ Knock-out capability with sensor, only for version with coil cable (without interior cable chain), ➢ Not possible in combination with integrated light curtain ➢ Integrated light curtain not possible in combination with knock-out function ➢ Automatic egress on power failure ➢ Extended flexible seal ➢ Actuators	
Option: Escape and rescue routes		
Size max.	(DWxDH) 4000 mm x 4000 mm	

Wind resistance	class 1 (EN 12424) up to DH = 3500 mm, class 0 (EN 12424 at DH > 3500 mm	
Control unit	Solely frequency converter control MCC^{VectorControl} with extension and special software (configuration).	
Drive unit	Hollow shaft gear motor with operating current brake	
Emergency opening	➢ In case of power failure the door opens automatically, the door can be opened manually via the main switch/CEE plug ➢ A radar motion detector for the detection of people is included in delivery. ➢ Key switches for the deactivation of the escape and rescue function is optionally available.	
Delivery	Installation incl. wiring	