S.NO.	TECHNICAL SPECS	VERTICAL SLIDING WINDOW
1	**Frame material**	Aluminuim Grade 6063 T6
2	**Frame profile size**	40mm X 42mm
3	**Guide Size**	70mm X 217mm (6000mm X 4000mm), 70mm X 163.5mm (6000mm X 2000mm)
4	**Glazing material**	Laminated Toughen Glass
5	**Glazing thickness**	8mmT
6	**Motorisation**	220VAC Single phase 50/60hz
7	**Activation System**	Wireless remote control (MC200 receiver 50hz)
8	**Motor mounting**	Top mount motor
9	**Motor mounting space**	163mm X 192mm
10	**Finish**	Electrostatic baked on powder coating
11	**Standard RAL**	RAL 8003, RAL 9005, RAL 9010, RAL 1019, RAL 7016, RAL 8014, RAL 9006, RAL 7024
12	**Weather seals**	Silent fin, brush pile with PVC fin & EPDM gasket
13	**EN standard & Certification**	EN 12208 (Water tightness) EN 12210 (Resistance to safety load) EN 12207 (Air permeability) EN 12210 (Resistance to wind load) CE Certification
14	**Limitation of space**	System rest inside the exisitng space. No projection outside or inside of the area
15	**Side Guide mounting space**	Center of the opening , within the frame, and looks seamless
16	**Motor Visibility**	Completely concealed inside the top cover. Not visible from inside or outside
17	**Noise Insulation**	More insulation and wider air gap between glass
	Thermal Insulation	Ug Value is lower, lesser the temperature loss
18	**Vertical profile pitch**	3000 mm (to maintain exisiting façade symmetry)
19	**Horizontal profile pitch**	1000-1100 mm
20	**System Safety feature**	Mechanical lock in stationary position
21	**Aesthetic View**	Panormic view with elegant and high quality product. Aesthetically matches the surrouding.