GANDHI
Automations Pvt Ltd

India's No.1 Entrance Automation & Loading Bay Equipment Company

Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

14869-R1/Q/2526 January 28, 2026

Pravisree
No. 65/68, 8th Main, JC Industrial
Estate, Bangalore-560078,
Karnataka, India.

Kind Attn: Mr. Prajwalesh Gupta

Dear Sir,

We thank you for the interest shown in our products and pleased to provide our detailed offer consisting the following:

A. Commercial Offer for Motorised Rolling Shutter

B. Optional Accessories

C. Terms and Conditions

D. Technical Specifications

We look forward to receiving your order in the near future.

Should you have any further queries please do not hesitate to contact us at any time.

Thanking and assuring of our best services.

Best Regards,

Pratima Karande
Manager - Business Development
Mobile : +91 73044 40640
Landline : +91 22 6672 0218

GANDHI
Automations Pvt Ltd

India's No.1 Entrance Automation & Loading Bay Equipment Company

Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240



A] COMMERCIAL OFFER

Offer No. & Date : 14869-R1/Q/2526 dtd January 28, 2026
Project : Self, Industrial
Location : Bangalore-560078, Karnataka
BOQ/Enquiry Reference : Not Applicable
Drawing Reference : Not Applicable
Drawing No. & Dt. : Not Applicable

Option-1 : Motorised RS78GS Rolling Shutters with Compact Gear P.R.C. Make Indirect Drive Operator

Sr. No.	Item Description	HSN Code	Size		Qty Nos	Purchase order to be issued for supply cost		Service order to be issued for installation	
			Clear Width (mm)	Clear Height (mm)		Unit Rate INR	Total Cost INR	Unit Rate INR	Total Cost INR
1	Motorised Rolling Shutter - Model: RS78GS - Curtain made of single skinned Galvalume steel laths with natural finish - Pressed galvalume steel hood & motor cover with natural finish - CE Certified CRS Compact Gear P.R.C. Make Indirect Drive Operator - External Safety Brake - Three station push button with deadman control - Inbuilt Wicket Door - 1 No. Size: 900mm x 1850mm	7308	5490	10940	2	7,21,000 Included	14,42,000 Included	72,000	1,44,000
						Total	14,42,000		1,44,000
	Packaging Charges						28,840		
	Freight Charges (40 Feet Trailer - 1 No.)						1,14,000		
	Transit Insurance						Inclusive		
	GST on Supply & Installation					@18%	2,85,271		25,920
	Total Supply & Installation with Tax						18,70,111		1,69,920
	Grand Total with Tax								**20,40,031**
	All applicable taxes at the time of dispatch will be charged extra								
	GSTIN : 27AACCG0522G1Z3								
	SAC Code : Installation Charges-998732								

GANDHI
Automations Pvt Ltd

India's No.1 Entrance Automation & Loading Bay Equipment Company

Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240



Option-2 : Motorised RS78GS Rolling Shutters with European Make Indirect Drive Operator

Sr. No.	Item Description	HSN Code	Size		Qty Nos	Purchase order to be issued for supply cost		Service order to be issued for installation	
			Clear Width (mm)	Clear Height (mm)		Unit Rate INR	Total Cost INR	Unit Rate INR	Total Cost INR
1	Motorised Rolling Shutter - Model: RS78GS - Curtain made of single skinned Galvalume steel laths with natural finish - Pressed galvalume steel hood & motor cover with natural finish - CE Certified European Make Indirect Drive Operator - External Safety Brake - Torque Enhancement - Three station push button with deadman control - Inbuilt Wicket Door - 1 No. Size: 900mm x 1850mm	7308	5070	10940	2	10,13,000 Included	20,26,000 Included	72,000	1,44,000
						Total	20,26,000		1,44,000
	Packaging Charges						40,520		
	Freight Charges (40 Feet Trailer - 1 No.)						1,14,000		
	Transit Insurance						Inclusive		
	GST on Supply & Installation					@18%	3,92,494		25,920
	Total Supply & Installation with Tax						25,73,014		1,69,920
	Grand Total with Tax								**27,42,934**
	All applicable taxes at the time of dispatch will be charged extra								
	GSTIN : 27AACCG0522G1Z3								
	SAC Code : Installation Charges-998732								



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

B] OPTIONAL ACCESSORIES

Description	Unit Rate (INR)
For Motorised Rolling Shutter	
- Additional three station push button	3,500 /-

Note : Packaging charges, Freight & GST on above optional accessories will be charged extra.



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

C] TERMS AND CONDITIONS

Exclusions:

- Unloading of consignment, safe storage at site until installation, shifting the consignment at the installation location, civil work, c-channel, structural support, hydra, ladder or scaffolding (if required) for installation will be in the client's scope.

- During the period of installation, any shortage of material due to pilferage, misplacement etc. at site would be in client's account.

- Further, if due to storage at site / warehouse for prolonged periods, the refurbishment from the weather deterioration like rust removal, re-painting etc. will be in client's account.

- Electrical wiring for providing single / three-phase AC supply through a separate MCB upto point of installation will be done by the client. Cables, Conduit & Cable trays required for installation of accessories will be supplied & laid by the client.

- Client shall provide a stabilized, uninterrupted power supply.

Warranty:

- Warranty for automation system against manufacturing defect will be provided for a period of 12 months from the date of installation or 13 months from the date of invoice whichever is earlier.

Payment Terms:

- For Supply: 75% advance along with Purchase Order, 25% against Proforma Invoice prior to despatch.

- For Installation: 50% mobilisation advance and 50% immediately after installation on pro rata basis.

Delivery Terms:

- FOR Site, Bangalore - 560078, Karnataka
  The freight charge given in above offer is applicable only for one time delivery & not for partial shipment.
- Vehicle Considered:- 40 Feet Trailer - 1 No.

Validity of Offer:

- 30 days from the date of offer.



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

D] TECHNICAL SPECIFICATIONS

Offer No. & Date	: 14869-R1/Q/2526 dtd January 28, 2026
Project	: Self, Industrial
Location	: Bangalore-560078, Karnataka
BOQ/Enquiry Reference	: Not Applicable
Drawing Reference	: Not Applicable
Drawing No. & Dt.	: Not Applicable

Option-1

Shutter Type: Gandhi® Motorised Rolling Shutter

Serial No	Clear Width (mm)	Clear Height (mm)	Quantity (Nos)
1	5490	10940	2

Performance Characterstics

Profile Type	RS 78GS
Profile Height	78mm
Roller Curtain	The shutter curtain is constructed from **Tata Bluescope / JSW 150 gsm** single skinned galvalume steel laths. Each lath is retained by interlocking with each other.
Surface	Galvalume with natural finish
Material Thickness	0.9mm
Structure Shape	Curved
Support Brackets	Mild Steel with one coat of grey epoxy primer by spray
Shaft	Shaft is manufactured from mild steel tube of suitable outside diameter and wall thickness to suit the shutter application and is unsprung
Finish	One coat of grey epoxy primer by spray
Side Guides	2.0mm thick heavy duty TG Galvanised Steel
Finish	One coat of grey epoxy primer by spray
Bottom Profile	Bend-resistant double-skinned extruded Aluminium profile for additional strength. The bottom rail is fitted with extruded rubber bottom seal that will seal against the floor when the door is fully closed. Galvanised steel profile available on request
Finish	One coat of grey epoxy primer by spray
Locking arrangement	Optional [applicable only for Galvanised steel Bottom profile]
Seals	Optional on side guides
Wind lock-Storm anchors	Included
Hood Cover	Pressed galvalume steel hood box complete with reinforced bracket as required to suit the shutter width.
Finish	Natural Finish
Surface with protective paint	Optional

CE Certified CRS Compact Gear P.R.C. Make Indirect Drive Operator with External safety brake

Drive Unit	Indirect drive operator System power supply wired with industrial plug
Safety mechanism	Safety brake in accordance with EN 14121-1: 2007 Safety of machinery The installation of safety brake for heavy rolling shutters performs two functions:



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

Safety mechanism	- A bearing support for the shutter's shaft - A mechanical brake blocking the descent of the shutter if sudden acceleration occurs This is a safety feature that will eliminate the possibility of the curtain free falling in the event of a motor failure.
Control Switch	Three station push button with deadman control
Emergency manual operation	Emergency operation by means of chain
Motor Cover	Pressed galvalume steel motor cover with natural finish.

Included Accessories

- Inbuilt Wicket Door - 1 no. Size: 900mm x 1850mm

Optional Accessories

- Additional three station push button

GANDHI
Automations Pvt Ltd
India's No.1 Entrance Automation & Loading Bay Equipment Company



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

Option-2

Shutter Type: Gandhi® Motorised Rolling Shutter

Serial No	Clear Width (mm)	Clear Height (mm)	Quantity (Nos)
1	5070	10940	2

Performance Characterstics

Profile Type	RS 78GS
Profile Height	78mm
Roller Curtain	The shutter curtain is constructed from **Tata Bluescope / JSW 150 gsm** single skinned galvalume steel laths. Each lath is retained by interlocking with each other.
Surface	Galvalume with natural finish
Material Thickness	0.9mm
Structure Shape	Curved
Support Brackets	Mild Steel with one coat of grey epoxy primer by spray
Shaft	Shaft is manufactured from mild steel tube of suitable outside diameter and wall thickness to suit the shutter application and is unsprung
Finish	One coat of grey epoxy primer by spray
Side Guides	2.0mm thick heavy duty TG Galvanised Steel
Finish	One coat of grey epoxy primer by spray
Bottom Profile	Bend-resistant double-skinned extruded Aluminium profile for additional strength. The bottom rail is fitted with extruded rubber bottom seal that will seal against the floor when the door is fully closed. Galvanised steel profile available on request
Finish	One coat of grey epoxy primer by spray
Locking arrangement	Optional [applicable only for Galvanised steel Bottom profile]
Seals	Optional on side guides
Wind lock-Storm anchors	Included
Hood Cover	Pressed galvalume steel hood box complete with reinforced bracket as required to suit the shutter width.
Finish	Natural Finish
Surface with protective paint	Optional

CE Certified European Make Indirect Drive Operator with External safety brake

Drive Unit	Indirect drive operator with Torque Enhancement System: 415V, 3P/N/PE/50 Hz, in accordance to the EEC standards EN 12453 System power supply wired with industrial plug, push button integrated in the housing lid
Safety mechanism	Safety brake in accordance with EN 12605: The safety brake is equipped with a patented shock- absorber system and a microswitch for disconnecting the electrical supply to the motor when the brake locks. The installation of safety brake enables to fully comply with the EN 12604 safety rule for heavy rolling shutters and performs two functions: - A bearing support for the shutter's shaft - A mechanical brake blocking the descent of the shutter if sudden acceleration occurs This is a safety feature that will eliminate the possibility of the curtain free falling in the event of a motor failure.



Registered Office : Chawda Commercial Centre, Link Road, Malad (W), Mumbai - 400064, India • STAR EXPORT HOUSE (Government of India Recognised)
Tel : +91 22 6672 0200 / 0300 (200 Lines) • Fax : +91 22 6672 0201 • Email : sales@geapl.com • Website : www.geapl.com • CIN : U31909MH2003PTC143240

Control Switch	Three station push button with deadman control which, for safety reasons, only allows a shutter to move as long as the operating button is being pressed. The control mechanism can be upgraded with the addition of further modules to function automatically.
Emergency manual operation	Emergency operation by means of chain
Motor Cover	Pressed galvalume steel motor cover with one coat of grey epoxy primer by spray

Included Accessories

- Inbuilt Wicket Door - 1 no. Size: 900mm x 1850mm

Optional Accessories

- Additional three station push button