Vertical Sectional Door- 4900 x 5500 mm

Sr. No	Description	Specification
1	**Model No**	ASSA ABLOY OH1042P
2	**Opening Direction & Mounting**	Vertical Lift
3	**Opening/Closing Speed**	CDM9 0,28 m/s
4	**Door Material**	Steel
5	**Panel Thickness**	42 mm
6	**Filling**	CFC-free polyurethane
7	**Door sealent**	All door sealants made of EPDM rubber, temperature resistant - 30/+70
8	**Water Penetration**	EN 12425 class 3
9	**Air Permealibity**	EN12426 class 3
10	**Thermal Transittance**	EN 12428 1.10W /m2K
11	**Bottom sealing**	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
12	**Door saftey**	Doors equiped with spring break device
13	**Incase of Power failuer**	Doors to be equiped with quick release fuction
14	**Operator power conumption**	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
15	**Drive Unit & Mounting Type**	Single phase 230V direct drive on shaft
16	**Emergency Operation**	by Disengagement rope manual
17	**Operating Switch**	Up/Down Keypad + stopbutton
18	**Locks : Lock bolt**	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
19	**Environmental Green Product Declaration Certification**	As per ISO 14025 and EN 15804

Horizontal HL Sectional Door- 4800 x 4500 mm

Sr. No	Description	Specification
1	**Model No**	ASSA ABLOY OH1042P
2	**Opening Direction & Mounting**	Horizontal High Lift
3	**Opening/Closing Speed**	CDM9 0,28 m/s
4	**Door Material**	Steel
5	**Panel Thickness**	42 mm
6	**Filling**	CFC-free polyurethane
7	**Door sealent**	All door sealants made of EPDM rubber, temperature resistant - 30/+70
8	**Water Penetration**	EN 12425 class 3
9	**Air Permealibity**	EN12426 class 3
10	**Thermal Transittance**	EN 12428 1.10W /m2K
11	**Bottom sealing**	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
12	**Door saftey**	Doors equiped with spring break device
13	**Incase of Power failuer**	Doors to be equiped with quick release fuction
14	**Operator power conumption**	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
15	**Drive Unit & Mounting Type**	Single phase 230V direct drive on shaft
16	**Emergency Operation**	by Disengagement rope manual
17	**Operating Switch**	Up/Down Keypad + stopbutton
18	**Locks : Lock bolt**	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
19	**Environmental Green Product Declaration Certification**	As per ISO 14025 and EN 15804