High Performance Door Rapid Roll® 300



Door type	RR_300	PL. indicate your requirement
Description	Flexible High Performance Door, opening in vertical direction for interior use in wind-protected areas.	
Self-supporting side frames	Made of galvanized steel, all fittings galvanized.	
Door curtain	Made of transparent PVC material with coated fabric reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar to RAL 3002).	
Top roll	made of aluminum	
Wind protection	Through wind tabs on the door curtain.	
Wind resistance	Class 1 (EN 12424).	
Bottom profile	Anodized aluminum.	
Drive unit	Hollow shaft gear motor.	
Protection	IP 55	
Control system	ACS 50, electric control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC	
Supply voltage	ACS 50: 3L/(N)PE 220/230/380/400/415V; 50Hz Transformer necessary for 440/480/500V	
Safety devices	Electrical safety contact edge, door line photocell, drop down protection integrated in gear box.	
Manual activation	By means of a crank.	
Opening / closing Speed	Up to max. 1.0 / 1.0 m/s.	
Size max	(DW x DH) 3500 x 3500 mm	
Make	ALBANY RapidRoll® 300	
Options		
Surface / material:	side frame made of stainless steel Control box made of stainless steel V2A - IP 65 Top roll / shafts made of stainless steel V2A Bottom profile made of stainless steel V2A	
Covers	Top roll cover Motor cover	
Door curtain (alternatively):	PVC with coloured reinforcement stripes Beige	

	(similar RAL 1014), Yellow (similar RAL 1021), Orange (similar RAL 2011), Green (similar RAL 6018), white (similar RAL 9016) or grey (similar RAL 7035) – PVC with silicone-free reinforcement stripes – Curtain made of non-transparent fabric, type travitop Blue (similar RAL 5010) red (similar RAL 3002) or grey(similar RAL 7035) only available without curtain tension – vision panels for door curtain type travitop – Curtain made of RollTex® Plus – colour Blue (similar RAL 5002) Orange (similar RAL 2009) or Grey (similar RAL 7001) Curtain made of RollTex® Original – colour Blue (similar RAL 5002) Orange (similar RAL 2009) or Grey (similar RAL 7001) – Curtain made of NomaTex® – colour grey (similar RAL 7038) – Window (DWxDH) 500x700mm (only for RollTex® or NomaTex®) – Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®) – Curtain made of NomaTex® flame retardent, without vision panels or window - colour grey (similar RAL 7045)	
Control system (alternatively)	ASC 25 (open/close) up to max. 0,8 m/s, Supply voltage 3L(N)PE/220/230/380/400/415V;50Hz, Transformer necessary for 440/480/500V 50/60 Hz Frequency converter control system MCCVectorControl, based on vector control including boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information regarding operation and service, (open/close) up to max. 2.3/1,0 m/s, Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz, Transformer necessary for 220/230/500V, 50/60 Hz	
Miscellaneous	Knock-out capability with sensor Extended flexible seal Actuators Additional safety devices	
Alternatively	(Version "Mini" for reduced space requirements over the lintel DWxDH up to 2000 x 3000 mm, Wind resistance class 0 (EN 12424), due to limited weight of door curtain no drop down protection required)	
Delivery	Installation incl. wiring	