Product:

NIHVA Double Wall Rolling Shutter

Clear Opening dimension (w) -- x (h) -- :

W)…… x (H) ……. std. dimension or non. std. dimension Double acrylic vision panels

Opening Direction: Vertical - from bottom to Top

Mounting Location area: Only Inside area

Mounting Surface: Side Brackets: Optional = On Concrete / Steel & Side Guides : Optional = On Concrete/Steel / Masonry

Opening/Closing Speed: 0.1 m/sec

Wind Resistance: 120 Km/hrs.

Slats material: insulated pre coated Galvanized steel (Polyurethane foam)

Slat size: 95mm x 19mm with PU filled inside

Curtain Panel: The panel made of 1.0mm thick CRCA steel

Curtain Profile: Corrugation

Slat (made in Option): Optional - German slats / China slats

Bottom Profile: 125mm x 15mm with extra angle support. (Optional - Rubber BottomSeal)

Side Guide Profile: M.S." U" Shaped profile 125 x 40mm x 3 mm thick (as per the opening width dimension)

Roller Shaft: MS Plate 3 mm to 10 mm thick , as per the opening dimension

Side Brackets: MS Plate 3 mm to 10 mm thick , as per the opening dimension

Hood Cover: Made of GI Sheet Thickness 0.8 mm with 25x25x3mm angle stiffener

Surface finish

Painting: Powder coated – Off white color

Vision Windows: With Vision Window / without Vision Window

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com

Automation

Control Type: Optional = Dead man / Pulse Control

Drive Unit & Mounting Type:

Option 1) Electric Motor (Imported German Make) (Single Phase/Three Phase) - Direct Mounting on Shaft
Option 2) Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement

Emergency Operation:

Option = Manual Hand Driven / Chain Wheel Drive

Operating Mode:

Option = Push Button from inside / or do you need Outside also

Option = Push Button / Key Switch From Outside

Integration optional:

Option = need to interlock or integrate with other door or machine or Equipment

Accessories: Option = Flashing Light / Safety Photocell / Remote Control

Installation Constraint any:

Need to be check = Space requirements + sub structure scope of work + Mounting access + Access in the event of power cut + clear opening dimensions

***** Option = need to select or specify your requirement by choosing Option, so clear communication will happen between us.***