Aluminum High Performance Door Rapid Roll® 3000
(High Speed Door)



Door type	RR3000	PL. indicate your requirement
Description	Aluminum High Performance Door, opening in vertical direction, for interior and exterior use	
Side frames	Edged galvanized steel profiles. Springs for curtain tension and counterbalance in the side frame.	
Door curtain	Ecru anodized double walled aluminum lamellas, hinge less connected by means of flexible heavy belts, wear-less to wind up without to contact each other, each single lamella can be replaced easily, pre-fitted on the top roll.	
Wind protection	Class 3-4 (EN 12424)	
Drive unit	Gear motor, pluggable electrical connections	
Protection	IP 55	
Control system	MCCVector Control, with vector control technology and boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service	
Control voltage	24 V DC	
Supply voltage	3L/(N)PE 380/400/415/440V; 50/60 Hz Transformer necessary for 230/480/500V; 50/60 Hz	
Safety devices	➢ Patented, contact-free pre-running safety photocell (transmitter/receiver) ➢ Stationary safety photocell (transmitter/receiver) ➢ Drop down protection by integrated balancing system	
Manual activation	By releasing the brake at ground level. Partly opening by means of the pre-stressed tension springs	
Opening / closing speed	Up to max. 2,2/0,7 m/s	

Size max	(DW x DH): 5000 x 5000 mm	
Make	ALBANY Rapid Roll® 3000	
Options:		
Covers	➢ Top roll cover made of anodized aluminum ➢ Motor cover made of anodized aluminum	
Surface/material	➢ Side frames with covers made of anodized aluminum ➢ Side frames colored ➢ Aluminum lamellas colored	
Miscellaneous	➢ Lamellas with windows ➢ insulation ➢ extended flexible seal	
Actuators	Additional safety devices	
Delivery	Installation incl. wiring	