Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR355

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

© ASSA ABLOY Entrance Systems AB PL.MAN/RR355/DEU.EN-1.1/1504 / 64 100 480 Technical data subject to change without notice

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR355

Product group	Description	150.000 cycles	500.000 cycles	500.000 cycles or 10 years	1.000.000 cycles	1.000.000 cycles or 5 years	5 years	10 years	wear / tear related
Actuators	Safety photocell re / tr							●	
Cable chain	Cable chain, complete with cable and bracket		●						
Counterbalancing	Curtain tension / weight counterbalance complete		●						
	Rope	●							
	Rope pulley with screw		●						
Curtain	Set of wind tabs		●						
	Curtain including top roll								●
Top roll	Flange bearing		●						
	Top roll with curtain		●						
Bottom profile	Rubber profile with contact strip						●		
Crash	Proximity switch							●	
	Sliding part for crash		●						
	Swiveling roller		●						
	Tappet down		●						
Sliding/Guiding	Sliding part safety edge / prerunning photocell			●					
Drive unit	Chain drive unit				●				
	Chain wheel - frequency converter				●				
	Drive unit - contactor control		●						
	Drive unit - frequency converter				●				
	Microswitch					●			
Chain drive	Chain wheel - frequency converter				●				
	Roller chain complete				●				
	Shaft with chain wheel				●				
Brake	Brake - contactor control		●						
	Brake - frequency converter				●				
Encoder	Double Proximity switch							●	
	Encoder 50 pulses, only electronic part							●	
Damper	Vibration absorber		●						
Electronic / PCB	Junction box							●	

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization