DESIGN OF ROLLING SHUTTER

WIND SPEED	47	M/SEC			
WIND PRESSURE	1325.4	N/SQM			
or	0.001325	n/sqmm			
WIDTH	8000	mm			
HEIGHT	8000	mm			
MAX MOMENT	4750.234	nmm			
MOMENT IN 75 MM PLATE	356.2675	nmm			
m.i.	1564	mm^4			
Length	8000	mm			
Deflection	7.231509	mm			
Permissible Deflection L/250	32	mm			
Stress	1.708444	n/sqmm	<165	n/sqmm	

Max Deflection	5xMXL^2/(48XEXI)
i	Moment of inertia
E	2.1*10^5
Stress	B.M*7.5/I

Permissible Deflection as per IS 800 L/250

SATISH M. GHANEKAR
LISCENCED STRUCTURAL ENGINEER
L. NO. 135 (PMC)
4, Sant Kripa Commercial Complex, Yamunanagar, Nigdi, Pune 44

DESIGN OF ROLLING SHUTTER

WIND SPEED	47	M/SEC			
WIND PRESSURE	1325.4	N/SQM			
or	0.001325	n/sqmm	W		
WIDTH	8200	mm	L		
HEIGHT	8200	mm			
MAX MOMENT	11139.99	nmm			
MOMENT IN 75 MM PLATE	835.499	nmm			
M.I.	1564	mm^4	I		
Length	8200	mm			
Deflection	237.5665	mm			
	Assuming Simply supported flat				
Permissible Deflection L/250	32.8	mm			
Stress	4.006549	n/sqmm	<165	n/sqmm	

Max Deflection	5xWXL^4/(384xEXI)
I	Moment of inertia
E	2.1*10^5
Stress	B.M*7.5/I

Permissible Deflection as per IS 800 L/250

SATISH M. GHANEKAR
LISCENCED STRUCTURAL ENGINEER
L. NO. 135 (PMC)
4, Sant Kripa Commercial Complex, Yamunanagar, Nigdi, Pune