HORIZON CHUTES PVT. LTD.
GAT NO 6B,PLOT NO 2, KASURDI KHE BA, SHIVAPUR-SASWAD,TAL -BHOR
PUNE - 412205
MAHARASHTRA INDIA

Ref . No.: **HCPL/U2/1218/SQ/0379** **Version:** **Date :** **05-12-2018**

To,

NIHVA TECHNOLOGIES PRIVATE LIMITED

8/1 Coromant Housing Society ,Sec No 27,
Nigdi Pradhikaran

Pune Maharashtra 411044 India

Subject: Offer for Fire Rated Door & General Purpose Door for Nihva Project

Kind Attention: Ms. Pratiksha

Dear Sir / Madam,

We are into manufacturing of different products which are enhancing the utility and safety in the built environment. Our metal fire doors are tested successfully at CBRI (Roorkee) & ARAI (Automotive Research Association of India), Pune laboratory, as per British Standard BS 476 (Part 20 & 22), 1987/ IS3614. We are manufacturing Fire doors in our State Of Art manufacturing unit by using CNC controlled machines to produce quality fire doors.

RELEASED

We are manufacturing & Supplying: -

1) Metal Fire Doors (60/120/240 Min).
2) Sliding Doors (120/240 Min).
3) Trap Doors (60/120/240 Min).
4) Glazed / Glass Fire Doors & Partitions (120 Min).
5) Blast Resistance Doors.

We are OEM for Promat Asia Pacific for manufacturing Wooden Fire Doors Glass Fire Doors, Sliding Doors, etc.

Thanking you and assuring our very best always,

For HORIZON CHUTES PVT.LTD.

1 - TECHNICAL SPECIFICATIONS

INPUT DATA BASIS OF DESIGN

TECHNICAL SPECIFICATIONS FOR DOORS:

1. Hardware Optional : Hardware such as Panic devices, External Devise, Mortise Locks, Cylinder Locks, Hydraulic Doors Closers, Concealed Tower bolts & Vision Panels can be used as per service requirements.

2. Hinges : SS Ball bearing hinges suitable for door thickness.

3. Finish : Powder Coating.

4. Infill : Rock wool

5. Type of Doors : Single leaf & Double leaf.

6. Material of Construction : Galvanized Steel.

A. FIRE RATED DOOR

1. Shutter : Thickness 46 mm manufactured in 1.2 mm thk. Sheet

2. Frame : Thickness 1.5 mm thk.sheet(Single Rabbet)

3. Fire rating : 120 Minute(2 Hours)for Integrity and stability.

4. Fire Doors tested according to : BS 476 part (20 & 22) tested at CBRE & ARAI (Automotive Research Association Of India)

RELEASED

B.NON FIRE RATED DOORS.

1.Shutter : Thickness 46 mm manufactured 0.8 mm thk.Sheet.

2. Frame : Thickness 1.2 mm thk.sheet(Single Rabbet).

2 - SCOPE OF SUPPLY

1.0 Complete Door set as per requirement along with required planned hardware.

Following is the list of exclusions from our scope

3 - EXCLUSIONS

1 All what so ever Civil Scope needed at site for erection of doors such as giving clear cut out in wall, Concrete filling in frames, etc.
2 Free Power connection at alternate floor for erection activities at site
3 Free Secured storage place for storage of materials before site erection at your site
4 Any other item not listed in our scope

6 - TERMS & CONDITIONS

1. Warranty - 1 Year against manufacturing defect on frames & doors. 1 year warranty against manufacturing on hardware as per OEM's terms.
2. Taxes as applicable during invoicing as per government regulation.
3. Disputes: All disputes arising under this contract shall be subject to the jurisdiction of the Pune courts only.
4. All pages of the quotation, terms and conditions shall be signed and enclosed as annexure to the purchase order released by you.
5. Required documents at the time of dispatch will be provided by you.
6. Transport, Mathadi, Unloading : Extra at actual is in your scope.

We hope that you will find our offer in line with your requirement and request you to please give us a chance to serve your organisation.

For **HORIZON CHUTES PVT. LTD.**

Dipali Dalvi

RELEASED

	Seal	For Horizon Chutes Pvt Ltd