ASSA ABLOY

# PROFORMA RECHNUNG/
# PROFORMA INVOICE

**ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt**

| | |
|---|---|
| NIHVA Technologies PVT LTD<br>27 8/1 Coromant Housing Society<br>411044 Pune, Nigdi Pradhikar<br>India | **Auftrags-Nr./Order No** 30815382<br>**Datum/Date** 2021-01-15<br>**Referenz/Reference** Mr. Kurhade<br>**Verkäufer/Salesman** |

| **Kunden-Nr./Customer No.** | **Innendienst/Internal department** | **Versandart/Way of delivery** |
|---|---|---|
| 1059669 | Olga Ziebart +49.2941.766. x 746 | Air |
| **Ihre Ust-ID Nr./Your TAX No** | **Ihre Bestell-Nr./Your Order** | **Versandbedingungen/Terms of delivery** |
| | NVA-507 | FCA / Stenovice incl.stand.packing / Forwarder (W) |

| **Lieferadresse/Delivery address** **Nr. Lieferadresse/Delivery address No.** | **Zahlungsbedingungen/Terms of payment** |
|---|---|
| NIHVA Technologies PVT LT1059669<br>27 8/1 Coromant Housing Society<br>411044 Pune, Nigdi Pradhikar<br>India | 810 EUR advance<br>20750 Due Net 90 |

| Pos.<br>item | Produkt<br>Product | Beschreibung<br>Description | Versanddatum<br>Ship date | Anzahl<br>QTY | Einheit<br>Unit | Preis/Einh.<br>Price/Unit | Preis<br>Price |
|---|---|---|---|---|---|---|---|
| 10 | AD_RP300 | ASSA ABLOY RP300 | 2021-02-08 | 1.000 | ST | 4,312.00 | 4,312.00 |

**Serien-Nr. 2620006959**

| | |
|---|---|
| Door type | High-speed roller door RapidProtect 300 |
| Daylight width | 1.800 mm |
| Daylight height | 2.000 mm |
| Door control system | MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit |
| Max. Opening Speed | 2,3 m/s |
| Max. Closing Speed | 1,7 m/s |
| Control box position | Mounted next to the drive unit |
| Control system position | Right |
| Motor Position | Right |
| Wind class | 1 |
| Side frame version | Aluminium |
| Bottom plate | Delivered without bottom plates |
| Bottom profile | Aluminium |
| Safety contact edge | Pre running photocell at the bottom profile |
| Photocell | With photocell |
| Crank | With crank for manual operation |
| Top roll material | Aluminum |
| Door curtain | RollTex Plus |
| Door curtain colour | Blue, similar to RAL 5002 |
| Silicone free | Silicone free |
| Window type | Window 700X500 mm, type anti UV |
| Window Quantity | 1 |
| Height:bott.edge to bott.prof. | 1.200 mm |



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

| Pos. item | Produkt Product | Beschreibung Description | Versanddatum Ship date | Anzahl QTY | Einheit Unit | Preis/Einh. Price/Unit | Preis Price |
|---|---|---|---|---|---|---|---|

| | |
|---|---|
| Motor cover | Motor cover powder coated standard |
| Top roll cover | Top roll cover made of aluminium |
| MCC type | Standard version |
| MCC display type | Display delivered separately, not mounted |
| Power supply | 400 V, 3-phase |
| Frequency | 50 Hz |
| Main switch | With main switch |
| Interface cable length | 3.000 mm |
| Mains connection cable length | 3.000 mm |
| Dry contact | Dry contacts for signal door open / closed and door in operation |
| Interface card | Interface card delivered separately, installation on site in the customer control box |
| Safety limit switch (MP) | Schmersal on 1 side with relay for cat. 4 |
| Cable marking | Including cable and component marking |
| Documentation language | English |
| Documenation door | English |
| Documentation control system | English |
| Wiring plan | English |
| MCC display language | English |
| CE - Sign | Yes |
| Warranty | 1 Year |
| Dimension packing 1 LxWxH | 2500X480X400 |
| Dimension packing 2 LxWxH | 800X600X370 |
| commodity code 39252000 | |

**20 AD_RP300 ASSA ABLOY RP300 2021-02-09 1.000 ST 4,312.00 4,312.00**

**Serien-Nr. 2620006960**

| | |
|---|---|
| Door type | High-speed roller door RapidProtect 300 |
| Daylight width | 1.800 mm |
| Daylight height | 2.000 mm |
| Door control system | MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit |
| Max. Opening Speed | 2,3 m/s |
| Max. Closing Speed | 1,7 m/s |
| Control box position | Mounted next to the drive unit |
| Control system position | Right |
| Motor Position | Right |
| Wind class | 1 |
| Side frame version | Aluminium |
| Bottom plate | Delivered without bottom plates |
| Bottom profile | Aluminium |
| Safety contact edge | Pre running photocell at the bottom profile |
| Photocell | With photocell |
| Crank | With crank for manual operation |
| Top roll material | Aluminum |
| Door curtain | RollTex Plus |
| Door curtain colour | Blue, similar to RAL 5002 |
| Silicone free | Silicone free |
| Window type | Window 700X500 mm, type anti UV |
| Window Quantity | 1 |
| Height:bott.edge to bott.prof. | 1.200 mm |
| Motor cover | Motor cover powder coated standard |
| Top roll cover | Top roll cover made of aluminium |
| MCC type | Standard version |
| MCC display type | Display delivered separately, not mounted |



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

| Pos. | Produkt | Beschreibung | Versanddatum | Anzahl | Einheit | Preis/Einh. | Preis |
|---|---|---|---|---|---|---|---|
| item | Product | Description | Ship date | QTY | Unit | Price/Unit | Price |

| | |
|---|---|
| Power supply | 400 V, 3-phase |
| Frequency | 50 Hz |
| Main switch | With main switch |
| Interface cable length | 3.000 mm |
| Mains connection cable length | 3.000 mm |
| Dry contact | Dry contacts for signal door open / closed and door in operation |
| Interface card | Interface card delivered separately, installation on site in the customer control box |
| Safety limit switch (MP) | Schmersal on 1 side with relay for cat. 4 |
| Cable marking | Including cable and component marking |
| Documentation language | English |
| Documenation door | English |
| Documentation control system | English |
| Wiring plan | English |
| MCC display language | English |
| CE - Sign | Yes |
| Warranty | 1 Year |
| Dimension packing 1 LxWxH | 2500X480X400 |
| Dimension packing 2 LxWxH | 800X600X370 |
| commodity code 39252000 | |

**30 AD_RP300 ASSA ABLOY RP300 2021-02-09 1.000 ST 4,312.00 4,312.00**

**Serien-Nr. 2620006961**

| | |
|---|---|
| Door type | High-speed roller door RapidProtect 300 |
| Daylight width | 1.800 mm |
| Daylight height | 2.000 mm |
| Door control system | MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit |
| Max. Opening Speed | 2,3 m/s |
| Max. Closing Speed | 1,7 m/s |
| Control box position | Mounted next to the drive unit |
| Control system position | Right |
| Motor Position | Right |
| Wind class | 1 |
| Side frame version | Aluminium |
| Bottom plate | Delivered without bottom plates |
| Bottom profile | Aluminium |
| Safety contact edge | Pre running photocell at the bottom profile |
| Photocell | With photocell |
| Crank | With crank for manual operation |
| Top roll material | Aluminum |
| Door curtain | RollTex Plus |
| Door curtain colour | Blue, similar to RAL 5002 |
| Silicone free | Silicone free |
| Window type | Window 700X500 mm, type anti UV |
| Window Quantity | 1 |
| Height:bott.edge to bott.prof. | 1.200 mm |
| Motor cover | Motor cover powder coated standard |
| Top roll cover | Top roll cover made of aluminium |
| MCC type | Standard version |
| MCC display type | Display delivered separately, not mounted |
| Power supply | 400 V, 3-phase |
| Frequency | 50 Hz |
| Main switch | With main switch |
| Interface cable length | 3.000 mm |



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

| Pos. / item | Produkt / Product | Beschreibung / Description | Versanddatum / Ship date | Anzahl / QTY | Einheit / Unit | Preis/Einh. / Price/Unit | Preis / Price |
|---|---|---|---|---|---|---|---|

| | |
|---|---|
| Mains connection cable length | 3.000 mm |
| Dry contact | Dry contacts for signal door open / closed and door in operation |
| Interface card | Interface card delivered separately, installation on site in the customer control box |
| Safety limit switch (MP) | Schmersal on 1 side with relay for cat. 4 |
| Cable marking | Including cable and component marking |
| Documentation language | English |
| Documenation door | English |
| Documentation control system | English |
| Wiring plan | English |
| MCC display language | English |
| CE - Sign | Yes |
| Warranty | 1 Year |
| Dimension packing 1 LxWxH | 2500X480X400 |
| Dimension packing 2 LxWxH | 800X600X370 |
| commodity code 39252000 | |

**40 AD_RP300 ASSA ABLOY RP300 2021-02-09 1.000 ST 4,312.00 4,312.00**

**Serien-Nr. 2620006962**

| | |
|---|---|
| Door type | High-speed roller door RapidProtect 300 |
| Daylight width | 1.800 mm |
| Daylight height | 2.000 mm |
| Door control system | MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit |
| Max. Opening Speed | 2,3 m/s |
| Max. Closing Speed | 1,7 m/s |
| Control box position | Mounted next to the drive unit |
| Control system position | Right |
| Motor Position | Right |
| Wind class | 1 |
| Side frame version | Aluminium |
| Bottom plate | Delivered without bottom plates |
| Bottom profile | Aluminium |
| Safety contact edge | Pre running photocell at the bottom profile |
| Photocell | With photocell |
| Crank | With crank for manual operation |
| Top roll material | Aluminum |
| Door curtain | RollTex Plus |
| Door curtain colour | Blue, similar to RAL 5002 |
| Silicone free | Silicone free |
| Window type | Window 700X500 mm, type anti UV |
| Window Quantity | 1 |
| Height:bott.edge to bott.prof. | 1.200 mm |
| Motor cover | Motor cover powder coated standard |
| Top roll cover | Top roll cover made of aluminium |
| MCC type | Standard version |
| MCC display type | Display delivered separately, not mounted |
| Power supply | 400 V, 3-phase |
| Frequency | 50 Hz |
| Main switch | With main switch |
| Interface cable length | 3.000 mm |
| Mains connection cable length | 3.000 mm |
| Dry contact | Dry contacts for signal door open / closed and door in operation |
| Interface card | Interface card delivered separately, installation on site in the customer control box |



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

| Pos. / item | Produkt / Product | Beschreibung / Description | Versanddatum / Ship date | Anzahl / QTY | Einheit / Unit | Preis/Einh. / Price/Unit | Preis / Price |
|---|---|---|---|---|---|---|---|

| | |
|---|---|
| Safety limit switch (MP) | Schmersal on 1 side with relay for cat. 4 |
| Cable marking | Including cable and component marking |
| Documentation language | English |
| Documenation door | English |
| Documentation control system | English |
| Wiring plan | English |
| MCC display language | English |
| CE - Sign | Yes |
| Warranty | 1 Year |
| Dimension packing 1 LxWxH | 2500X480X400 |
| Dimension packing 2 LxWxH | 800X600X370 |
| commodity code 39252000 | |

**50 AD_RP300 ASSA ABLOY RP300 2021-02-09 1.000 ST 4,312.00 4,312.00**

**Serien-Nr. 2620006963**

| | |
|---|---|
| Door type | High-speed roller door RapidProtect 300 |
| Daylight width | 1.800 mm |
| Daylight height | 2.000 mm |
| Door control system | MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit |
| Max. Opening Speed | 2,3 m/s |
| Max. Closing Speed | 1,7 m/s |
| Control box position | Mounted next to the drive unit |
| Control system position | Right |
| Motor Position | Right |
| Wind class | 1 |
| Side frame version | Aluminium |
| Bottom plate | Delivered without bottom plates |
| Bottom profile | Aluminium |
| Safety contact edge | Pre running photocell at the bottom profile |
| Photocell | With photocell |
| Crank | With crank for manual operation |
| Top roll material | Aluminum |
| Door curtain | RollTex Plus |
| Door curtain colour | Blue, similar to RAL 5002 |
| Silicone free | Silicone free |
| Window type | Window 700X500 mm, type anti UV |
| Window Quantity | 1 |
| Height:bott.edge to bott.prof. | 1.200 mm |
| Motor cover | Motor cover powder coated standard |
| Top roll cover | Top roll cover made of aluminium |
| MCC type | Standard version |
| MCC display type | Display delivered separately, not mounted |
| Power supply | 400 V, 3-phase |
| Frequency | 50 Hz |
| Main switch | With main switch |
| Interface cable length | 3.000 mm |
| Mains connection cable length | 3.000 mm |
| Dry contact | Dry contacts for signal door open / closed and door in operation |
| Interface card | Interface card delivered separately, installation on site in the customer control box |
| Safety limit switch (MP) | Schmersal on 1 side with relay for cat. 4 |
| Cable marking | Including cable and component marking |
| Documentation language | English |
| Documenation door | English |



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

ASSA ABLOY

| Pos. item | Produkt Product | Beschreibung Description | Versanddatum Ship date | Anzahl QTY | Einheit Unit | Preis/Einh. Price/Unit | Preis Price |
|---|---|---|---|---|---|---|---|

| | |
|---|---|
| Documentation control system | English |
| Wiring plan | English |
| MCC display language | English |
| CE - Sign | Yes |
| Warranty | 1 Year |
| Dimension packing 1 LxWxH | 2500X480X400 |
| Dimension packing 2 LxWxH | 800X600X370 |
| commodity code 39252000 | |

**Warenwert/Value of goods** **21,560.00**

**Summe/Total** **EUR** **21,560.00**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.



ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm