Technical Specifications For 200 mm - Traffic Light





No.	Item	Specifications	Compliances
1	**Brand**		**Nucleonics traffic equipmentts**
2	**Model**		**NTE10055**
3	**Technology**	LED based 5mm oval type	**Yes**
4	**Dimension**	280mm x 560mm x 350mm	**250mm x 475mm x 50mm**
5	**Led retrofit dia.**	200mm (±10%) full round	**200mm**
6	**Material and finishes**	Polypropylene/Polycarbonate /Mild Steel with black color powder coated with Sun visor	**Mild steel powder coated black texture color with sun visor**
7	**Aspect diameter**	200mm	**Yes**
8	**PCB**	Masking Pads- Tin plated Conformal coating for moisture protection	**Yes**
9	**Aspect Color**	Red and Yellow	**Yes**
10	**Type of signal**	Ball type	**Yes**

11	**Luminance**	Red-265cd	**Yes**
12	**Chain failure**	No chain failure of LED's.Failed LED will not work	**Failed LED with 7 LED's in series will not work**
13	**Wavelength**	Red - 625nm	**Yes**
14	**Aspect Color**	Red and Yellow	**Yes**
15	**Interface**	24V/AC switching from potential free devices	**Yes**
16	**Visibility**	>20mtrs	**>100 mtrs**
17	**Viewing Angle**	< 23 degrees	**23 degree**
18	**Cables**	Power Cable	**Yes**
19	**LED Type**	Super Bright Day visible	**Yes**
		12000 - 14000 mcd at 20 mA, 30˚ viewing angle for Red	**15000 to 20000mcd at 20ma , 23 degree standard viewing angle**
		21000 - 24000 mcd at 20 mA, 30˚ viewing angle for Yellow 96 Leds & 12 V	**21000 to 24000mcd at 20ma , 23 degree standard viewing angle**
20	**Weight**	<6 Kg	**3 Kg**
21	**Operating Voltage**	220-270VAc /50-60 Hz	**Yes**
22	**Power Consumption**	8 W max	**8 watts**
23	**Installation**	Bolting Arrangement to the Traffic Pole	**yes clamps and brackets wth hose clip to the traffc pole**
24	**Environment Conditions**	Operating Temp : -10°C to 60°C	**Yes**
		Humidity : 0 to 90%	**Yes**
25	**Reliability**	MBTF: 50,000 hours	**Yes**
		MTTR: 0.20 hrs	**Yes**
26	**Access For maintenance**	Front Door Access for Easy Maintenance	**Yes**
27	**Protection**	IP65	**Yes**
28	**Operating Temperature -**	5 ºC to 65 ºC	**Yes**
29	**Auto Diming**	Night Dimming facility available (optionally)	**No**