High Performance Door Rapid Roll® Clean (High Speed Door)



Door type	RR Clean	PL. indicate your Requirement
Description	Certified flexible high performance door, opening in vertical direction, certified for the use in cleanrooms. Compliant to the national norms and regulations in cleanroom applications according to DIN EN ISO 14644-1 and GMP Certified according to ISO 5 and GMP class C.	
Opening/closing speed	2.0 / 1.0 m/s	
Leakage	Max. 20m³/h at a pressure difference of 25 Pa, at a door size of 3 m²	
Self-supporting side frames made of stainless steel V2A	Self-supporting side frames max. DW 110 mm, motor and top roll cover with max. Lintel requirement of 410 mm, bottom profile.	
Door curtain	Made of PVC with vertical reinforcement stripes in white (similar RAL 9016).	
Control system incl. self-opening	Frequency converter control MCC^{VectorControl} with uninterrupted power supply (UPS) for continuous operation in case of power failure. UPS and MCC^{VectorControl} are installed under the top roll cover. Graphic display and foil keypad for easy operation installed on the drive side.	
Safety devices	Pre-running photocell, door line photocell integrated in the side frames, drop down protection in the drive unit	
Actuator	Integrated, contactless actuator	
Main switch	Integrated in the side frame on the drive side	
Drive unit	Gear motor, mountable left or right	
Supply voltage	3L/(N)PE 380/400/415/440/480V; 50/60 Hz	
Protection	IP 55	
Control voltage	24 V DC	
Make	ALBANY RapidRoll® Clean	
Delivery	Installation incl. wiring	