TORQUE

YUKEN

House Of Hydraulics

HOUSE OF HYDRAULICS



THPL

TARGET

HYDRAUTECH PVT. LTD.

Hydraulic Valves, Motors, Pumps,
AC / DC Compact Power Pack & Accessories

TORQUE

HYDRAULIC VALVES

Solenoid Directional Control Valve



MODEL : 4WE-6**-60/ERAC***N9K4
4WE-10**-60/ERAC***N9K4

Solenoid Directional Control Valve (pilot Operated)



Model: 4WE 16**- 60/ERACD**N9K4
4WE 20**- 60/ERACD**N9K4

Pressure Relief Valve



Model : DBW-** 1B1-50/200S

Pressure Relief Vlave



Model: DB-** 1-50/200S

Modular Valves



Model : TV-0**M, 4 TCV-0**M

Modular Valves



Model: BRV-0***M, RV-0***M

Proportional Electro-hydraulic Valve



Model No : EFBG-01/03/06 ***

Solenoid Coil



Model : Solenoid Coil AC 240 & DC 24 V

TORQUE

HYDRAULIC MOTORS

Orbital Hydraulic Motor : TMP



Volume : 50cc/rev to 400cc/rev
Max. Pressure : 140bar to 70 bar
Flow : 40 LPM to 60 LPM

This series motor is equivalent to Danfoss - OMP and M+S-MP

MODEL : TMP

Orbital Hydraulic Motor : TMR



Volume : 50cc/rev to 400cc/rev
Max. Pressure : 140bar to 70 bar
Flow : 40 LPM to 60 LPM

This series motor is equivalent to Danfoss - OMR and M+S-MR

MODEL : TMR

Orbital Hydraulic Motor : TMS



Volume : 80cc/rev to 400cc/rev
Max. Pressure : 175 bar to 70 bar
Flow : 65 LPM to 75 LPM

This series motor is equivalent to Danfoss - OMS and M+S - MS.

MODEL : TMS

Orbital Hydraulic Motor : TMT



Volume : 160cc/rev to 500cc/rev
Max. Pressure : 200bar to 160 bar
Flow : 100 LPM to 125 LPM

This series motor is equivalent to Danfoss - OMT and M+S-MT.

MODEL : TMT

Radial Piston Motors : TMDG



Series:-
TMDG1, TMDG-2, TMDG-3, TMDG-6, TMDG-11, TMDG-16, TMDG-31
Displacement:-
125cc/rev to 3500cc/rev
This motor is equivalent to SAI - GM series and Intermot NHM series

MODEL : TMDG

Sphere Piston Hydraulic Motor : QJM



QJM hydraulic motor that can constitute a hydraulic actuator with different oil pumps, valves and hydraulic parts is able to adapt itself to all kinds of mechanical conditions by reason of some measures taken to its design. The motor has many advantages, e.g. light weight, small size, widespeed regulating range, capable of stepping variation, reliable performance and long useful life, etc. It has been widely applied for mine engineering,hoisting transport, metallurgy, ships, plastics injection, etc.

MODEL : QJM

Hydraulic Steering Unit



Hydraulic steering control units(SCU), new design, better performance. Widely applied to low speed and heavy load vehicles E.g. construction machinary, forklift, tractor, harvester and helm control etc.

MODEL : THPL OSPB, OSPC, OSPJ

Hydraulic Transmission : ZCM



ZCM hydraulic transmission is made up of hydraulic motor, multi-disc friction braker and planet gearbox decelerator, Having Characteristics of small, light, large torque, high start and transmission efficiency, low noise, etc. Output shaft can bear large radial force. ZCM1600/B(C)-ZCM6000/B(C) is hydraulic transmission with one grade planet decelerating, two grade decelerating be applied in ZCMZ.3/B-ZCM2.6/B series,they also constitute of all the part mentioned-Above and valve group with braking function, etc.
Hydraulic transmission can he applied in kinds of hydraulic transmission system and rotating facilities.

MODEL : ZCM

TORQUE

HYDRAULIC PUMPS

PISTON PUMPS : THPL 'A' SERIES



A series variable displacement piston pumps has high efficiency, lower noise and accomplishment energy-saving characteristic and so widely used in plastic injection machinery, pressure founding machinery, tools machinery, chemical and light industry field and so on. It has two kinds of control type, which are pressure compensatory - pe ("01" type) and proportional electro-Hydraulic load sensing type("04"type).

MODEL : A37,45,56,70,96
(FR - 01 & FR - 04)

PISTON PUMPS : THPL 'AR' SERIES



- Compact and minimum weight design
- Low-Carbon Steel Structure
- For normal pressure 160 kgf/cm^2, max. pressure 210 kgf/cm^2
- Available for motor connection directly

Model : AR10.AR16.AR22

VARIABLE DISPLACEMENT PUMP



Variable displacement Axial Piston Pump Swash plate design in single, double and triple pump execution.

CC / rew : 28,45,71,100,140

Nominal Pressure PN : 280
Peack Pressure Pmax : 350

MODEL : THPL - A10VSO

FIXED DISPLACEMENT BENT AXIS PISTON PUMP.



CC/rev : 16,23,28,32,45, 56,63,80,90,107, 125, 160, 180

Nominal Pressure up to 450 bar
Nominal Pressure up to 400bar

Model : THPL - A2F0

VARIABLE DISPLACEMENT PUMP



Pump THPL A4VSO of swash plate design is design for hydrostatic transmission in open circuit.
Flow is proportional to input speed and displacement, and is infinitely variable by adjustment of the swash plate.

Feature:
slot-control swash plate design, continuous variable displacement, good suction characteristics, permissible continuous operating pressure 350bar, low noise level, long service life, the drive shaft capable of absorbing the axial and radial loads, high power/weight ratio, modular design, the pump combinations possible, pump position optional, mounting position optional, operation on HFC fluids under reduced operational parameter possible in prepare!!

MODEL : THPL - A4VSO

VARIABLE DISPLACEMENT PUMP / MOTOR



Variable displacement motor AV is design for hydrostatic drive. The displacement of infinitely variable in the range Vmax / Vmin = 3.47.

Special features :
Wide control range of hydrostatic drives. Various control regulating devices. Cost saving through elimination of gear box and possibility of using smaller pumps, compact low until power. Good starting characteristics. Low inertia.

Model : THPL - A6V

VARIABLE VANE PUMP



Flow:-
VP-12-70 – 12LPM
VP-20-70 – 20LPM
VP30-70- 30LPM
VP-40-70-40 LPM
Pressure:- 70 Bar

MODEL NO:- TVP SERIES

VANE PUMP (VICKERS)



Pump & Cartridge
20V- (8-10-12-14)
25V- (12-14-17-21)
35V – (25-30-35-38)
45V – (42-45-50-60)
Double pump also available

MODEL NO:- 20V, 25V, 35V, 45V

TORQUE

POWER PACK

DC POWER UNIT 12V



Voltage Rating	: 12V
Power Rating	: 1.6kw
Pump Option	: 1.00cc/2.00cc/ 3.3.cc/4.2cc 5.8cc/7.00cc/ 9.00cc
Manifold Option	: Single Acting / Double Acting
Tank Option	: 8L, 15L, 25L

DC POWER UNIT 24 V



Voltage Rating	: 24V
Power Rating	: 2.2kw
Pump Option	: 1.00cc/2.00cc/ 3.3.cc/ 4.2 cc/ 5.8cc/7.00cc/ 9.00cc
Manifold Option	: Single Acting / Double Acting
Tank Option	: 8L, 15L, 25L

PUMP MOTOR UNIT - 12V & 24V



Voltage Rating	: 12 v & 24 V
Power Rating	: 1.6 KW 2.2 KW

DC POWER UNIT 3 KW



Voltage Rating	: 24 v
Power Rating	: 3.0 KW
Pump Option	: 1.00cc/2.00cc/ 3.3.cc/ 4.2 cc/ 5.8cc/7.00cc/ 9.00cc
Manifold Option	: Single Acting /
Tank Option	: 25L, 35 L

AC POWER UNIT (FOR MATERIAL HANDLING EQUIPMENTS)



Voltage Rating	: 230V & 440V
Power Rating	: 1H.P, 2H.P, 3 H.P & 5 H.P
Pump Option	: 1.00cc/2.00cc/ 3.3.cc/ 4.2 cc/ 5.8cc/7.00cc/ 9.00cc
Manifold Option	: Single Acting / Double Acting
Tank Option	: 8L, 15L, 25L

AC POWER UNIT (FOR HEAVEY DUTY WORK)



Voltage Rating	: 230V & 440V
Power Rating	: 1H.P, 2H.P, 3 H.P & 5 H.P
Pump Option	: 1.00cc/2.00cc/ 3.3.cc/ 4.2 cc/ 5.8cc/7.00cc/ 9.00cc
Manifold Option	: Single Acting / Double Acting
Tank Option	: 8L, 15L, 25L

LIFT VALVE BLOCK



Flow:- 20 LPM
Pressure:- 200bar
Coil Voltage:- AC 220V
DC 12V, 24V
Check valve, Relief valve, Flow Control valve & Solenoid valve

MODEL NO:- LKT-20

CAR PARKING BLOCK



Poppet type Double Check Type Solenoid Valve...
Flow:- 30 LPM
Pressure:- 200bar
Coil Voltage:- AC 220V
DC 12V, 24V

TORQUE

MOBILE HYDRAULIC

Directional Control Valve : P - 40



Technical Parameters :

Ambient Temperature	:	40C....+60C
Hydraulic liquid-mineral oil based/hydraulic oil viscosity	:	12..800 mm2/s
FluidTemperature	:	15C....+80C
Filtration	:	10toNAS1638
Max. operating pressure, P=250; T=50 bar	:	A, B = 300 bar
Leakage (A, B-T)	:	15cm3/minat 120bar
Nominal Flow	:	40 l/min.
Spool stroke	:	6mm
Actuating Force	:	<200N
Modification/Spools :		with 1 to 7

Directional Control Valve : P - 80



Technical Parameters :

Ambient Temperature	:	-40C....+60C
Hydraulic liquid-mineral oil based/hydraulic oil viscosity	:	12..800 mm2/s
FluidTemperature	:	-15C....+80C
Filtration	:	10toNAS1638
Max. operating pressure, P=250; T=50 bar	:	A, B = 300 bar
Leakage (A, B-T)	:	18cm3/minat 120bar
Nominal Flow	:	80 l/min.
Spool stroke	:	+/- 7mm
Actuating Force	:	<200N
Modification/Spools :		with 1 to 6

SECTIONAL TYPE DIRECTION CONTROL VALVE



Technical parameters:

Ambient temperature	:	8C...+60C
Hydraulic liquid-mineral oil based/hydraulic oil Viscosity	:	12..800 mm2/s
Fluid temperatur	:	15C...+80CMax
operating pressure. P=250; T=50 bar	:	A , B = 300 bar
Leakage	:	18cm3/min at 120bar
Nominal flow	:	70 l/min
Spool stroke	:	+/- 7 mm
Actuating force	:	< 200N
Modification/Sections	:	up to 8

SOLENOID CONTROL SECTIONAL AND MONOBLOCK VALVES



Technical parameters:

Modification / Spools	: with 1 to 7
Nominal flow	: 50 l/m
Internal leakage A(B)-T,P=100 bar viscosity 35 cSt	: max 18 ccm/min
Spools , Schemes	: Spool A ; D
Spool Stroke	: 3.2 mm
Coils , connector ISO 4400	: 12VDC,24VDC
Threads P.T - G1/2,SAE 10	: A,B-G3/8, SAE 8

Hand Pump

TORQUE



PRB - 12 : 12CC / Stroke
PRB - 18 : 18CC / Stroke
PRB - 25 : 25CC / Stroke

HOSE BRUST VALVE



VUBA ¼" (20lpm flow)
VUBA 3/8" (50lpm flow)
VUBA 1/2" (80lpm flow)
VUBA ¾" (140lpm flow)
VUBA 1" (180lpm flow)
Pressure:- 350 Bar

MODEL NO:- VUBA

JOYSTICK



We have Joystick available for Badestnost P40 Series, P80 Series

ACCESSORIES



We have Lever Cap Assembly, detent kit for Badestnost (P40 & P80 Series)

YUKEN

HYDRAULIC VALVES

DIRECTIONAL CONTROL VALVES



Directional control valves can be used for controlling direction of oil flow so as to operate start up, stop and moving direction of actuators in a hydraulic circuit. Their operating modes are solenoid controlled, solenoid operated and pilot controlled, pilot controlled, manual controlled, cam - actuated and so on.

MODEL : DSG 01 & 03
DSHG 04, 06, 10

PRESSURE CONTROL VALVES



Pressure control valves are used for controlling the pressure in a hydraulic system and protect its hydraulic pump and actuators from over-load. Accordingly to their functions, they can be divided into different types such as relief valve, pressure reducing valves, sequence valve and unloading relief valve.

MODEL : BG, BSG, BT, BST, HCG, RCG, BUCG, RG.
SIZE : 03, 06 & 10

MODULAR VALVES



Yuken series modular valves are one kind of valves without pipe connecting, which can meet the requirement of modern hydraulic system in diversity and reasonable design.

They have mounting faces which meet with international standards (ISO 46601) and have proper body thickness. According to requirements for control of a hydraulic system, single modules with different types of modular valve with mounting screws.

MODEL : MSW, MRP, MBP, MRA, MPW
SIZE : 01, 03 & 06

LOGIC VALVES



Logic valves comprise cartridge elements and covers with pilot passages. They are suitable in the hydraulic system with high pressure, high flow rate and low pressure drop. Application of the valves can implement quick shifting and shockless movements of hydraulic system.

MODEL : LB, LD & LDS
SIZE : 16,25,32,40,50,60,63

PROPORTIONAL ELECTRO - HYDRAULIC VALVES



These valves are one kind of controllers which control pressure or flow rate continuously vary in proportion with electric input signal. They are typical mechanical, electrical and hydraulic integral products.

MODEL : EFBG, 03, 06 & 10
EFG 01

FLOW CONTROL VALVES



Flow control valves can be used for controlling revolving or reciprocating speed of actuators in a hydraulic circuit. These valves are pressure and temperature compensating type and can maintain a constant flow rate independent of change in system pressure (load) and temperature (viscosity of the fluid)

MODEL : FG, FCG, SRCT, ZCG
SIZE : 01,02,03 & 06

(MANUALLY OPERATED) DIRECTIONAL VALVE



Manually Operated Directional ValvesThese valves may be used to manually shift the spool position and change the direction of oil flow.We keep running stock DMG-01, DMG-03 & DMG-06 size

MODEL : DMG
SIZE : 01,03 & 06

(CAM OPERATED) DIRECTIONAL CONTROL VALVE



Cam Operated Directional Valves These valves may be used to shift the direction of oil flow by depressing the spool by way of a cam.

MODEL : DCG
SIZE : 01 & 03

TORQUE

CARTRIDGE VALVES

SOLENOID VALVE – SINGLE CHECK TYPE



Flow:- 20lpm
Pressure:- 250bar
Coil Voltage:- AC 220V
DC 12V, 24V

MODEL NO:- SCA

SOLENOID VALVE – DOUBLE CHECK TYPE



Flow:- 20lpm
Pressure:- 250bar
Coil Voltage:- AC 220V
DC 12V, 24V

MODEL NO:- D SCA

SOLENOID VALVE – 3 WAY 4 POSITION



Flow:- 12lpm, 22lpm
Pressure:- 200 Bar
Coil Voltage:- AC 220V
DC 12V, 24V

MODEL NO:- LSV-08 (12LPM)
LSV-10 (22LPM)

CHECK VALVE



Size:- 12,14, 18
Flow:- 22, 50,80 lpm
Pressure:- 350bar

MODEL NO:- CV2000 – G14 (22LPM)
CV2000 – G38 (50LPM)
CV2000 – G12 (80LPM)

FLOW CONTROL VALVE



Flow:- 9, 20,30,80
Pressure:- 250bar

MODEL NO:-LNV-08 (9 LPM)
LNV-10 (45LPM)
LNV-12 (116 LPM)

PILOT OPERATED CHECK VALVE



Flow:- 20,30,60
Pressure:- 350bar

MODEL NO:- LPC

RELIEF VALVE

MODEL NO:-LNRV-08 (30 LPM) 350 BAR
RV-03 (20 LPM) 200 BAR

PRESSURE COMPENSATED FLOW CONTROL VALVE

Fix Type IFC-6T (10LPM)
Adjustable LMR-10 (50 LPM)

TORQUE

FALCON

FLOW CONTROL VALVE – INLINE TYPE



Flow:- 12 to 300 lpm
Pressure:- 350 Bar

MODEL NO:- FRV

FLOW CONTROL VALVE – SUBPLATE TYPE



Flow:- 6 to 300 lpm
Pressure:- 350 Bar

MODEL NO:- FRVP

CHECK VALVE – INLINE TYPE



Flow:- 12 to 400 lpm
Pressure:- 350bar

MODEL NO:- FCV

CHECK VALVE– SUBPLATE TYPE



Flow:- 12 to 280 lpm
Pressure:- 350 Bar

MODEL NO:- FCVP

SHUTI OFF VALVE – INLINE TYPE



Flow:- 20 to 250 lpm
Pressure:- 350 Bar

MODEL NO:- FSV

SHUTI OFF VALVE – SUBPLATE TYPE



Flow:- 20 to 250 lpm
Pressure:- 350 Bar

MODEL NO:- FSVP

NEEDLE VALVE



Flow:- 06 to 65 lpm
Pressure:- 350 Bar

MODEL NO:- FNV

BALL VALVE



Flow:- 30 to 500 lpm
Pressure:- 350 Bar

MODEL NO:- FBV

TORQUE

POLYHYDRON

RADIAL PISTON PUMP
OPEN EXECUTION & CLOSE EXECUTION



Elements :- 2,3 & 5
Flow:- 1 to 13 lpm

MODEL NO:- IR & IRC SERIES

PRESSURE CONTROL MODULE



MODEL NO:- PCM 06-06
PCM 10-06
PCM 20-06
PCM 20-10

RELIEF VALVE



Type:- Subplate and Inline Type

MODEL NO:- DPRH-06
DPRH-10
DPRH-20

CHECK VALVE



MODEL NO:- CV-10
CV-20
CV-30
POCV-10
POCV-20
POCV-30

PRESSURE SWITCH



MODEL NO:-IPSW-50
IPSW-100
IPSW-200
IPSW-315

MODULAR VALVE



MODEL NO:- TCM-06 AB
TCM-10 AB
CIM-06 AB
CIM-10 AB

PREFILL VALVE



MODEL NO:-PV-40
PV-50

HAND LEVER VALVE



MODEL NO:- 4DCVL-10-SGS
4DCVL-10-SGD
4DCVL-10-SCS

TORQUE

HYDRAULIC ACCESSORIES

BELL HOUSING



OIL LEVEL INDICATOR



GEAR COUPLING



FILLER BREATHER



SUCTION STAINER



MANIFOLD BLOCK



RETURN LINE FILTER



PRESSURE GAUGE



TARGET HYDRAUTECH PVT. LTD.

House Of Hydraulics


AMTEX-2014


RMTS-2014


AMTEX-2015


VASAI EXPO-2016


RMTS-2016


HITEX-2016


PLAST INDIA-2015


PLAST ASIA-2016


BAUMA-2016


PLASTVISION 2017

OUR PREVIOUS PARTICIPATION

House Of Hydraulics

PRODUCT RANGE

- Solenoid and Modular Valves.
- Proportional & Relief Valves.
- Hydraulic Motors : Radial Piston & Oribital.
- Variable Displacement Axial Piston Pump.
- Fixed Displacement Axial Piston Pump.
- D.C. Compact Power Pack 12 V & 24 V.
- A.C. Power Pack 1 HP to 5 HP.
- A.C. & D.C. Car Lift Block.
- Gear Pump
- "Torque" Mobile Control Valve.
- Power Pack & Accessories.



THPL

TARGET
HYDRAUTECH PVT. LTD.

UNIT NO.112, VASUNDHARA INDUSTRIAL ESTATE,
K.T PARK PHASE 1, Nr ARROW INDUSTRIES, GORAIPADA,
VASAI (E) PIN-401208, MUMBAI (MAHARASHTRA)
Mobile : +91-8080750080, 8080869456
E-mail : sales@targethyd.com Web : www.targethydraulic.com

Branches :
AHMEDABAD : 8905138811 • RAJKOT : 8080139929