TECHNICAL DESCRIPTION:

Door Type Horizontal Sliding Door (Chiller and freezer application)

Door Blade: 0.6 mm galvanized steel – PVC-coated - Food safe available in the following colors:

- White
- Red
- Blue

(other colours are available however not as food safe).

Thickness: - 60 mm, 100 mm , 120 mm and 150 mm

Insulation: - High insulating, polythan - free foam

Frame: - 0.6 mm PPGI and 1.2 mm Alu.

Insulation: - The frame is always insulated.

Sliding Rails: - Anodized aluminium.

Rollers: - The rollers are made of POM (nylon). The roller brackets, the stud bolt, the washer and the nuts are made of stainless steel.

Recess: - The sliding rail is supplied with recess blocks to ensure hermetic closing towards frame and floor.

Gaskets: - Rubber quality approved for use in the food industry. The gaskets are fitted into anodized aluminium profiles.

Handles: -

Face side:	If manual - Solid stainless steel DAN-doors handle fitted on edge of door blade. If automatic – Bow handle
Rear side:	Flush fitted stainless steel handle in a nylon holder manual as well as automatic.

Bottom Guide:	-	The bottom guide rail and the bottom guides are manufactured in salt water resistant anodized aluminium. The bottom guides are supplied with solid nylon bushes.
Min/ Max size		1 leaf: W x H: 1000 x 2000 / W: 3200 x 3600 2 leaf: W x H: 1600 x 2000 / W: 6000 x 3600

When larger or smaller doors are required, please contact Hicon doors sales dept.

FREEZER DOORS :

Heating Arrangement:	-	Supplied with heating cables in both frame/threshold and door blade. The threshold which is manufactured of anodized aluminium is to be placed into the floor. Alternatively, the door can be supplied without a threshold, if supplied with extra heating at bottom of the door blade. The heating cables on the door blade are fitted into aluminium profiles with the gaskets. The heating cables are terminated in a connection box for connection to a 230 V / 50 Hz supply (Connection to other voltage is possible.) Power consumption per meter for this heating cable is approx 30 W.
Remark	-	Heating in the floor around the door is always recommended.

ADDITIONAL EQUIPMENT:

Locks: - Cylinder lock with emergency opening device in black PEHD 1000 nylon and stainless steel. Heating in locks for freezer doors.
(To be locked from face side or rear side.)

Padlock fitting with or without emergency opening device in black PEHD1000 nylon and stainless steel.(To be locked from face or rear side)

Window: - Standard sizes:

- 150 x 300 mm
- 400 x 600 mm
- 500 x 600 mm

(Only for chill room doors)

Frame: - Available in anodized aluminium

Window: - Min. 2-layer thermo glass

Sliding Rail: - Special Anodized alu.

Automation: - Can be supplied with tooth belt automation.

(Further information to be found in the paragraph about automation for sliding doors)

Sliding Rail Protection: - Identical to door blade

Emergency Hatch/Door: - Hatch standard size : 600 x 1000 mm
- Door standard size : 800 x 1800 mm

Kick Plates: - Door width x height 300 mm (standard)

or

Door width x height 800 mm (max)

Blast Freeze: - Freezer room doors can be manufactured as blast freezer doors.