NIHVA
NIHVA TECHNOLOGIES PVT. LTD.





NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Hermetically Sealed
SLIDING DOORS







Reliable, Innovative, Robust, Durable Doors

HERMETIC DOORS USED IN THE **MEDICAL FIELD**







SPECIFICATIONS

Track	:	High grade aluminum extrusion profile to carry any door weight (till size 3000mm X 2400mm) with deep indentations to ensure perfect hermetic sealing.
Canopy	:	For HPCL Door:- Powder coated galvanized sheet over the full length of track with sloping top and closing caps.
Door Blade	:	Door core of 60mm thick built up with:- - For HPCL:- 4mm thick HPCL (High Pressure Compact Laminate) skin at both side of the door to provide better strength and rigidity. - Chloro Fluoro Carbon (CFC) free, high density polyurethane puff (density 40 kg/m3), thickness 52mm to provide better insulation.
Door Profile	:	Door core is surrounded by 2.5 mm thick high grade aluminum extrusion profiles with natural anodizing of 15 microns finish. The aero-dynamic design of profiles makes the door DURABLE & ROBUST in its segment league.
Gaskets	:	Door blade is made with 3-tier specially designed 3 side heavy duty replaceable EPDM gasket against wall frame. Bottom sealing with 2-tier heavy duty EPDM gasket to flush with finished floor.
Opener	:	Stainless Steel Hermed lever handle on both side of the door blade for smooth and easy door opening and closing OR for small door outside D-grip handle and inside flush grip.
Vision Glass	:	High Quality double glazed flush vision window of 350mm X 350mm view size. Both sides flush with the door blade.
Wall Frame	:	High grade Aluminum extrusion with natural anodized 15 micron finish wall frame profile. This wall frame profile is 3-sided blind fixed with cladding on wall cut-out section from inside and outside of the room.
Cladding	:	The cut-out of wall section is covered with 1mm thick high pressure laminate glued on 9mm high density particle board.
Acoustic	:	Sound reducing door up to 28db.
Operation	:	Door can be open/close manually.
Weight	:	Complete door blade weight is 60 Kg approx; plank & track assembly is 60 Kg.
Sliding	:	Door can be open to Right Hand Side OR Left Hand Slide.

APPLICATION AREAS

- Operation Theaters
- Intensive Care Units (ICU)
- Laboratories
- Sterile Rooms
- Pediatric Wards
- Quarantine Areas
- Lobbies
- X-Ray Rooms
- Fluoroscopy Rooms
- Radio Therapy Rooms
- Mammography Rooms
- Rooms with Radiation Equipments Inside



SUPERIORITY

The latest design in the industry with added benefits

3-tier sealing on all three sides and 2-tier sealing on bottom side ensure complete hermetic sealing from all four sides

Hermetic sealing maintain quick positive pressure, required inside the O.T.

Less number of air exchange required with hermetic Door

High quality Aluminum anodizing and better quality of HPCL with stand high abrasion during cleaning and sterilization of O.T.

The hermetic door prevents air-turbulence which ensure required sterile environment inside the O.T.

Self lubricating high quality nylon wheels, confirms no noise during door operation

3-D door movement during closing and 2-D wheel chair adjustment ensure perfect door sealing and better adjustment tolerances

New aesthetic and flush designing help easy cleaning

Stop cold smoke spreading in case of fire, which gives more time to evacuate

Easy and smooth opening with lever handle

Better door weight load distribution on installation wall

Convenient for trolley, wheel chair and heavy equipments movement inside/outside the O.T.



OPTIONS AVILABLE

Manual Operations

Vision glass customized sizes over and above than standard(350x350mm) size

Mechanical Lock

Door handle types i.e. Special MED1 type Lever, D-Grip, Flush-Grip

Door blade with wide range of colors Choice

Door blade color matching with inside and outside the O.T

Canopy in PCGI, Stainless Steel



NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Hermetically Sealed
SLIDING DOORS



Analysing the Global requirement of
reliable, cost efficient and robust
Medical Doors

NIHVA
NIHVA TECHNOLOGIES PVT. LTD.