TENDER SPECIFICATION	ASSA ABLOY

High-performance door Nihva-Albany RR300

Description:

Flexible High-performance door, opening in vertical direction for interior use in wind-protected areas.

Self-supporting side frames made of galvanized steel, all fittings galvanised.

Door curtain made of transparent PVC material with coated fabric reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar to RAL 3002).

Top roll made of aluminium.

Wind protection: through wind tabs on the door curtain.

Wind resistance: class 1 (EN 12424).

Bottom profile: anodized aluminium.

Drive unit: Hollow shaft gear motor.

Protection: IP 55

Control system: ACS 50, electric control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC

Supply voltage:
ACS 50: 3L/(N)PE 220/230/380/400/415V; 50Hz
Transformer necessary for 440/480/500V

Safety devices: electrical safety contact edge, door line photocell, drop down protection integrated in gear box.

Manual activation: by means of a crank.

Opening / closing speed: up to max. 1.0 / 1.0 m/s.

Size max.: (DWxDH) 3500 x 3500 mm

Make: Albany RR300

Options

Surface / material:
side frame made of stainless steel
Control box made of stainless steel V2A - IP 65
Top roll / shafts made of stainless steel V2A
Bottom profile made of stainless steel V2A

Covers:
Top roll cover
Motor cover

Door curtain (alternatively):

- PVC with coloured reinforcement stripes
  Beige (similar RAL 1014),
  Yellow (similar RAL 1021),
  Orange (similar RAL 2011),
  Green (similar RAL 6018),
  white (similar RAL 9016) or
  grey (similar RAL 7035)

- PVC with silicone-free reinforcement stripes

- Curtain made of non-transparent fabric, type travitop
  Blue (similar RAL 5010)
  red (similar RAL 3002) or
  grey(similar RAL 7035)
  only available without curtain tension

- vision panels for door curtain type travitop

- Curtain made of RollTex® Plus – colour
  Blue (similar RAL 5002)
  Orange (similar RAL 2009) or
  Grey (similar RAL 7001)

- Curtain made of RollTex® Original – colour
  Blue (similar RAL 5002)
  Orange (similar RAL 2009) or
  Grey (similar RAL 7001)

- Curtain made of NomaTex® – colour grey (similar RAL 7038)

- Window (DWxDH) 500x700mm (only for RollTex® or NomaTex®)
- Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®)

- Curtain made of NomaTex® flame retardent, without vision panels or window - colour grey

(similar RAL 7045)

Control system (alternatively)
ASC 25 (open/close) up to max. 0,8 m/s,
Supply voltage 3L(N)PE/220/230/380/400/415V;50Hz,
Transformer necessary for 440/480/500V 50/60 Hz

Frequency converter control system MCCVectorControl, based on vector control including boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information regarding operation and service, (open/close) up to max. 2.3/1,0 m/s,
Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz,
Transformer necessary for 220/230/500V, 50/60 Hz

Miscellaneous:
Knock-out capability with sensor
Extended flexible seal
Actuators
Additional safety devices

Alternatively:
Version ”Mini” for reduced space requirements over the lintel
DWxDH up to 2000 x 3000 mm, Wind resistance class 0 (EN 12424),
due to limited weight of door curtain no drop down protection required)

Delivery:

Installation incl. wiring