
DRAWING



TECHNICAL SPECIFICATION :

SR.	SPECIFICATIONS	DETAILS
1	USE	INTERNAL DOOR
2	MOUNTING	ON STRUCTURE: INSIDE
3	CURTAIN PANEL	PVC FABRIC THICKNESS 1.2 MM.
4	MANUAL RELEASE	CRANK HANDLE
5	DOOR TRAVEL SPEED	OPENING: UPTO 1.5M/SEC & CLOSING: 0.8 M/SEC
6	RAL CODE	BLUE

HIGH SPEED ROLL UP DOOR SIZES :-

SR	CLEAR WIDTH (CW)	CLEAR HEIGHT (CH)	QTY
1	**800**	**1000**	03

NOTE : All DIMENSIONS ARE IN MM.

SPECIAL INSTRUCTION'S :

This drawing & design is the property of NIHVA TECHNOLOGIES. Not to be sold or copied to any other concern.

TITLE - DOOR AUTOMATION

DWG NO - NTPL-301-PM-01

NIHVA TECHNOLOGIES PVT.LTD.PUNE
Website - www.nihva.com

	NAME	SIGNATURE	DATE
DRAWN	J.P.		06-11-2025
CHK'D	B.S.		07-11-2025
APPV'D	V.T.		07-11-2025

IF ANY QUERIES CONTACT - Design@nihva.com

ALL DIMENSIONS ARE IN 'MM' | A2

PRODUCT - HIGH SPEED DOOR

PROJECT NO - NTPL- 301 | REVISION - 00

SITE LOCATION - WARGAL | WEIGHT -

MATERIAL - | QTY - 3

PROJECTION METHOD | SCALE :

SHEET 1 OF 1