TECHNICAL SPECIFICATIONS OF MODEL GX 200 D

Tender Enquiry Item Serial Nos. 6, 7, 8, 10, 11, 12, 13 & 15

(1) Make / Model of Forklift Truck Offered :

Godrej 2.0 Tonne Diesel Forklift Truck Model GX 200 D of capacity 2000 kg at 500 mm Load Centre, 1000 mm long Forks, Single Drive, Pneumatic / Solid Tyres (please specify), 4 Stroke Diesel Engine, 2 Speed Forward / 2 Speed Reverse Automatic Hydrodynamic Transmission(***) or Fluid Coupling Transmission, Hydraulic Brakes, Heavy Duty Air Filter, Horn, Driver's Overhead Guard, Head Lights, Tail Lights, Signal Lights, Rear View Mirror, Light Reflectors, Rear Towing Arrangement, Standard Tool Kit and Consumables as per list attached.

(2) Capacity at 500 mm load centre with load elevated & mast vertical for both, Automatic Transmission and Fluid Coupling Transmission

Mast		MFH (mm)	FL (mm)	OAHL (mm)	OAHR (mm)	Capacity (kg)
2-Stage Clear View Mast		3660	105	2630*	4400	2000
		4500	105	3100	5350	1500
3-Stage Clear View Mast	**	4500	1530	2150	5100	1500
	#	5500	1825	2480	6100	1300

* OAHL of 2360 mm can be made available on request

** Capacity with Dual Drive is 1700 kg

*** Inching Control, if required, will be provided free of cost on FLTs fitted with Automatic Transmission

Only available with Dual Drive (Item Serial No. 74). Dual Drive is mandatory for Item Serial Nos. 9, 10, 14 & 15.

(3) Overall Dimensions (in mm)

(a) Height : For both, Automatic & Fluid Coupling Transmission

(i) Maximum Fork Height (See "MFH" in Chart above)

(ii) Free Lift (See "FL" in Chart above)

(iii) Overall Height Lowered (See "OAHL" in Chart above)

(iv) Overall Height Raised (See "OAHR" in Chart above)

(b)

(i) Overall Width

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	1210 mm	1210 mm
Dual	1650 mm	1650 mm

(ii) Wheel Track – Front

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	990 mm	990 mm
Dual	1490 mm	1490 mm

(iii) Overall Length (with 1000 mm long forks)

Automatic Transmission	Fluid Coupling Transmission
3580 mm	3580 mm

(iv) Wheel Base

Automatic Transmission	Fluid Coupling Transmission
1620 mm	1620 mm

(v) Minimum Ground Clearance

Automatic Transmission	Fluid Coupling Transmission
110 mm	110 mm

(4) Fork Dimensions

Forks	Drive	Automatic Transmission	Fluid Coupling Transmission
Length of Forks	Single / Dual	1000 mm	1000 mm
Fork Spread	Single	Adjustable Upto 970 mm	Adjustable Upto 970 mm
	Dual	Adjustable Upto 1475 mm	Adjustable Upto 1475 mm

(5) Mast Tilt (in degrees)

Tilt	MFH	Automatic Transmission	Fluid Coupling Transmission
Forward	Upto 3660 mm	5	6
	Over 3660 mm	4	4
Backward	Upto 3660 mm	10	12
	Over 3660 mm	6	6

(6) Speed & Gradient

(a) Speed (Laden)

Speed	Automatic Transmission	Fluid Coupling Transmission
Maximum Speed (Forward / Reverse)	18 / 18 kmph	18 / 18 kmph
Number of Speeds (Forward / Reverse)	2 / 2	2 / 2

(b) Maximum Gradient (Laden) (%)

Tyres	Automatic Transmission	Fluid Coupling Transmission
Pneumatic	28	15
Solid Cushion	28	15

(c) Maximum Gradient (Unladen) (%)

Tyres	Automatic Transmission	Fluid Coupling Transmission
Pneumatic	28	15
Solid Cushion	28	15

(d) Lifting Speeds

Mast	Automatic Transmission	Fluid Coupling Transmission
2 Stage Clear View Mast	0.50 m/sec	0.50 m/sec
3 Stage Clear View Mast with FFL	0.45 m/sec	0.45 m/sec

(e) Lowering Speeds

Mast	Automatic Transmission	Fluid Coupling Transmission
2 Stage Clear View Mast	0.50 m/sec	0.50 m/sec
3 Stage Clear View Mast with FFL	0.50 m/sec	0.50 m/sec

(7) Outer Turning Radius

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	2460 mm	2460 mm
Dual	2500 mm	2500 mm

(8) Brakes (For both, Automatic Transmission & Fluid Coupling Transmission)

Service Brakes	Foot Operated, Hydraulically Operated
Parking Brakes	Hand Operated, Hydraulically Operated

(9) Type & Size of Tyres
(For both Automatic & Fluid Coupling Transmission and also for Single & Dual Drive)

Tyres		Size
Pneumatic	Front	7.00 x 12 x 12 PR
	Rear	6.50 x 10 x 10 PR
Solid Cushion	Front	7.00 x 12
	Rear	6.50 x 10

(10) Prime Mover – For Both Automatic Transmission & Fluid Coupling Transmission

Engine	Suitable 4-Stroke Diesel Engine
Rated Power	35.79 kw at 2200 rpm
Method of Cooling	Radiator Water Cooled
Method of Starting Engine	Electric Starting (Battery & Alternator Fitted)

TECHNICAL SPECIFICATIONS OF MODEL GX 300 D

Tender Enquiry Item Serial Nos. 21, 22, 24, 25, 26, 27, 28 & 30

(1) Make / Model of Forklift Truck Offered :

Godrej 3.0 Tonne Diesel Forklift Truck Model GX 300 D of capacity 3000 kg at 500 mm Load Centre, 1000 mm long Forks, Single Drive, Pneumatic / Solid Tyres (please specify), 4 Stroke Diesel Engine, 2 Speed Forward / 2 Speed Reverse Automatic Hydrodynamic Transmission(***) or Fluid Coupling Transmission, Hydraulic Brakes, Heavy Duty Air Filter, Horn, Driver's Overhead Guard, Head Lights, Tail Lights, Signal Lights, Rear View Mirror, Light Reflectors, Rear Towing Arrangement, Standard Tool Kit and Consumables as per list attached.

(2) Capacity at 500 mm load centre with load elevated & mast vertical for both, Automatic Transmission and Fluid Coupling Transmission

Mast		MFH (mm)	FL (mm)	OAHL (mm)	OAHR (mm)	Capacity (kg)
2-Stage Clear View Mast		3660	105	2630*	4410	3000
		4500	105	3100	5350	2600
3-Stage Clear View Mast	**	4500	1530	2150	5100	2750
	#	5500	1825	2480	6100	2500

* OAHL of 2360 mm can be made available on request

** Capacity with Dual Drive is 3000 kg

*** Inching Control, if required, will be provided free of cost on FLTs fitted with Automatic Transmission

Only available with Dual Drive (Item Serial No. 74). Dual Drive is mandatory for Item Serial Nos. 23, 24, 29 & 30.

(3) Overall Dimensions (in mm)

(a) Height : For both, Automatic & Fluid Coupling Transmission

(i) Maximum Fork Height (See "MFH" in Chart above)

(ii) Free Lift (See "FL" in Chart above)

(iii) Overall Height Lowered (See "OAHL" in Chart above)

(iv) Overall Height Raised (See "OAHR" in Chart above)

(b)

(i) Overall Width

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	1210 mm	1210 mm
Dual	1650 mm	1650 mm

(ii) Wheel Track – Front

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	1025 mm	1025 mm
Dual	1490 mm	1490 mm

(iii) Overall Length (with 1000 mm long forks)

Automatic Transmission	Fluid Coupling Transmission
3700 mm	3700 mm

(iv) Wheel Base

Automatic Transmission	Fluid Coupling Transmission
1700 mm	1700 mm

(v) Minimum Ground Clearance

Automatic Transmission	Fluid Coupling Transmission
110 mm	110 mm

(4) Fork Dimensions

Forks	Drive	Automatic Transmission	Fluid Coupling Transmission
Length of Forks	Single / Dual	1000 mm	1000 mm
Fork Spread	Single	Adjustable Upto 970 mm	Adjustable Upto 970 mm
	Dual	Adjustable Upto 1475 mm	Adjustable Upto 1475 mm

(5) Mast Tilt (in degrees)

Tilt	MFH	Automatic Transmission	Fluid Coupling Transmission
Forward	Upto 3660 mm	5	6
	Over 3660 mm	4	4
Backward	Upto 3660 mm	10	12
	Over 3660 mm	6	6

(6) Speed & Gradient

(a) Speed (Laden)

Speed	Automatic Transmission	Fluid Coupling Transmission
Maximum Speed (Forward / Reverse)	18 / 18 kmph	18 / 18 kmph
Number of Speeds (Forward / Reverse)	2 / 2	2 / 2

(b) Maximum Gradient (Laden) (%)

Tyres	Automatic Transmission	Fluid Coupling Transmission
Pneumatic	28	15
Solid Cushion	28	15

(c) Maximum Gradient (Unladen) (%)

Tyres	Automatic Transmission	Fluid Coupling Transmission
Pneumatic	28	15
Solid Cushion	28	15

(d) Lifting Speeds

Mast	Automatic Transmission	Fluid Coupling Transmission
2 Stage Clear View Mast	0.50 m/sec	0.50 m/sec
3 Stage Clear View Mast with FFL	0.45 m/sec	0.45 m/sec

(e) Lowering Speeds

Mast	Automatic Transmission	Fluid Coupling Transmission
2 Stage Clear View Mast	0.50 m/sec	0.50 m/sec
3 Stage Clear View Mast with FFL	0.50 m/sec	0.50 m/sec

(7) Outer Turning Radius

Drive	Automatic Transmission	Fluid Coupling Transmission
Single	2500 mm	2500 mm
Dual	2600 mm	2600 mm

(8) Brakes (For both, Automatic Transmission & Fluid Coupling Transmission)

Service Brakes	Foot Operated, Hydraulically Operated
Parking Brakes	Hand Operated, Hydraulically Operated

(9) Type & Size of Tyres
(For both Automatic & Fluid Coupling Transmission)

Tyres		Single Drive	Dual Drive
Pneumatic	Front	8.15 x 15 x 14 PR	7.00 x 12 x 12 PR
	Rear	6.50 x 10 x 10 PR	6.50 x 10 x 10 PR
Solid Cushion	Front	7.00 x 12	7.00 x 12
	Rear	6.50 x 10	6.50 x 10

(10) Prime Mover – For Both Automatic Transmission & Fluid Coupling Transmission

Engine	Suitable 4-Stroke Diesel Engine
Rated Power	35.79 kw at 2200 rpm
Method of Cooling	Radiator Water Cooled
Method of Starting Engine	Electric Starting (Battery & Alternator Fitted)

TECHNICAL SPECIFICATIONS OF MODEL G 100 E

Tender Enquiry Item Serial Nos. 86 & 87

(1) Make / Model of Forklift Truck Offered :

Godrej 1.0 Tonne Electric Forklift Truck Model G 100 E of capacity 1000 kg at 500 mm Load Centre, 1000 mm long Forks, MOSFET Electronic Control, Single Drive, Hydraulic Brakes, Solid Tyres(*) including Traction Battery, Battery Charger, Horn, Driver's Overhead Guard, Head Lights, Tail Light, Signal Lights, Rear View Mirror, Light Reflectors and Standard Tool Kit

(*) Only Solid Tyres will be provided on Electric Forklift Trucks at no extra cost

(2) Capacity at 500 mm load centre with load elevated & mast vertical

Mast	MFH (mm)	FL (mm)	OAHL (mm)	OAHR (mm)	Capacity (kg)
2-Stage Clear View Mast	3660	105	2500	3950	1000
	4500	105	3000	5200	950

(3) Overall Dimensions (in mm)

(a) Height :

(i) Maximum Fork Height (See "MFH" in Chart above)

(ii) Free Lift (See "FL" in Chart above)

(iii) Overall Height Lowered (See "OAHL" in Chart above)

(iv) Overall Height Raised (See "OAHR" in Chart above)

(b)

(i) Overall Width : 945 mm

(ii) Wheel Track – Front : 805 mm

(iii) Overall Length (with 1000 mm long forks) : 2700 mm

(iv) Wheel Base : 930 mm

(v) Minimum Ground Clearance : 75 mm

(4) Fork Dimensions

(a) Length of Forks : 1000 mm

(b) Fork Spread : Adjustable Upto 825 mm

(5) Mast Tilt (in degrees)

Tilt	MFH	Deg
Forward	Upto 3660 mm	3
	Over 3660 mm	2
Backward	Upto 3660 mm	10
	Over 3660 mm	5

(6) Speed (Laden)

(a) Maximum Speed (Forward / Reverse) : 7 kmph

(b) Number of Speeds (Forward / Reverse) : Stepless – Infinite Electronic Control

(c) Maximum Gradient (Laden / Unladen) : 13% Over Limited Distance

(d) Lifting Speed :
For 2 Stage : 0.23 m/sec
For 3 Stage : 0.18 m/sec

(e) Lowering Speed (For 2 Stage / 3 Stage) : 0.40 m/sec

(7) Outer Turning Radius : 1665 mm

(8) Type of Brakes

Service Brakes	Foot Operated, Hydraulically Operated
Parking Brakes	Seat Operated, Mechanically Operated

(9) Type & Size of Tyres

Solid Tyres	Size
Front	16 x 6 x 11.5
Rear	13 x 4.5 x 8

(10) Prime Mover

Drive Motor Specifications	Ventilated DC Series Motor rated at 36 V, 2.7 kw @ 1100 rpm
Battery Rated Capacity	36 V / 455 AH Rated at 5 Hours continuous rate of discharge
Battery Charger to charge the above Battery	Works on 400 / 440 V, 3 Phase, 50 Hz AC Supply

TECHNICAL SPECIFICATIONS OF MODEL GX 200 E

Tender Enquiry Item Serial Nos. 88, 89, 90, 91 & 92

(1) Make / Model of Forklift Truck Offered :

Godrej 2.0 Tonne Electric Forklift Truck Model GX 200 E of capacity 2000 kg at 500 mm Load Centre, 1000 mm long Forks, MOSFET Electronic Control, Single Drive, Hydraulic Brakes, Solid Tyres(*) including Traction Battery, Battery Charger, Horn, Driver's Overhead Guard, Head Lights, Tail Lights, Signal Lights, Rear View Mirror, Light Reflectors and Standard Tool Kit

(#) Only Solid Tyres will be provided on Electric Forklift Trucks at no extra cost

(2) Capacity at 500 mm load centre with load elevated & mast vertical

Mast	MFH (mm)	FL (mm)	OAHL (mm)	OAHR (mm)	Capacity (kg)
2-Stage Clear View Mast	3660	105	2630#	4400	2000
	4500	105	3100	5350	1600
	5500	105	3550	6250	1300
3-Stage Clear View Mast	4500	1530	2150	5100	1600
	5500	1825	2480	6100	1300

OAHL of 2360 mm can be made available on request

(3) Overall Dimensions (in mm)

(a) Height :

(i) Maximum Fork Height (See "MFH" in Chart above)

(ii) Free Lift (See "FL" in Chart above)

(iii) Overall Height Lowered (See "OAHL" in Chart above)

(iv) Overall Height Raised (See "OAHR" in Chart above)

(b)

(i) Overall Width : 1170 mm

(ii) Wheel Track – Front : 960 mm

(iii) Overall Length (with 1000 mm long forks) : 3050 mm

(iv) Wheel Base : 1225 mm

(v) Minimum Ground Clearance : 130 mm

(4) Fork Dimensions

(a) Length of Forks : 1000 mm

(b) Fork Spread : Adjustable Upto 965 mm

(5) Mast Tilt (in degrees)

Tilt	MFH	Deg
Forward	Upto 3660 mm	5
	Over 3660 mm	2
Backward	Upto 3660 mm	10
	Over 3660 mm	5

(6) Speed (Laden)

(a) Maximum Speed (Forward / Reverse) : 9 kmph

(b) Number of Speeds (Forward / Reverse) : Stepless – Infinite Electronic Control

(c) Maximum Gradient (Laden / Unladen) : 15% Over Limited Distance

(d) Lifting Speed (For 2 Stage / 3 Stage) : 0.20 m/sec

(e) Lowering Speed (For 2 Stage / 3 Stage) : 0.45 m/sec

(7) Outer Turning Radius : 2100 mm

(8) Type of Brakes

Service Brakes	Foot Operated, Hydraulically Operated
Parking Brakes	Hand Operated, Hydraulically Operated

(9) Type & Size of Tyres

Solid Tyres	Size
Front	21 x 7 x 15
Rear	18 x 7 x 8

(10) Prime Mover

Drive Motor Specifications	Ventilated DC SEPEX Motor rated at 48 V, 8.5 KW @ 1450 rpm
Battery Rated Capacity	48 V / 455 AH Rated at 5 Hours continuous rate of discharge
Battery Charger to charge the above Battery	Works on 400 / 440 V, 3 Phase, 50 Hz AC Supply

TECHNICAL SPECIFICATIONS OF MODEL GX 300 E

Tender Enquiry Item Serial Nos. 93, 94, 95, 96 & 97

(1) Make / Model of Forklift Truck Offered :

Godrej 3.0 Tonne Electric Forklift Truck Model GX 300 E of capacity 3000 kg at 500 mm Load Centre, 1000 mm long Forks, MOSFET Electronic Control, Single Drive, Hydraulic Brakes, Solid Tyres(*) including Traction Battery, Battery Charger, Horn, Driver's Overhead Guard, Head Lights, Tail Lights, Signal Lights, Rear View Mirror, Light Reflectors and Standard Tool Kit

(*) Only Solid Tyres will be provided on Electric Forklift Trucks at no extra cost

(2) Capacity at 500 mm load centre with load elevated & mast vertical

Mast	MFH (mm)	FL (mm)	OAHL (mm)	OAHR (mm)	Capacity (kg)
2-Stage Clear View Mast	3660	105	2630#	4400	3000
	4500	105	3100	5350	2500
	5500	105	3550	6250	2000
3-Stage Clear View Mast	4500	1530	2150	5100	2500
	5500	1825	2480	6100	2000

OAHL of 2360 mm can be made available on request

(3) Overall Dimensions (in mm)

(a) Height :

(i) Maximum Fork Height (See "MFH" in Chart above)

(ii) Free Lift (See "FL" in Chart above)

(iii) Overall Height Lowered (See "OAHL" in Chart above)

(iv) Overall Height Raised (See "OAHR" in Chart above)

(b)

(i) Overall Width : 1170 mm

(ii) Wheel Track – Front : 960 mm

(iii) Overall Length (with 1000 mm long forks) : 3360 mm

(iv) Wheel Base : 1310 mm

(v) Minimum Ground Clearance : 105 mm

(4) Fork Dimensions

(a) Length of Forks : 1000 mm

(b) Fork Spread : Adjustable Upto 965 mm

(5) Mast Tilt (in degrees)

Tilt	MFH	Deg
Forward	Upto 3660 mm	5
	Over 3660 mm	2
Backward	Upto 3660 mm	10
	Over 3660 mm	5

(6) Speed (Laden)

(a) Maximum Speed (Forward / Reverse) : 9 kmph

(b) Number of Speeds (Forward / Reverse) : Stepless – Infinite Electronic Control

(c) Maximum Gradient (Laden / Unladen) : 15% Over Limited Distance

(d) Lifting Speed (For 2 Stage / 3 Stage) : 0.16 m/sec

(e) Lowering Speed (For 2 Stage / 3 Stage) : 0.45 m/sec

(7) Outer Turning Radius : 2250 mm

(8) Type of Brakes

Service Brakes	Foot Operated, Hydraulically Operated
Parking Brakes	Hand Operated, Hydraulically Operated

(9) Type & Size of Tyres

Solid Tyres	Size
Front	21 x 7 x 15
Rear	18 x 7 x 8

(10) Prime Mover

Drive Motor Specifications	Ventilated DC SEPEX Motor rated at 48 V, 11 KW @ 1450 rpm
Battery Rated Capacity	48 V / 550 AH Rated at 5 Hours continuous rate of discharge
Battery Charger to charge the above Battery	Works on 400 / 440 V, 3 Phase, 50 Hz AC Supply