3. Technical data
Rolling door drives

Type		WF. 170/14	DF. 100/90	DF. 170/12,5	DF. 250/12,5	DF. 250/27	DF. 350/13,5	DF. 500/11	DF. 500/31	DF. 750/8	DF. 750/11
Rated voltage	V	230	3 ~ 230/400								
Rated frequency	Hz	50									
Rated current	A	6,7	5,5/3,2	3,2/1,85	4,5/2,6	5,2/3,0	4,2/2,4	5,7/3,3	10/6,0	5,9/3,4	6,9/4,0
cos φ		0,92	0,8	0,58	0,45	0,8	0,6	0,74	0,8	0,6	0,68
Insulation class		H									
Rated power consumption	kW	1,4	1,25	0,75	0,80	1,1	1,0	1,7	2,2	1,4	1,9
Rated torque[5])	Nm	170	100	170	250	250	350	500	500	750	750
Degree of protection	IP	54									
Rated operating time	S3	4 min	40%	60%	40%	40%	40%	60%	60%	40%	40%
Max. torque for rolling door operation[3)]											
RTB 80%	Nm	–	80	170	200	200	300	500	500	600	650
RTB 100%	Nm	–	60	150	170	170	250	400	400	500	550
Coil temperature limiter	C°/F°	130/266									
Door cycles per hour[4)]	$\frac{1}{1}$ h^{-1}	10	60	35	30	45	34	28	50	20	24
Permitted temperature range	C°/F°	–10 °C to +40° C/14 °F to 104 °F									
Continuous sound pressure level	db (A)	< 70	< 60								
Electromagnetic brake		●	●			●	●	●	●	●	●
Rated speed n2	min^{-1}	14	90	12,5	12,5	27	13,5	11	31	8	11
Mechanical limit switch range[2)] (centrally set at 9 revs.)	$\frac{1}{1}$	18 revs.									
Hollow shaft inside ø	mm	30						40			
Key width	mm	8						12			
Integrated safety brake	Type	F 40						F 80			
Stop torque	Nm	884						2302			
Deceleration	g	< 1,5						< 2,0			
TÜV SÜD certificate no.:	TorFV	5/061						5/062			
VDE checked				●	●		●	●			●
VDE-EMC			●	●	●	●	●	●			●
Drive weight	approx. kg	19	22	21	21	21	22	31	31	34	31

Note: If the drive is to be painted subsequently, then the shaft seals must remain free of paint.
Other voltages and frequencies upon request.

2) Only for three-phase motors, custom manufactured
Limit switch range 44 revolutions.
Designation: with additional D..**X**; only for cable application, etc.

3) **Rolling door operation RTB:** Rolling door drives with rolling doors are operated dynamically with load change.
The S 3 operating mode with intermittent duty in accordance with DIN EN is tested at the rated torque related to 10 minutes operating time with the defined duty cycle in %.

4) One door cycle is: 5 revolutions OPEN – 30 s pause – CLOSE.

5) The rated torques of the drives are guaranteed from -20 °C to 60 °C / -4 °F to 140 °F.

Correction table for three-phase mains power supply with frequency of 60 Hz

Motor designed for 50 Hz and	Operated with 60 Hz mains and	Speeds are increased by ...%	Rated torque and door weights are reduced by ....%.
3 ~ 230 V	230 V	20 %	23 %
3 ~ 400 V	400 V	20 %	20 %
	415 V	20 %	17 %
	440 V	20 %	12 %
	460 V	20 %	7 %