WORK ORDER

NIHVA TECHNOLOGIES PVT. LTD.

Client:	
Address:	

PO Number:	MAE/ 74/21-22	W. O. No-	SO/21-22/0133
PO Dated :	14-03-2022	W. O. Date	16-03-2022
PO Received Date:	14-03-2022	Sales Co ordinator	Shailesh
Ref. Quotation:	SQA.21.22.0487R1	Front Sales Person	VT

SO no - NTPL-202-SO

Contact Details		**Billing Address:**	**Dispatch Address:**
Contact Person:			John Deere India Pvt Ltd, SanaswadiTal-Shirur, Dist-Pune, Pin – 412208
Email ID of contact Person:			
Mobile No:			

A Technical Terms:

Sr. No	Description of Goods	Technical Details	UOM	Qty.	Supply Rate	Installation Rate	Total Amount	Dwg. Approval Status
1	Gear Operated Single Skin Rolling Shutter Width 4500 mm X Height 3670 mm	Sheet 2	Nos	1		0	0	Pending
						Total	0	

Non standard items/extra requirement, if any:	

B Commerical Terms:

1	**Payment Terms:**	50% Advance on Supply Basic Value B) 50% after Material at site C) Installation Part - After Installation		
2A	**Delivery Date as per PO:**	8 - 9 weeks from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.	**2B. Required Delivery Date:**	
3A	**Transportation Scope:**	In NIHVA Scope	**3B. Transportation Charges:**	
4	**P&F Charges:**	NIL		
5A	**Loading Scope:**	In NIHVA Scope	**5B. Loading Charges:**	
6A	**Unloading Scope:**	In Client Scope	**6B. Unloading Charges:**	
7A	**Lifting Equipments Scope:**	In Client Scope	**7B. Available Lifting Equipments:**	
8	**Warranty:**	12 Months from date of Supply		
9A	**Height arrangement Scope:**	In Client Scope	**9B. Available Equipments for working at Site:**	
10	**Electricity Supply:**	In Client Scope		
11	**GST:**	18%		
12A	**Installation Scope:**	In NIHVA Scope	**12B. Installation required date:**	
13	**Mode of import:**	NA		
14	**HSS:**	NA		
15	**Documentation Required:**	Standard Handover Documents		
16A	**Total site visits required:**		**16B. Site visit charges:**	

Certified that the above work order finalised in presence of:

GM	AGM	SALES		Operation	PROJECT	DESIGN	Date & Time
VT	AK	SB		PM	SM	GP	17-03-2022

Gear Operated Rolling Shutter

Sr .No.	Specification	MS Gear Operated Rolling Shutter
1	**Description**	Gear Operated Rolling Shutter with MS slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete
4	**Curtain Panel**	The panel made of 1.0mm thick MS.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
10	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm GF mm
11	**Surface finish**	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide-based enamel finish of approved color and
12	**Operation**	Gear Assembly.